

---

**emod-api**

**Institute for Disease Modeling**

**May 04, 2021**



# CONTENTS

|          |                            |           |
|----------|----------------------------|-----------|
| <b>1</b> | <b>emod_api</b>            | <b>3</b>  |
| 1.1      | emod_api package . . . . . | 3         |
| 1.1.1    | Subpackages . . . . .      | 3         |
| 1.1.2    | Submodules . . . . .       | 36        |
| <b>2</b> | <b>Glossary</b>            | <b>39</b> |
|          | <b>Python Module Index</b> | <b>41</b> |
|          | <b>Index</b>               | <b>43</b> |



EMOD-API is the interface for Epidemiological MODeling software (EMOD) that users of idmttools interact with to create and modify EMOD simulations. Additional functionality for interacting with EMOD is provided in the [emodpy](#) and [idmttools](#) packages.



## EMOD\_API

## 1.1 emod\_api package

**To generate a config.json from a param\_overrides.json (or params-of-interest.json):** python -m emod\_api.config.from\_overrides </path/to/po.json>

**To generate a default config.json based on the schema for a given Eradication binary:** python -m emod\_api.config.from\_schema -e </path/to/Eradiation.[exe]> ...

**To generate a schema.json:** python -m emod\_api.schema.get\_schema </path/to/Eradiation[.exe]>

For rest of emod-api documentation, please go to <https://github.com/InstituteForDiseaseModeling/emod-api>

### 1.1.1 Subpackages

#### emod\_api.channelreports package

##### Submodules

#### emod\_api.channelreports.channels module

Module for reading InsetChart.json channels.

```
class emod_api.channelreports.channels.Header (**kwargs)
    Bases: object

    property num_channels
    property dtk_version
    property time_stamp
    property report_type
    property report_version
    property step_size
        >= 1
    property start_time
        >= 0
    property num_time_steps
        >= 1
    as_dictionary() → dict
```

```
class emod_api.channelreports.channels.Channel (title, units, data)
    Bases: object

    property title
    property units
    property data
    as_dictionary() → dict

class emod_api.channelreports.channels.ChannelReport (filename: str = None, **kwargs)
    Bases: object

    property header
    property dtk_version
    property time_stamp
    property report_type
    property report_version
        major.minor
    property step_size
        >= 1
    property start_time
        >= 0
    property num_time_steps
        > 0
    property num_channels
    property channel_names
    property channels
        Channel objects keyed on channel name/title
    as_dataframe()
    write_file (filename: str, indent: int = 0, separators=',', ':')
        Write inset chart to specified text file.
```

## emod\_api.config package

### Submodules

#### emod\_api.config.default\_from\_schema module

`emod_api.config.default_from_schema.write_default_from_schema` (*path\_to\_schema*)  
This module is deprecated. Please use `default_from_schema_no_validation`.



## emod\_api.config.default\_from\_schema\_no\_validation module

emod\_api.config.default\_from\_schema\_no\_validation.**schema\_to\_config\_subnode** (*schema\_path\_in*,  
*subnode\_list*)

This is the code from regular schema\_to\_config:

```
config = json.load(open("default_config.json"), object_hook=s2c.ReadOnlyDict) os.remove( "de-  

fault_config.json" )
```

emod\_api.config.default\_from\_schema\_no\_validation.**write\_default\_from\_schema** (*path\_to\_schema*,  
*schema\_node=True*)

This very simple function takes a DTK schema json file and creates a default config.json file. It's as good as the schema it's given. Note that this is designed to work with a schema from a disease-specific build, otherwise it may contain a lot of params from other disease types.

emod\_api.config.default\_from\_schema\_no\_validation.**load\_default\_config\_as\_rod** (*config*)

**Parameters** *config* (*string/path*) – path to default or base config.json

**Returns** config (as ReadOnlyDict) with schema ready for schema-verified param sets.

emod\_api.config.default\_from\_schema\_no\_validation.**get\_config\_from\_default\_and\_params** (*config*,  
*set\_fn*)

Use this function to create a valid config.json file from a schema-derived base config, a callback that sets your parameters of interest, and an output path.

**Parameters**

- **config\_path** (*string/path*) – Path to valid config.json
- **set\_fn** (*function*) – Callback that sets params with implicit schema enforcement.

**Returns** dict

**Return type** config

emod\_api.config.default\_from\_schema\_no\_validation.**write\_config\_from\_default\_and\_params** (*config*,  
*set\_fn*,  
*config\_out\_path*)

Use this function to create a valid config.json file from a schema-derived base config, a callback that sets your parameters of interest, and an output path.

**Parameters**

- **config\_path** (*string/path*) – Path to valid config.json
- **set\_fn** (*function*) – Callback that sets params with implicit schema enforcement.
- **config\_out\_path** – (string/path) Path to write new config.json

**Returns** Nothing

**emod\_api.config.dtk\_post\_process\_adhocevents module**

`emod_api.config.dtk_post_process_adhocevents.application(output_path)`

**emod\_api.config.dtk\_pre\_process\_adhocevents module**

`emod_api.config.dtk_pre_process_adhocevents.do_mapping_from_events(config, ad-  
hoc_events)`

Given a config file, a campaign file, and a list of `ad_hoc_events`, do the mappings. The `ad_hoc_event` list originally came from scraping an existing campaign file but now comes from `emod_api.campaign`.

`emod_api.config.dtk_pre_process_adhocevents.application(config)`

This is the public interface function to the submodule.

**emod\_api.config.dtk\_pre\_process\_w5ml module**

`emod_api.config.dtk_pre_process_w5ml.application(filename)`

**emod\_api.config.from\_overrides module**

`emod_api.config.from_overrides.flattenConfig(configjson_path,  
new_config_name='config.json')`

Historically called ‘flattening’ but really a function that takes a parameter override json config that includes a `Default_Config_Path` and produces a `config.json` from the two.

**emod\_api.config.from\_poi\_and\_binary module**

`emod_api.config.from_poi_and_binary.schema_to_config(schema_path_in)`

Purpose: Take a `schema.json` and return a “smart” config object that can be assigned to with schema-enforcement. Use in conjunction with `to_file()`. Params: `schema_path_in` (str/path) Returns: config (smart dict)

`emod_api.config.from_poi_and_binary.set_schema(schema_path_in)`

`emod_api.config.from_poi_and_binary.make_config_from_poi_and_config_dict(start_config_dict,  
poi_set_param_fn)`

Use this function to create a `config.json` from an existing param dict (defaults or base) and a function with your parameter overrides or parameters of interest.

`emod_api.config.from_poi_and_binary.make_config_from_poi_and_config_file(start_config_path,  
poi_set_param_fn)`

Use this function to create a `config.json` from an existing config json file (defaults or base) and a function with your parameter overrides or parameters of interest.

`emod_api.config.from_poi_and_binary.make_config_from_poi_and_schema(schema_path,  
poi_set_param_fn)`

Use this function to create a `config.json` from an existing schema json file and a function with your parameter overrides or parameters of interest.

`emod_api.config.from_poi_and_binary.make_config_from_poi(eradication_path,  
poi_set_param_fn)`

This function uses `emod_api` to produce a guaranteed working config starting with an Eradication binary and a parameters-of-interest python function. This is a usable and useful function.

## Parameters

- **eradication\_path** (*string*) – Fully-qualified path to Eradication binary that can be invoked to get a schema.
- **poi\_set\_param\_fn** (*function*) – User-provided function/callback/hook that looks like:
- **set\_params** (*def*) – `config.parameters.<param_name> = <schema valid param_value>`  
 <repeat for each param> return config

**Returns** Hardcoded configuration filename written to pwd.

**Return type** “config.json” (string)

## emod\_api.config.from\_schema module

argparse for command-line usage -s schema file -m model name -c config file

**Sample code:** `from emod_api.config import schema_to_config as s2c builder = s2c.SchemaConfigBuilder()  
 builder.enumerate_params() builder.validate_dependent_params() builder.write_config_file()`

That will look for a local file called schema.json and produce a file called config.json that should work with an Eradication binary that produced the schema.json.

**To build a default config for MALARIA\_SIM, do:** `builder = s2c.SchemaConfigBuilder(model="MALARIA_SIM")`

To generate a schema.json file from a binary, see help text for `emod_api.schema`.

```
class emod_api.config.from_schema.SchemaConfigBuilder (schema_name='schema.json',
                                                         model='GENERIC_SIM',
                                                         config_out='config.json',
                                                         debug=False)
```

Bases: `object`

## emod\_api.config.schema\_to\_config module

```
class emod_api.config.schema_to_config.SchemaConfigBuilder (schema_name='schema.json',
                                                             model='GENERIC_SIM',
                                                             con-
                                                             fig_out='config.json',
                                                             debug=False)
```

Bases: `emod_api.config.from_schema.SchemaConfigBuilder`

Deprecated in API v.1. Supported temporarily as pass-through functionality to `emod_api.config.from_schema`.

## emod\_api.demographics package

### Submodules

## emod\_api.demographics.BaseInputFile module

```
class emod_api.demographics.BaseInputFile.BaseInputFile (idref)
    Bases: object
    abstract generate_file (name)
```

**generate\_headers** (*extra=None*)

## emod\_api.demographics.Demographics module

`emod_api.demographics.Demographics.from_template_node` (*lat=0, lon=0, pop=1000000.0, name='Erewhon', forced\_id=1*)

This function creates a single-node Demographics instance from the params you give it.

`emod_api.demographics.Demographics.from_file` (*base\_file*)

`emod_api.demographics.Demographics.get_node_ids_from_file` (*demographics\_file*)

`emod_api.demographics.Demographics.get_node_pops_from_params` (*tot\_pop, num\_nodes, frac\_rural*)

`emod_api.demographics.Demographics.from_params` (*tot\_pop=1000000.0, num\_nodes=100, frac\_rural=0.3, id\_ref='from\_params'*)

This function creates an EMOD-compatible Demographics object with the population and number of nodes specified, distributing per the additional parameters.

`emod_api.demographics.Demographics.from_csv` (*input\_file, res=0.008333333333333333*)

This function uses a csv population-by-node file to create an EMOD-compatible Demographics object.

`emod_api.demographics.Demographics.from_pop_csv` (*pop\_filename\_in, pop\_filename\_out='spatial\_gridded\_pop\_dir', site='No\_Site'*)

**class** `emod_api.demographics.Demographics.Demographics` (*nodes, idref='Gridded world grump2.5arcmin', base\_file=None*)

Bases: `emod_api.demographics.BaseInputFile.BaseInputFile`

This class is a container of data necessary to produce a EMOD-valid demographics input file. It can be initialized from an existing valid demographics.json type file or from an array of valid Nodes.

**generate\_file** (*name='demographics.json'*)

**property** `node_ids`

**property** `node_count`

**get\_node** (*nodeid*)

Return the node identified by nodeid. Search either name or actual id :param nodeid: :return:

**SetIndividualAttributesWithFertMort** (*CrudeBirthRate=0.04, CrudeMortRate=0.02*)

**AddIndividualPropertyAndHINT** (*Property, Values, InitialDistribution=None, TransmissionMatrix=None*)

This function takes the HINT configuration json, which are presumed to be correct, and inserts them into the right place in the demographics json structure.

**AddAgeDependentTransmission** (*Age\_Bin\_Edges\_In\_Years=[0, 1, 2, - 1], TransmissionMatrix=[[1.0, 1.0, 1.0], [1.0, 1.0, 1.0], [1.0, 1.0, 1.0]]*)

**SetDefaultIndividualAttributes** ()

NOTE: This is very Measles-ish. We might want to move into MeaslesDemographics

**SetMinimalNodeAttributes** ()

**SetDefaultNodeAttributes** (*birth=True*)

```

SetDefaultIndividualProperties ()
SetDefaultProperties ()
SetDefaultPropertiesFertMort (CrudeBirthRate=0.04, CrudeMortRate=0.02)
    Set defaults assuming constant birth and mortality rate
SetDefaultFromTemplate (template, setter_fn=None)
SetNodeDefaultFromTemplate (template, setter_fn)
SetOverdispersion (new_overdispersion_value, nodes=[])
SetConstantSusceptibility ()
SetInfectivityMultiplierByNode (node_id_to_multiplier)

```

## emod\_api.demographics.DemographicsGenerator module

```

exception emod_api.demographics.DemographicsGenerator.InvalidResolution
    Bases: BaseException

```

Custom Exception

```

class emod_api.demographics.DemographicsGenerator.DemographicsType (value)
    Bases: enum.Enum

    STATIC = 'static'

```

```

emod_api.demographics.DemographicsGenerator.arcsec_to_deg (arcsec: float) → float
    Arc second to degrees :param arcsec: arcsecond as float

```

**Returns** arc second converted to degrees

```

emod_api.demographics.DemographicsGenerator.validate_res_in_arcsec (res_in_arcsec)
    Validate that the resolution is valid :param res_in_arcsec: Resolution in arsecond. Supported values can be
    found in VALID_RESOLUTIONS

```

**Returns** None.

**Raise:** KeyError: If the resolution is invalid, a key error is raised

```

class emod_api.demographics.DemographicsGenerator.DemographicsGenerator (nodes,
                                                                           con-
                                                                           cerns:
                                                                           Op-
                                                                           tional[Union[emod_api.dtk
                                                                           List[emod_api.dtk_tools.de
                                                                           =
                                                                           None,
                                                                           res_in_arcsec='custom',
                                                                           node_id_from_lat_long=Fa

```

Bases: object

Generates demographics file based on population input file. The population input file is csv with structure

node\_label\*, lat, lon, pop\*

\*-ed columns are optional

**set\_resolution** (*res\_in\_arcsec*)

The canonical way to set arcsecond/degree resolutions on a DemographicsGenerator object. Verifies everything is set properly

**Parameters** *res\_in\_arcsec* – The requested resolution. e.g. 30, 250, ‘custom’

Returns: No return value.

**generate\_nodes** (*defaults*)

generate demographics file nodes

The process for generating nodes starts with looping through the loaded demographics nodes. For each node, we:

1. First determine the node’s id. If the node has a forced id set, we use that. If we are using a custom resolution, we use the index (ie 1, 2, 3...). Lastly, we build the node id from the lat and lon id of the node

2. We then start to populate the node\_attributes and individual attributes for the current node. The node\_attributes will have data loaded from the initial nodes fed into DemographicsGenerator. The individual attributes start off as an empty dict.

3. We next determine the birthrate for the node. If the node attributes contains a Country element, we first lookup the birthrate from the World Pop data. We then build a MortalityDistribution configuration with country specific configuration elements and add that to the individual attributes. If there is no Country element in the node attributes, we set the birth rate to the default\_birth\_rate. This value was set in initialization of the DemographicsGenerator to the birth rate of the specified country from the world pop data

4. We then calculate the per\_node\_birth\_rate using get\_per\_node\_birth\_rate and then set the birth rate on the node attributes

5. We then calculate the equilibrium\_age\_distribution and use that to create the AgeDistribution in individual\_attributes

6. We then add each new demographic node to a list to end returned at the end of the function

**generate\_metadata** ()

generate demographics file metadata

**generate\_demographics** ()

return all demographics file components in a single dictionary; a valid DTK demographics file when dumped as json

```

emod_api.demographics.DemographicsGenerator.from_dataframe(df, demographics_filename: Optional[str] = None, concerns: Optional[Union[emod_api.dtk_tools.demographics.DemographicsNodeGeneratorConcern, List[emod_api.dtk_tools.demographics.DemographicsNodeGeneratorConcern]]] = None, res_in_arcsec='custom', node_id_from_lat_long=True, default_population: int = 1000, load_other_columns_as_attributes=False, include_columns: Optional[List[str]] = None, exclude_columns: Optional[List[str]] = None, nodeid_column_name: Optional[str] = None, latitude_column_name: str = 'lat', longitude_column_name: str = 'lon', population_column_name: str = 'pop')

```

Generates a demographics file from a dataframe

#### Parameters

- **df** – pandas DataFrame containing demographics information. Must contain all the columns specified by latitude\_column\_name, longitude\_column\_name. The population\_column\_name is optional. If not found, we fall back to default\_population
- **demographics\_filename** – demographics file to save the demographics file too. This is optional
- **concerns** (*Optional[DemographicsNodeGeneratorConcern]*) – What DemographicsNodeGeneratorConcern should
- **apply**. If not specified, we use the DefaultWorldBankEquilibriumConcern (we) –
- **res\_in\_arcsec** – Resolution in Arcseconds
- **node\_id\_from\_lat\_long** – Determine if we should calculate the node id from the lat long. By default this is true unless you also set res\_in\_arcsec to CUSTOM\_RESOLUTION. When not using lat/long for ids, the first fallback it to check the node for a forced id. If that is not found, we assign it an index as id
- **load\_other\_columns\_as\_attributes** – Load additional columns from a csv file as node attributes
- **include\_columns** – A list of columns that should be added as node attributes from the csv file. To be used in conjunction with load\_other\_columns\_as\_attributes.
- **exclude\_columns** – A list of columns that should be ignored as attributes when

load\_other\_columns\_as\_attributes is enabled. This cannot be combined with include\_columns

- **default\_population** – Default population. Only used if population\_column\_name does not exist
- **nodeid\_column\_name** – Column name to load nodeid values from
- **latitude\_column\_name** – Column name to load latitude values from
- **longitude\_column\_name** – Column name to load longitude values from
- **population\_column\_name** – Column name to load population values from

**Returns** demographics file as a dictionary

```
emod_api.demographics.DemographicsGenerator.from_file(population_input_file:
    str,          demographics_filename: Optional[str]
    = None, concerns: Optional[Union[emod_api.dtk_tools.demographics.DemographicsNodeGeneratorConcern,
    List[emod_api.dtk_tools.demographics.DemographicsNodeGeneratorConcern]]]
    = None,
    res_in_arcsec='custom',
    node_id_from_lat_long=True,
    default_population:
    int          = 1000,
    load_other_columns_as_attributes=False,
    include_columns: Optional[List[str]] = None,
    exclude_columns: Optional[List[str]] = None,
    nodeid_column_name: Optional[str] = None,
    latitude_column_name:
    str          = 'lat', longitude_column_name:
    str          = 'lon', population_column_name: str =
    'pop')
```

Generates a demographics file from a CSV population

#### Parameters

- **population\_input\_file** – CSV population file. Must contain all the columns specified by latitude\_column\_name, longitude\_column\_name. The population\_column\_name is optional. If not found, we fall back to default\_population
- **demographics\_filename** – demographics file to save the demographics file too. This is optional
- **concerns** (*Optional[DemographicsNodeGeneratorConcern]*) – What DemographicsNodeGeneratorConcern should
- **apply**. If not specified, we use the DefaultWorldBankEquilibriumConcern (we) –
- **res\_in\_arcsec** – Resolution in Arcseconds
- **node\_id\_from\_lat\_long** – Determine if we should calculate the node id from the lat long. By default this is true unless you also set res\_in\_arcsec to CUSTOM\_RESOLUTION.



When not using lat/long for ids, the first fallback is to check the node for a forced id. If that is not found, we assign it an index as id

- **load\_other\_columns\_as\_attributes** – Load additional columns from a csv file as node attributes
- **include\_columns** – A list of columns that should be added as node attributes from the csv file. To be used in conjunction with load\_other\_columns\_as\_attributes.
- **exclude\_columns** – A list of columns that should be ignored as attributes when load\_other\_columns\_as\_attributes is enabled. This cannot be combined with include\_columns
- **default\_population** – Default population. Only used if population\_column\_name does not exist
- **nodeid\_column\_name** – Column name to load nodeid values from
- **latitude\_column\_name** – Column name to load latitude values from
- **longitude\_column\_name** – Column name to load longitude values from
- **population\_column\_name** – Column name to load population values from

**Returns** demographics file as a dictionary

## emod\_api.demographics.DemographicsInputDataParsers module

This file contains functions used to read, parse, and process input data files and convert the data into Nodes. Plus utility support function that are part of that process. There is no fixed fileformat for the incoming data. Any file format that is supported by a function here is a supported format. You can add to this.

```
emod_api.demographics.DemographicsInputDataParsers.node_ID_from_lat_long(lat,
                                                                           long,
                                                                           res=0.008333333333333333)

emod_api.demographics.DemographicsInputDataParsers.duplicate_nodeID_check(nodelist)

emod_api.demographics.DemographicsInputDataParsers.fill_nodes_legacy(node_info,
                               De-
                               moDf,
                               res=0.008333333333333333)

emod_api.demographics.DemographicsInputDataParsers.ConstructNodesFromDataFrame(node_info,
                                         ex-
                                         tra_data_column,
                                         res=0.008333333333333333)
```

## emod\_api.demographics.DemographicsTemplates module

```
emod_api.demographics.DemographicsTemplates.NoRisk()
    NoRisk puts everyone at 0 risk.

emod_api.demographics.DemographicsTemplates.FullRisk(demog)
    FullRisk puts everyone at 100% risk.

emod_api.demographics.DemographicsTemplates.InitRiskUniform(demog, min=0,
                                                             max=1)
    InitRiskUniform puts everyone at somewhere between 0% risk and 100% risk, drawn uniformly.
```

### Parameters

- **min** (*float*) – Low end of uniform distribution. Must be  $\geq 0$ ,  $< 1$ .
- **max** (*float*) – High end of uniform distribution. Must be  $\geq \text{min}$ ,  $\leq 1$ .

**Returns** json object aka python dict that can be directly passed to Demographics::SetDefaultFromTemplate

**Raises** None –

`emod_api.demographics.DemographicsTemplates.NoInitialPrevalence (demog)`

NoInitialPrevalence disables initial prevalence; outbreak seeding must be done from an Outbreak intervention (or serialized population).

**Parameters** **demog** – emod-api.demographics.Demographics instance.

**Returns** None

**Raises** None –

`emod_api.demographics.DemographicsTemplates.InitPrevUniform (demog, prevalence)`

`emod_api.demographics.DemographicsTemplates.InitSusceptConstant (demog)`

`emod_api.demographics.DemographicsTemplates.EveryoneInitiallySusceptible (demog, setting=1.0)`

`emod_api.demographics.DemographicsTemplates.StepFunctionSusceptibility (demog, protected_setting=0.0, threshold_age=1825.0)`

`emod_api.demographics.DemographicsTemplates.SimpleSusceptibilityDistribution (demog, mean_AgeAt_Infection=2.5)`

`emod_api.demographics.DemographicsTemplates.DefaultSusceptibilityDistribution (demog)`

`emod_api.demographics.DemographicsTemplates.MortalityRateByAge (demog, age_bins, mort_rates)`

Mortality Rate by Age

`emod_api.demographics.DemographicsTemplates.ConstantMortality (demog, CrudeMortRate)`

`emod_api.demographics.DemographicsTemplates.MortalityStructureNigeriaDHS (demog)`

`emod_api.demographics.DemographicsTemplates.get_fert_dist (path_to_csv)`

This function takes a fertility csv file (by year and age bin) and populates a DTK demographics.json file, and the corresponding config file to do individual pregnancies by age and year from data.

**Parameters**

- **demog** – emod-api.demographics.Demographics instance.
- **path\_to\_csv** – absolute path to csv input file. The file should have columns for 5-year age bins
- **"15-19", etc. up to "45-49", and a column named "Years" with values like "1950-1955". (labelled)** –

- can be extra columns and the columns can be anywhere. (There) –

**Returns** (complex) dictionary. fertility distribution, ready to be added to demographics file.

`emod_api.demographics.DemographicsTemplates.InitAgeUniform(demog)`

`emod_api.demographics.DemographicsTemplates.AgeStructureUNWPP(demog)`

`emod_api.demographics.DemographicsTemplates.EquilibriumAgeDistFromBirthAndMortRates(demog, Crude-BirthRate, Crude-MortalityRate=0.0)`

For the moment, this is assuming constant mortality, should update with an interpolator based on demographics file to improve Reuse of some of these demographics variables and passing them around indicates this may be better as a class. May be best to wait however, until the idmtools Demographics class is around, so that we can inherit from that and only add functionality. Should maybe allow user to specify the “fineness” of the age-binning for the final demographics distribution Having to do this conversion of crude birth rates to per-day per-person rates frequently. Should find the right place to do this only once.

## emod\_api.demographics.Node module

**class** `emod_api.demographics.Node.Node` (*lat, lon, pop, name="", area=None, forced\_id=None, extra\_attributes={}, meta={}*)

Bases: `object`

**default\_density** = 200

**default\_population** = 1000

**res\_in\_degrees** = 0.041666666666666664

**to\_dict**()

**to\_tuple**()

**property id**

**classmethod init\_resolution\_from\_file** (*fn*)

**classmethod from\_data** (*data*)

Function used to create the node object from data (most likely coming from a demographics file) :param data: :return:

`emod_api.demographics.Node.get_xpix_ypix(nodeid)`

`emod_api.demographics.Node.lat_lon_from_nodeid(nodeid, res_in_deg=0.041666666666666664)`

`emod_api.demographics.Node.xpix_ypix_from_lat_lon(lat, lon, res_in_deg=0.041666666666666664)`

`emod_api.demographics.Node.nodeid_from_lat_lon(lat, lon, res_in_deg=0.041666666666666664)`

`emod_api.demographics.Node.nodes_for_DTK(filename, nodes)`

`emod_api.demographics.Node.basicNode(lat=0, lon=0, pop=1000000.0, name=1, forced_id=1)`

## emod\_api.demographics.demographics\_utils module

`emod_api.demographics.demographics_utils.set_risk_mod(filename, distribution, par1, par2)`

Set the RiskDistributionFlag, RiskDistribution1 and RiskDistribution2 in a demographics file.

### Parameters

- **filename** – The demographics file location
- **distribution** – The selected distribution (need to come from `distribution_types`)
- **par1** – Parameter 1 of the distribution
- **par2** – Parameter 2 of the distribution (may be unused depending on the selected distribution)

**Returns** Nothing

`emod_api.demographics.demographics_utils.set_immune_mod(filename, distribution, par1, par2)`

Set the ImmunityDistributionFlag, ImmunityDistribution1 and ImmunityDistribution2 in a demographics file.

### Parameters

- **filename** – The demographics file location
- **distribution** – The selected distribution (need to come from `distribution_types`)
- **par1** – Parameter 1 of the distribution
- **par2** – Parameter 2 of the distribution (may be unused depending on the selected distribution)

**Returns** Nothing

`emod_api.demographics.demographics_utils.apply_to_defaults_or_nodes(demog, fn, *args)`

Apply the `fn` function either to the `Defaults` dictionary or to each of the nodes depending if the `IndividualAttributes` parameter is present in the `Defaults` or not.

### Parameters

- **demog** – The demographic file represented as a dictionary
- **fn** – The function to apply the `Defaults` or individual nodes
- **args** – Argument list needed by `fn`

**Returns** Nothing

`emod_api.demographics.demographics_utils.set_demog_distributions(filename, distributions)`

Apply distributions to a given demographics file. The distributions needs to be formatted as a list of (name, distribution, par1, par2) with:

- **name:** Immunity, Risk, Age, Prevalence or MigrationHeterogeneity
- **distribution:** One distribution contained in `distribution_types`
- **par1, par2:** the values for the distribution parameters

```
# Set the PrevalenceDistribution to a uniform distribution with 0.1 and 0.2
# and the ImmunityDistributionFlag to a constant distribution with 1
demog = json.load(open("demographics.json", "r"))
distributions = list()
distributions.add(("Prevalence", "UNIFORM_DISTRIBUTION", 0.1, 0.2))
distributions.add(("Immunity", "CONSTANT_DISTRIBUTION", 1, 0))
set_demog_distribution(demog, distributions)
```

### Parameters

- **filename** – the demographics file as json
- **distributions** – the different distributions to set contained in a list

**Returns** Nothing

`emod_api.demographics.demographics_utils.set_static_demographics(cb, use_existing=False)`  
 Create a static demographics based on the demographics file specified in the config file of the DTKConfigBuilder object passed to the function.

This function takes the current demographics file and adjust the birth rate/death rate to get a static population (the deaths are always compensated by new births).

### Parameters

- **cb** – The config builder object
- **use\_existing** – If True will only take the demographics file name and add the .static to it. If False will create a static demographics file based on the specified demographics file.

**Returns** Nothing

`emod_api.demographics.demographics_utils.set_growing_demographics(cb, use_existing=False)`  
 This function creates a growing population. It works the same way as the `set_static_demographics` but with a birth rate more important than the death rate which leads to a growing population.

### Parameters

- **cb** – The DTKConfigBuilder object
- **use\_existing** – If True will only take the demographics file name and add the .growing to it. If False will create a growing demographics file based on the specified demographics file.

**Returns** Nothing

## emod\_api.demographics.grid\_construction module

- construct a grid from a bounding box
- label a collection of points by grid cells
- input: - points csv file with required columns lat,lon # see example input files (structures\_households.csv)
- **output: - csv file of grid locations**
  - csv with grid cell id added for each point record

`emod_api.demographics.grid_construction.get_grid_cell_id(idx, idy)`

```
emod_api.demographics.grid_construction.construct (x_min, y_min, x_max, y_max)
    Creating grid
emod_api.demographics.grid_construction.get_bbox (data)
emod_api.demographics.grid_construction.lon_lat_2_point (lon, lat)
emod_api.demographics.grid_construction.point_2_grid_cell_id_lookup (point,
                                                                    grid_id_2_cell_id,
                                                                    origin)
```

## **emod\_api.interventions package**

### **Submodules**

#### **emod\_api.interventions.common module**

```
emod_api.interventions.common.BroadcastEvent (camp, Event_Trigger: str = 'Births')
    Wrapper function to create and return a BroadcastEvent intervention.
```

##### **Parameters**

- **camp** – emod\_api.campaign object with schema\_path set.
- **Event\_Trigger** – A valid trigger/event/signal.

**Returns** Schema-based smart dictionary representing a new BroadcastEvent intervention ready to be added to a campaign.

**Return type** *ReadOnlyDict*

```
emod_api.interventions.common.BroadcastEventToOtherNodes (camp, Event_Trigger,
                                                            Node_Selection_Type='DISTANCE_ONLY',
                                                            Max_Distance_To_Other_Nodes_Km=-1,
                                                            Include_My_Node=1)
    Wrapper function to create and return a BroadcastEventToOtherNodes intervention.
```

##### **Parameters**

- **camp** – emod\_api.campaign object with schema\_path set.
- **Event\_Trigger** – A valid trigger/event/signal.
- **Node\_Selection\_Type** – TBD.
- **Max\_Distance\_To\_Other\_Nodes\_Km** – TBD.
- **Include\_My\_Node** – TBD.

**Returns** Schema-based smart dictionary representing a new BroadcastEvent intervention ready to be added to a campaign.

**Return type** *ReadOnlyDict*

```
emod_api.interventions.common.MultiInterventionDistributor (camp, Intervention_List)
    Wrapper function to create and return a MultiInterventionDistributor intervention.
```

##### **Parameters**

- **camp** – emod\_api.campaign object with schema\_path set.
- **Intervention\_List** – List of 1 or more valid intervention dictionaries to be

- **together.** (*distributed*) –

**Returns** Schema-based smart dictionary representing a new MultiInterventionDistributor intervention ready to be added to a campaign.

**Return type** *ReadOnlyDict*

`emod_api.interventions.common.DelayedIntervention` (*camp*, *Configs*, *Delay\_Dict=None*)

Wrapper function to create and return a DelayedIntervention intervention.

#### Parameters

- **camp** – `emod_api.campaign` object with `schema_path` set.
- **Config** – Valid intervention config.
- **Delay\_Dict** – Dictionary of 1 or 2 params that are the literal `Delay_Distribution`
- **but without the distribution, which is inferred. E.g.,**  
(*parameters*,) –
- **"Delay\_Period\_Exponential" ({} – 5 }**

**Returns** Schema-based smart dictionary representing a new DelayedIntervention intervention ready to be added to a campaign.

**Return type** *ReadOnlyDict*

`emod_api.interventions.common.HSB` (*camp*, *Event\_Or\_Config='Event'*, *Config=None*,  
*Event='NoTrigger'*, *Tendency=1.0*, *Single\_Use=True*,  
*Name='HSB'*)

Wrapper function to create and return a HealthSeekingBehaviour intervention.

#### Parameters

- **camp** – `emod_api.campaign` object with `schema_path` set.
- **Event\_Or\_Config** – “Event” or “Config”.
- **Config** – Complete, valid intervention configuration to be distributed.
- **Event** – Event/Trigger/Signal to be broadcast, alternative to an intervention.
- **Tendency** – Daily probability of ‘seeking care’ aka distributing payload intervention.
- **Single\_Use** – One-and-done, or continuous?
- **Name** – Intervention Name. Useful if you want to provide uniqueness and not worry about
- **intervention management.** (*duplicate*) –

**Returns** Schema-based smart dictionary representing a new HSB intervention ready to be added to a campaign.

**Return type** *ReadOnlyDict*

`emod_api.interventions.common.NLHTI` (*camp*, *Triggers*, *Interventions*, *Property\_Restrictions=None*, *Demographic\_Coverage=1.0*,  
*Target\_Demographic='Everyone'*, *Target\_Age\_Min=0*,  
*Target\_Age\_Max=45625*, *Target\_Gender='All'*,  
*Target\_Residents\_Only=1*, *Duration=- 1*, *Blackout\_Event\_Trigger='Blackout\_Event\_Trigger'*, *Blackout\_Period=0*,  
*Blackout\_On\_First\_Occurrence=0*,  
*Disqualifying\_Properties=None*)

Wrapper function to create and return a NodeLevelHealthTriggeredIntervention intervention.

#### Parameters

- **camp** – emod\_api.campaign object with schema\_path set.
- **Triggers** – List of Triggers/Events/Signals
- **Interventions** – List of interventions to distribute when signal is heard.
- **Property\_Restrictions** – Individual Properties that an agent must have to qualify for intervention.
- **Demographic\_Coverage** – Percentage of individuals to receive intervention.
- **Target\_Demographic** – Everyone, ExplicitAgeRanges, etc.
- **Target\_Age\_Min** – Minimum age (in years).
- **Target\_Age\_Max** – Maximum age (in years).
- **Target\_Gender** – All, Male, or Female.
- **Target\_Residents\_Only** – Not used.
- **Duration** – How long this listen-and-distribute should last.
- **Blackout\_Event\_Trigger** – Not used.
- **Blackout\_Period** – Not used.
- **Blackout\_On\_First\_Occurrence** – Not used.
- **Disqualifying\_Properties** – Not used.

**Returns** Schema-based smart dictionary representing a new NLHTI intervention ready to be added to a campaign.

**Return type** *ReadOnlyDict*

```
emod_api.interventions.common.PropertyValueChanger(camp,      Target_Property_Key,  
                                                    Target_Property_Value,  
                                                    New_Property_Value,  
                                                    Daily_Probability=1.0,    Maxi-  
                                                    mum_Duration=1,  Revert=False,  
                                                    Intervention_Name="",  
                                                    Event_Trigger_Distributed="",  
                                                    Event_Trigger_Expired="")
```

Wrapper function to create and return a PropertyValueChanger intervention.

**Parameters** **camp** – emod\_api.campaign object with schema\_path set.

**Returns** Schema-based smart dictionary representing a new PropertyValueChanger intervention ready to be added to a campaign.

**Return type** *ReadOnlyDict*



```

emod_api.interventions.common.ScheduledCampaignEvent (camp, Start_Day, Node-
set_Config, Number_Repetitions=1,
Timesteps_Between_Repetitions=1,
Event_Name='Scheduled_Campaign_Event',
Node_Property_Restrictions=None,
Property_Restrictions=None, Target_Demographic='Everyone',
Demographic_Coverage=1.0,
Target_Age_Min=0, Target_Age_Max=45625, Target_Gender='All', Intervention_List=None)

```

Wrapper function to create and return a ScheduledCampaignEvent intervention. The alternative to a ScheduledCampaignEvent is a TriggeredCampaignEvent.

#### Parameters

- **camp** – emod\_api.campaign object with schema\_path set.
- **Start\_Day** – When to start.
- **Event\_Name** – Name for overall campaign event, of not functional meaning.
- **Nodeset\_Config** – Nodes to target with this intervention, return from utils.do\_nodes().
- **Node\_Property\_Restrictions** – Optional property restriction for node-targeted interventions.
- **Property\_Restrictions** – Individual Properties a person must have to receive the intervention(s).
- **Number\_Repetitions** – N/A
- **Timesteps\_Between\_Repetitions** – N/A
- **Demographic\_Coverage** – Percentage of individuals to receive intervention.
- **Target\_Demographic** – Everyone, ExplicitAgeRanges, etc.
- **Target\_Age\_Min** – Minimum age (in years).
- **Target\_Age\_Max** – Maximum age (in years).
- **Target\_Gender** – All, Male, or Female.
- **Intervention\_List** – List of 1 or more valid intervention dictionaries to be
- **together.** (*distributed*) –

**Returns** Schema-based smart dictionary representing a new ScheduledCampaignEvent intervention ready to be added to a campaign.

**Return type** *ReadOnlyDict*

```
emod_api.interventions.common.TriggeredCampaignEvent (camp, Start_Day, Event_Name,
Nodeset_Config, Triggers, Intervention_List,
Node_Property_Restrictions=None,
Property_Restrictions=None,
Number_Repetitions=1,
Timesteps_Between_Repetitions=-1,
Demographic_Coverage=1.0, Target_Demographic='Everyone',
Target_Age_Min=0, Target_Age_Max=45625,
Target_Gender='All', Target_Residents_Only=1,
Duration=-1, Blackout_Event_Trigger='Blackout_Event_Trigger',
Blackout_Period=0, Blackout_On_First_Occurrence=0,
Disqualifying_Properties=None, Delay=None)
```

Wrapper function to create and return a TriggeredCampaignEvent intervention. The alternative to a TriggeredCampaignEvent is a ScheduledCampaignEvent.

#### Parameters

- **camp** – emod\_api.campaign object with schema\_path set.
- **Start\_Day** – When to start.
- **Event\_Name** – Name for overall campaign event, of not functional meaning.
- **Nodeset\_Config** – Nodes to target with this intervention, return from utils.do\_nodes().
- **Triggers** – List of triggers/events/signals to listen to in order to trigger distribution.
- **Intervention\_List** – List of 1 or more valid intervention dictionaries to be
- **together.** (*distributed*) –
- **Node\_Property\_Restrictions** – N/A.
- **Property\_Restrictions** – Individual Properties a person must have to receive the intervention(s).
- **Demographic\_Coverage** – Percentage of individuals to receive intervention.
- **Target\_Demographic** – Everyone, ExplicitAgeRanges, etc.
- **Target\_Age\_Min** – Minimum age (in years).
- **Target\_Age\_Max** – Maximum age (in years).
- **Target\_Gender** – All, Male, or Female.
- **Target\_Residents\_Only** – Not used.
- **Duration** – How long this listen-and-distribute should last.
- **Blackout\_Event\_Trigger** – Not used.
- **Blackout\_Period** – Not used.
- **Blackout\_On\_First\_Occurrence** – Not used.

- **Disqualifying\_Properties** – Not used.
- **delay** – Optional delay between trigger and actual distribution.

**Returns** Schema-based smart dictionary representing a new TriggeredCampaignEvent intervention ready to be added to a campaign.

**Return type** *ReadOnlyDict*

```
emod_api.interventions.common.StandardDiagnostic(camp, Base_Sensitivity=1,
                                                    Base_Specificity=1,
                                                    Days_To_Diagnosis=0,
                                                    Treatment_Fraction=1,
                                                    Event_Or_Config='Config')
```

Wrapper function to create and return a StandardDiagnostic intervention.

#### Parameters

- **camp** – emod\_api.campaign object with schema\_path set.
- **Intervention\_List** – List of 1 or more valid intervention dictionaries to be
- **together**. (*distributed*) –

**Returns** Schema-based smart dictionary representing a new MultiInterventionDistributor intervention ready to be added to a campaign.

**Return type** *ReadOnlyDict*

### emod\_api.interventions.import\_pressure module

```
emod_api.interventions.import_pressure.new_intervention(timestep, durs=[], dips=[],
                                                         nods=[])
```

```
emod_api.interventions.import_pressure.new_intervention_as_file(timestep, file-
                                                                name=None)
```

### emod\_api.interventions.node\_multiplier module

```
emod_api.interventions.node_multiplier.new_intervention(camp, new_infectivity=1.0,
                                                         profile='CONST',
                                                         **kwargs)
```

Create new NodeInfectivityModifying intervention.

#### Parameters

- **profile** – multiplier options include:
  - **CONST(ANT)**
    - \* new\_infectivity lasts forever (or until replaced).
  - **TRAP(EZOID)**
    - \* rise\_dur(ation)
    - \* peak\_dur(ation)
    - \* fall\_dur(ation)
  - **EXP(ONENTIAL) (not implemented yet)**
    - \* rise duration

- \* rise rate
- **SIN(USOIDAL)** (not implemented yet)
- \* period
- **do boxcar, specify 0 rise and fall durations** ( $T_0$ ) –

**Returns** new NodeInfectivityMult intervention dictionary.

```
emod_api.interventions.node_multiplier.new_scheduled_event(camp, start_day=1,
                                                           new_infectivity=1.0,
                                                           profile='CONST',
                                                           node_ids=None,
                                                           recurring=True,
                                                           **kwargs)
```

Create new NodeInfectivityModifying intervention as scheduled campaign event.

```
emod_api.interventions.node_multiplier.new_intervention_as_file(camp,
                                                                timestep, file-
                                                                name=None)
```

Create new NodeInfectivityModifying intervention as sole scheduled campaign event inside working campaign json file.

## emod\_api.interventions.outbreak module

```
emod_api.interventions.outbreak.seed_by_coverage(timestep, campaign_hook, cover-
                                                  age=0.01, ignore_immunity=None)
```

This simple function provides a very common piece of functionality to seed an infection. A future version will support targeted nodesets.

```
emod_api.interventions.outbreak.new_intervention(timestep, campaign_hook, cases=1)
```

Create EMOD-ready Outbreak intervention.

### Parameters

- **timestep** (*float*) – timestep at which outbreak should occur.
- **cases** (*integer*) – new parameter that specifies maximum number of cases. May not be supported.

**Returns** event as dict (json)

**Return type** event (json)

```
emod_api.interventions.outbreak.new_intervention_as_file(timestep, camp, cases=1,
                                                         filename=None)
```

## emod\_api.interventions.simple\_vaccine module

```
emod_api.interventions.simple_vaccine.new_intervention(timestep, v_type='Generic',
                                                         efficacy=1.0,
                                                         sv_name='Vaccine',
                                                         waning_duration=100,
                                                         d_a_d=None, e_i_r=None)
```

This is mostly an example but also potentially useful. With this you get a Vaccine with working defaults but 2 configurables: type and efficacy. The duration is fixed at box. You of course must specify the timestep and you can add a vaccine name which is mostly useful if you're managing a duplicate policy.

```
emod_api.interventions.simple_vaccine.new_intervention2(timestep)
```

This version lets you invoke the function sans-parameters. You get the module-level params which you can set before calling this. This is designed to support a more data-oriented way of using this API, with everything like “a.b=c”, and avoid “churn” on the API itself (constantly changing function signature). TBD: Make sure that if this is called twice, we understand whether we have copies or references going on.

```
emod_api.interventions.simple_vaccine.new_intervention_as_file(timestep, file-
                                                                name=None)
```

## emod\_api.interventions.utils module

```
emod_api.interventions.utils.do_nodes(schema_path, node_ids)
```

Create and return a NodeSetConfig based on node\_ids list.

```
emod_api.interventions.utils.get_waning_from_params(schema_path, initial=1.0,
                                                    box_duration=365, de-
                                                    cay_rate=0)
```

Get well configured waning structure. Default is 1-year full efficacy box. Note that an infinite decay rate (0 or even -1) is same as Box. Note that an infinite box duration (-1) is same as constant. Note that a zero box duration is same as Exponential.

## emod\_api.migration package

### Submodules

### emod\_api.migration.migration module

```
class emod_api.migration.migration.Layer
```

Bases: `dict`

The Layer object represents a mapping from source node (IDs) to destination node (IDs) for a particular age, gender, age+gender combination, or all users if no age or gender dependence. Users will not generally interact directly with Layer objects.

**property DatavalueCount**

Get (maximum) number of data values for any node in this layer

**Returns** Maximum number of data values for any node in this layer

**property NodeCount**

Get the number of (source) nodes with rates in this layer

**Returns** Number of (source) nodes with rates in this layer

```
class emod_api.migration.migration.Migration
```

Bases: `object`

Represents migration data in a mapping from source node (IDs) to destination node (IDs) with rates for each pairing.

Migration data may be age dependent, gender dependent, both, or the same for all ages and genders. A migration file (along with JSON metadata) can be loaded from the static method `Migration.from_file()` and inspected and/or modified. Migration objects can be started from scratch with `Migration()`, and populated with appropriate source-dest rate data and saved to a file with the `to_file()` method. Given `migration = Migration()`, syntax is as follows:

age and gender agnostic: migration[source\_id][dest\_id] age dependent: migration[source\_id:age] # age should be  $\geq 0$ , ages > last bucket value use last bucket value gender dependent: migration[source\_id:gender] # gender one of Migration.MALE or Migration.FEMALE age and gender dependent: migration[source\_id:gender:age] # gender one of Migration.MALE or Migration.FEMALE

EMOD/DTK format migration files (and associated metadata files) can be written with migration.to\_file(<filename>). EMOD/DTK format migration files (with associated metadata files) can be read with migration.from\_file(<filename>).

**SAME\_FOR\_BOTH\_GENDERS = 0**

**ONE\_FOR\_EACH\_GENDER = 1**

**LINEAR\_INTERPOLATION = 0**

**PIECEWISE\_CONSTANT = 1**

**LOCAL = 1**

**AIR = 2**

**REGIONAL = 3**

**SEA = 4**

**FAMILY = 5**

**INTERVENTION = 6**

**IDREF\_LEGACY = 'Legacy'**

**IDREF\_GRUMP30ARCSEC = 'Gridded world grump30arcsec'**

**IDREF\_GRUMP2PT5ARCMIN = 'Gridded world grump2.5arcmin'**

**IDREF\_GRUMP1DEGREE = 'Gridded world grump1degree'**

**MALE = 0**

**FEMALE = 1**

**MAX\_AGE = 125**

**property AgesYears**

List of ages - ages < first value use first bucket, ages > last value use last bucket.

**property Author**

str: Author value for metadata for this migration datafile

**property DatavalueCount**

int: Maximum data value count for any layer in this migration datafile

**property DateCreated**

datetime: date/time stamp of this datafile

**property GenderDataType**

int: gender data type for this datafile - SAME\_FOR\_BOTH\_GENDERS or ONE\_FOR\_EACH\_GENDER

**property IdReference**

str: ID reference metadata value

**property InterpolationType**

int: interpolation type for this migration data file - LINEAR\_INTERPOLATION or PIECEWISE\_CONSTANT

**property MigrationType**

int: migration type for this migration data file - LOCAL | AIR | REGIONAL | SEA | FAMILY | INTERVENTION

**property Nodes****property NodeCount**

int: maximum number of source nodes in any layer of this migration data file

**get\_node\_offsets** (*limit: int = 100*) → dict**property NodeOffsets**

dict: mapping from source node id to offset to destination and rate data in binary data

**property Tool**

str: tool metadata value

**to\_file** (*binaryfile: pathlib.Path, metafile: pathlib.Path = None, value\_limit: int = 100*)

Write current data to given file (and .json metadata file)

**Parameters**

- **binaryfile** (*Path*) – path to output file (metadata will be written to same path with “.json” appended)
- **metafile** (*Path*) – override standard metadata file naming
- **value\_limit** (*int*) – limit on number of destination values to write for each source node (default = 100)

**Returns** path to binary file

**Return type** (*Path*)

`emod_api.migration.migration.from_file` (*binaryfile: pathlib.Path, metafile: pathlib.Path = None*)

Reads migration data file from given binary (and associated JSON metadata file)

**Parameters**

- **binaryfile** (*Path*) – path to binary file (metadata file is assumed to be at same location with “.json” suffix)
- **metafile** (*Path*) – use given metafile rather than inferring metafile name from the binary file name

**Returns** Migration object representing binary data in the given file.

`emod_api.migration.migration.examine_file` (*filename*)

`emod_api.migration.migration.from_params` (*demographics\_file\_path=None, pop=1000000.0, num\_nodes=100, mig\_factor=1.0, frac\_rural=0.3, id\_ref='from\_params', migration\_type=1*)

This function is for creating a migration file that goes with a (multinode) demographics file created from a few parameters, as opposed to one from real-world data. Note that the ‘demographics\_file\_path’ input param is not used at this time but in future will be exploited to ensure nodes, etc., match.

`emod_api.migration.migration.from_demog_and_param_gravity` (*demographics\_file\_path, gravity\_params, id\_ref, migration\_type=1*)

Create migration files from a gravity model and an input demographics file.

`emod_api.migration.migration.to_csv` (*filename: pathlib.Path*)

### emod\_api.schema package

#### Submodules

#### emod\_api.schema.dtk\_post\_process\_schema module

`emod_api.schema.dtk_post_process_schema.recurser` (*in\_json*)

`emod_api.schema.dtk_post_process_schema.application` (*schema\_file*)

#### emod\_api.schema.get\_schema module

`emod_api.schema.get_schema.dtk_to_schema` (*path\_to\_binary*, *path\_to\_write\_schema*='schema.json')  
Runs /path/to/Eradication --get-schema --schema-path=schema.json and then post-processes the schema into something more useful. Error cases handled: - schema.json file already exists in cwd; does not overwrite. Asks users to move and retry. - Specified binary fails to run to completion. - Specified binary fails to produce a schema.json

### emod\_api.serialization package

#### Submodules

#### emod\_api.serialization.CensusAndModPop module

`emod_api.serialization.CensusAndModPop.change_ser_pop` (*input\_serpop\_path*,  
*mod\_fn*=None,  
*save\_file\_path*=None)

This function loads a serialization population file, iterates over each person, calls a user-provided callback with each individuals, and saves the population as manipulated by the user.

The mod function can act at will on the population object. There are no checks.

The new file is saved to a name provided by user. Interactive if none provided to function.

Assuming a single node file for now.

#### emod\_api.serialization.SerializedPopulation module

Class to load and manipulate a saved population.

**class** `emod_api.serialization.SerializedPopulation.SerializedPopulation` (*file*:  
*str*)

Bases: `object`

Opens the passed file and reads in all the nodes.

**Parameters** `file` – serialized population file



## Examples

Create an instance of SerializedPopulation:

```
import emod_api.serialization.SerializedPopulation as SerPop
ser_pop = SerPop.SerializedPopulation('state-00001.dtk')
```

### property nodes

All nodes.

## Examples

Delete number\_of\_ind individuals from node 0:

```
node = ser_pop.nodes[0]
del node.individualHumans[0:number_of_ind]
```

Only keep individuals with a certain condition:

```
node.individualHumans = [ind for ind in node.individualHumans if keep_
↳ fct(ind)]
```

Change susceptibility of an individual:

```
print(node.individualHumans[0].susceptibility)
new_susceptibility = {"age": 101.01, "mod_acquire": 0}
node.individualHumans[0].susceptibility.update(new_susceptibility)
```

Copy individual[0] from node 0, change properties and add individual as new individual:

```
import copy
individual_properties={"m_age": 1234}
individual = copy.deepcopy(node.individualHumans[0])
individual["suid"] = ser_pop.get_next_individual_suid(0)
individual.update(individual_properties)
ser_pop.nodes[0].individualHumans.append(individual)
```

Infect an individual with an infection copied from another individual:

```
infection = node["individualHumans"][0]["infections"][0]
infection["suid"] = self.get_next_infection_suid()
node["individualHumans"][1]["infections"].append(infection)
node["individualHumans"][1].m_is_infected = True
```

### flush()

Save all made changes to the node(s).

### write(output\_file: str = 'my\_sp\_file.dtk')

Write the population to a file.

**Parameters** output\_file – output file

### get\_next\_infection\_suid()

Each infection needs a unique identifier, this function returns one.

### get\_next\_individual\_suid(node\_id: int) → dict

Each individual needs a unique identifier, this function returns one.

**Parameters** node\_id – The first parameter.

**Returns** The return value. True for success, False otherwise.

## Examples

To get a unique id for an individual:

```
print(sp.get_next_individual_suid(0))
{'id': 2}
```

`emod_api.serialization.SerializedPopulation.find(name: str, handle, currentlevel='dtk.nodes')`

Recursively searches for a paramters that matches or is close to name and prints out where to find it in the file.

### Parameters

- **name** – the paramter you are looking for e.g. “age”, “gender”.
- **handle** – some iterable data structure, can be a list of nodes, a node, list of individuals, etc  
**currentlevel**: just a string to print out where the found item is located e.g. “dtk.nodes” or “dtk.node.individuals”

## Examples

What is the exact paramteter name used for the age of an individual?:

```
SerPop.find("age", node)
...
1998 Found in: dtk.nodes.individualHumans[999].m_age
1999 Found in: dtk.nodes.individualHumans[999].susceptibility.age
2000 Found in: dtk.nodes.m_vectorpopulations[0].EggQueues[0].age
2001 Found in: dtk.nodes.m_vectorpopulations[0].EggQueues[1].age
...
```

`emod_api.serialization.SerializedPopulation.get_parameters(handle, currentlevel='dtk.nodes')`

Return a set of all parameters in the serialized population file. Helpful to get an overview about what is in the serialized population file.

### Parameters

- **handle** – some iterable data structure, can be a list of nodes, a node, list of individuals, etc
- **currentlevel** – just a string to print out where the found item is located e.g. “dtk.nodes” or “dtk.node.individuals”

## Examples

Print all parameters in serialized population file:

```
for n in sorted(SerPop.get_parameters(node)):
    print(n)
```

**emod\_api.serialization.dtkFileSupport module**

```

class emod_api.serialization.dtkFileSupport.Uncompressed
    Bases: object

    classmethod compress (data)

    classmethod uncompress (data)

class emod_api.serialization.dtkFileSupport.EllZeeFour
    Bases: object

    classmethod compress (data)

    classmethod uncompress (data)

class emod_api.serialization.dtkFileSupport.Snappy
    Bases: object

    classmethod compress (data)

    classmethod uncompress (data)

class emod_api.serialization.dtkFileSupport.SerialObject (dictionary={})
    Bases: dict

```

**emod\_api.serialization.dtkFileTools module**

Support for three formats of serialized population files: 1. “Original version”: single payload chunk with simulation and all nodes, uncompressed or snappy or LZ4 2. “First chunked version”: multiple payload chunks, one for simulation and one each for nodes 3. “Second chunked version”: multiple payload chunks, simulation and node objects are “root” objects in each chunk 4. “Metadata update”: compressed: true/false + engine: NONE|LZ4|SNAPPY replaced with compression: NONE|LZ4|SNAPPY

```
emod_api.serialization.dtkFileTools.uncompress (data, engine)
```

```
emod_api.serialization.dtkFileTools.compress (data, engine)
```

```

class emod_api.serialization.dtkFileTools.DtkHeader (dictionary={'author': 'unknown',
                                                                    'bytecount': 0, 'chunkcount': 0,
                                                                    'chunksizes': [], 'compressed':
                                                                    True, 'date': 'Tue May 04
                                                                    17:12:28 2021', 'engine': 'LZ4',
                                                                    'tool': 'dtkFileTools.py', 'ver-
                                                                    sion': 1})
    Bases: emod_api.serialization.dtkFileSupport.SerialObject

```

```

class emod_api.serialization.dtkFileTools.DtkFile (header)
    Bases: object

    class Contents (parent)
        Bases: object

        append (item)

    class Objects (parent)
        Bases: object

        append (item)

    property header

```

```
property compressed
property compression
property byte_count
property chunk_count
property chunk_sizes
property author
property date
property tool
property version
property chunks
property nodes

class emod_api.serialization.dtkFileTools.DtkFileV1(header={'author': 'unknown',
    'bytecount': 0, 'chunkcount':
    0, 'chunksizes': [], 'com-
    pressed': True, 'date': 'Tue May
    04 17:12:28 2021', 'engine':
    'LZ4', 'tool': 'dtkFileTools.py',
    'version': 1}, filename="",
    handle=None)
    Bases: emod_api.serialization.dtkFileTools.DtkFile
    property simulation

class emod_api.serialization.dtkFileTools.DtkFileV2(header={'author': 'unknown',
    'bytecount': 0, 'chunkcount':
    0, 'chunksizes': [], 'com-
    pressed': True, 'date': 'Tue May
    04 17:12:28 2021', 'engine':
    'LZ4', 'tool': 'dtkFileTools.py',
    'version': 1}, filename="",
    handle=None)
    Bases: emod_api.serialization.dtkFileTools.DtkFile

class NodesV2(parent)
    Bases: object
    property simulation

class emod_api.serialization.dtkFileTools.DtkFileV3(header={'author': 'unknown',
    'bytecount': 0, 'chunkcount':
    0, 'chunksizes': [], 'com-
    pressed': True, 'date': 'Tue May
    04 17:12:28 2021', 'engine':
    'LZ4', 'tool': 'dtkFileTools.py',
    'version': 1}, filename="",
    handle=None)
    Bases: emod_api.serialization.dtkFileTools.DtkFile

class NodesV3(parent)
    Bases: object
    property simulation
```

```

class emod_api.serialization.dtkFileTools.DtkFileV4 (header={'author': 'unknown',
                                                             'bytecount': 0, 'chunkcount':
                                                             0, 'chunksizes': [], 'compressed': True, 'date': 'Tue May
                                                             04 17:12:28 2021', 'engine':
                                                             'LZ4', 'tool': 'dtkFileTools.py',
                                                             'version': 1}, filename="",
                                                             handle=None)
    Bases: emod_api.serialization.dtkFileTools.DtkFileV3
emod_api.serialization.dtkFileTools.read(filename)
emod_api.serialization.dtkFileTools.write(dtk_file, filename)

```

## emod\_api.serialization.dtkFileUtility module

## emod\_api.spatialreports package

### Submodules

## emod\_api.spatialreports.spatial module

emod-api spatial report module. Exposes SpatialReport and SpatialNode objects.

```

class emod_api.spatialreports.spatial.SpatialNode (node_id: int, data)
    Bases: object

```

Class representing a single node of a spatial report.

**property id**  
Node ID

**property data**  
Time series data for this node.

```

class emod_api.spatialreports.spatial.SpatialReport (filename: str = None, node_ids:
List[int] = None, data:
numpy.array = None, start:
int = 0, interval: int = 1)
    Bases: object

```

Class for reading (and, optionally, writing) spatial reports in EMOD/DTK format. “Filtered” reports will have start > 0 and/or reporting interval > 1.

**property data**  
Returns full 2 dimensional NumPy array with report data. Shape is (#values, #nodes).

**property node\_ids**  
Returns list of node IDs (integers) for nodes in the report.

**property nodes**  
Returns dictionary of SpatialNodes keyed on node ID.

**property node\_count**  
Number of nodes in the report.

**property time\_steps**  
Number of samples in the report.

**property start**

Time step of first sample.

**property interval**

Interval, in time steps, between samples.

**write\_file** (*filename: str*)

Save current nodes and timeseries data to given file.

**emod\_api.tabularoutput package****emod\_api.weather package****Submodules****emod\_api.weather.weather module**

emod-api Weather module - Weather, Metadata, and WeatherNode objects along with IDREF and CLIMATE\_UPDATE constants.

**class** emod\_api.weather.weather.**WeatherNode** (*node\_id: int, data*)

Bases: `object`

Represents information for a single node: ID and timeseries data.

**property id**

Node ID

**property data**

Time series data for this node.

**class** emod\_api.weather.weather.**Metadata** (*node\_ids: List[int], datavalue\_count: int, author: str = None, created: datetime.datetime = None, frequency: str = None, provenance: str = None, reference: str = None*)

Bases: `object`

Metadata:

- [DateCreated]
- [Author]
- [OriginalDataYears]
- [StartDayOfYear]
- [DataProvenance]
- IdReference
- NodeCount
- DatavalueCount
- UpdateResolution
- NodeOffsets

**property author**

Author of this file.

**property creation\_date**

Creation date of this file.

**property datavalue\_count**

Number of data values in each timeseries, should be > 0.

**property id\_reference**

‘Schema’ for node IDs. Commonly *Legacy*, *Gridded world grump2.5arcmin*, and *Gridded world grump30arcsec*.

*Legacy* usually indicates a 0 or 1 based scheme with increasing ID numbers.

*Gridded world grump2.5arcmin* and *Gridded world grump30arcsec* encode latitude and longitude values in the node ID with the following formula:

```
latitude = ((nodeid - 1) & 0xFFFF) * resolution) - 90
longitude = ((nodeid >> 16) * resolution) - 180
# nodeid = 90967271 @ 2.5 arcmin resolution
# longitude = -122.1667, latitude = 47.5833
```

**property node\_count****property node\_ids****property provenance****property update\_resolution****property nodes**

WeatherNodes offsets keyed by node id.

**write\_file** (filename: *str*) → *None*

**classmethod from\_file** (filename: *str*)

Read weather metadata file. Metadata’ and ‘NodeOffsets’ keys required. DatavalueCount’, ‘UpdateResolution’, and ‘IdReference’ required in ‘Metadata’.

```
class emod_api.weather.weather.Weather (filename: str = None, node_ids: List[int] = None,
                                         datavalue_count: int = None, author: str = None,
                                         created: datetime.datetime = None, frequency: str
                                         = None, provenance: str = None, reference: str =
                                         None, data: numpy.array = None)
```

Bases: *object*

**property data**

Raw data as numpy array[node index, time step].

**property metadata****property author****property creation\_date****property datavalue\_count**

>= 1

**property id\_reference****property node\_count**

>= 1

**property node\_ids****property provenance**

**property** `update_resolution`

**property** `nodes`

WeatherNodes indexed by node id.

**write\_file** (*filename: str*) → *None*

Writes data to filename and metadata to filename.json.

**classmethod** `from_csv` (*filename: str*, *var\_column: str* = 'airtemp', *id\_column: str* = 'node\_id',  
*step\_column: str* = 'step', *author: str* = *None*, *provenance: str* = *None*)

Create weather from CSV file with specified variable column, node id column, and time step column.

---

**Note:**

- Column order in the CSV file is not significant, but columns names must match what is passed to this function.
  - Because a CSV might hold air temperature (may be negative and well outside 0-1 values), relative humidity (must *\_not\_* be negative, must be in the interval [0-1]), or rainfall (must *\_not\_* be negative, likely > 1), this function does not validate incoming data.
- 

## 1.1.2 Submodules

### emod\_api.campaign module

You use this simple campaign builder by importing it, adding valid events via “add”, and writing it out with “save”.

`emod_api.campaign.add` (*event*, *name=None*, *first=False*)

Add a complete campaign event to the campaign builder. The new event is assumed to be a Python dict, and a valid event. The new event is not validated here. Set the first flag to True if this is the first event in a campaign because it functions as an accumulator and in some situations like sweeps it might have been used recently.

`emod_api.campaign.get_trigger_list` ()

`emod_api.campaign.save` (*filename='campaign.json'*)

Save 'camapign\_dict' as 'filename'.

`emod_api.campaign.get_adhocs` ()

`emod_api.campaign.get_schema` ()

`emod_api.campaign.get_recv_trigger` (*trigger*, *old=False*)

Get the correct representation of a trigger (also called signal or even event) that is being listened to.

`emod_api.campaign.get_send_trigger` (*trigger*, *old=False*)

Get the correct representation of a trigger (also called signal or even event) that is being broadcast.

`emod_api.campaign.get_event` (*event*, *old=False*)

Basic placeholder functionality for now. This will map new ad-hoc events to GP\_EVENTS and manage that 'cache' If event in built-ins, return event, else if in adhoc map, return mapped event, else add to adhoc\_map and return mapped event.



**emod\_api.schema\_to\_class module**

**class** emod\_api.schema\_to\_class.ReadOnlyDict

Bases: `collections.OrderedDict`

**set\_schema** (*schema*)

Add schema node.

**to\_file** (*config\_name='config.json'*)

Write 'clean' config file out to disk as json. Param: *config\_name* (defaults to 'config.json')

**finalize** ()

Remove all params that are disabled by depends-on param being off and schema node.

emod\_api.schema\_to\_class.**get\_default\_for\_complex\_type** (*schema, idmtype*)

This function used to be more involved and dumb but now it's a passthrough to `get_class_with_defaults`. If this approach proves robust, it can probably be deprecated. Depends a bit on completeness of schema.

emod\_api.schema\_to\_class.**get\_class\_with\_defaults** (*classname, schema\_path=None*)

Returns the default config for a datatype in the schema.



## **GLOSSARY**

The following terms describe both the features and functionality of the EMOD-API software, as well as information relevant to using EMOD-API.

**asset collection** The set of specific input files (such as input parameters, weather or migration data, or other configuration settings) required for running a simulation.

**assets** See asset collection.

**builder** TBD

**experiment** A collection of multiple simulations, typically sent to an HPC.

**high-performance computing (HPC)** The use of parallel processing for running advanced applications efficiently, reliably, and quickly.

**task** TBD

**template** TBD



## PYTHON MODULE INDEX

### e

emod\_api, 3  
emod\_api.campaign, 36  
emod\_api.channelreports, 3  
emod\_api.channelreports.channels, 3  
emod\_api.config, 4  
emod\_api.config.default\_from\_schema, 4  
emod\_api.config.default\_from\_schema\_no\_validation, 5  
emod\_api.config.dtk\_post\_process\_adhoc\_events, 6  
emod\_api.config.dtk\_pre\_process\_adhoc\_events, 6  
emod\_api.config.dtk\_pre\_process\_w5ml, 6  
emod\_api.config.from\_overrides, 6  
emod\_api.config.from\_poi\_and\_binary, 6  
emod\_api.config.from\_schema, 7  
emod\_api.config.schema\_to\_config, 7  
emod\_api.demographics, 7  
emod\_api.demographics.BaseInputFile, 7  
emod\_api.demographics.Demographics, 8  
emod\_api.demographics.demographics\_utils, 16  
emod\_api.demographics.DemographicsGenerator, 9  
emod\_api.demographics.DemographicsInputDataParsers, 13  
emod\_api.demographics.DemographicsTemplates, 13  
emod\_api.demographics.grid\_construction, 17  
emod\_api.demographics.Node, 15  
emod\_api.interventions, 18  
emod\_api.interventions.common, 18  
emod\_api.interventions.import\_pressure, 23  
emod\_api.interventions.node\_multiplier, 23  
emod\_api.interventions.outbreak, 24  
emod\_api.interventions.simple\_vaccine, 24  
emod\_api.interventions.utils, 25  
emod\_api.migration, 25  
emod\_api.migration.migration, 25  
emod\_api.schema, 28  
emod\_api.schema.dtk\_post\_process\_schema, 28  
emod\_api.schema.get\_schema, 28  
emod\_api.schema\_to\_class, 37  
emod\_api.serialization, 28  
emod\_api.serialization.CensusAndModPop, 28  
emod\_api.serialization.dtkFileSupport, 31  
emod\_api.serialization.dtkFileTools, 31  
emod\_api.serialization.dtkFileUtility, 33  
emod\_api.serialization.SerializedPopulation, 28  
emod\_api.spatialreports, 33  
emod\_api.spatialreports.spatial, 33  
emod\_api.tabularoutput, 34  
emod\_api.weather, 34  
emod\_api.weather.weather, 34



## A

`add()` (in module *emod\_api.campaign*), 36

`AddAgeDependentTransmission()`  
(*emod\_api.demographics.Demographics.Demographics*  
method), 8

`AddIndividualPropertyAndHINT()`  
(*emod\_api.demographics.Demographics.Demographics*  
method), 8

`AgeStructureUNWPP()` (in module  
*emod\_api.demographics.DemographicsTemplates*),  
15

`AgessYears()` (*emod\_api.migration.migration.Migration*  
property), 26

`AIR` (*emod\_api.migration.migration.Migration* at-  
tribute), 26

`append()` (*emod\_api.serialization.dtkFileTools.DtkFile.Contents*  
method), 31

`append()` (*emod\_api.serialization.dtkFileTools.DtkFile.Objects*  
method), 31

`application()` (in module  
*emod\_api.config.dtk\_post\_process\_adhocevents*),  
6

`application()` (in module  
*emod\_api.config.dtk\_pre\_process\_adhocevents*),  
6

`application()` (in module  
*emod\_api.config.dtk\_pre\_process\_w5ml*),  
6

`application()` (in module  
*emod\_api.schema.dtk\_post\_process\_schema*),  
28

`apply_to_defaults_or_nodes()` (in module  
*emod\_api.demographics.demographics\_utils*),  
16

`arcsec_to_deg()` (in module  
*emod\_api.demographics.DemographicsGenerator*),  
9

`as_dataframe()` (*emod\_api.channelreports.channels.ChannelReport*  
method), 4

`as_dictionary()` (*emod\_api.channelreports.channels.Channel*  
method), 4

`as_dictionary()` (*emod\_api.channelreports.channels.Header*

method), 3

asset collection, 39

assets, 39

`author()` (*emod\_api.migration.migration.Migration*  
property), 26

`author()` (*emod\_api.serialization.dtkFileTools.DtkFile*  
property), 32

`author()` (*emod\_api.weather.weather.Metadata* prop-  
erty), 34

`author()` (*emod\_api.weather.weather.Weather* prop-  
erty), 35

## B

`BaseInputFile` (class in  
*emod\_api.demographics.BaseInputFile*),

`basicNode()` (in module  
*emod\_api.demographics.Node*), 15

`BroadcastEvent()` (in module  
*emod\_api.interventions.common*), 18

`BroadcastEventToOtherNodes()` (in module  
*emod\_api.interventions.common*), 18

builder, 39

`byte_count()` (*emod\_api.serialization.dtkFileTools.DtkFile*  
property), 32

## C

`change_ser_pop()` (in module  
*emod\_api.serialization.CensusAndModPop*),  
28

`Channel` (class in *emod\_api.channelreports.channels*),  
3

`channel_names()` (*emod\_api.channelreports.channels.ChannelReport*  
property), 4

`ChannelReport` (class in  
*emod\_api.channelreports.channels*), 4

`channels()` (*emod\_api.channelreports.channels.ChannelReport*  
property), 4

`chunk_count()` (*emod\_api.serialization.dtkFileTools.DtkFile*  
property), 32

`chunk_sizes()` (*emod\_api.serialization.dtkFileTools.DtkFile*  
property), 32

[illegible]



## E

|  |  |    |  |
|--|--|----|--|
| EllZeeFour   | (class   | in | emod_api.interventions.node_multiplier                           |
|  | <i>emod_api.serialization.dtkFileSupport</i> ), 31 |    | module, 23   |
| emod_api   |  |    | emod_api.interventions.outbreak                                  |
| module, 3  |  |    | module, 24   |
| emod_api.campaign                                  |  |    | emod_api.interventions.simple_vaccine                            |
| module, 36   |  |    | module, 24   |
| emod_api.channelreports                            |  |    | emod_api.interventions.utils                                     |
| module, 3  |  |    | module, 25   |
| emod_api.channelreports.channels                   |  |    | emod_api.migration   |
| module, 3  |  |    | module, 25   |
| emod_api.config                                    |  |    | emod_api.migration.migration                                     |
| module, 4  |  |    | module, 25   |
| emod_api.config.default_from_schema                |  |    | emod_api.schema  |
| module, 4  |  |    | module, 28   |
| emod_api.config.default_from_schema_no_validation  |  |    | emod_api.schema.dtk_post_process_schema                          |
| module, 5  |  |    | module, 28   |
| emod_api.config.dtk_post_process_adhoc_events      |  |    | emod_api.schema.get_schema                                       |
| module, 6  |  |    | module, 28   |
| emod_api.config.dtk_pre_process_adhoc_events       |  |    | emod_api.schema_to_class   |
| module, 6  |  |    | module, 37   |
| emod_api.config.dtk_pre_process_w5ml               |  |    | emod_api.serialization   |
| module, 6  |  |    | module, 28   |
| emod_api.config.from_overrides                     |  |    | emod_api.serialization.CensusAndModPop                           |
| module, 6  |  |    | module, 28   |
| emod_api.config.from_poi_and_binary                |  |    | emod_api.serialization.dtkFileSupport                            |
| module, 6  |  |    | module, 31   |
| emod_api.config.from_schema                        |  |    | emod_api.serialization.dtkFileTools                              |
| module, 7  |  |    | module, 31   |
| emod_api.config.schema_to_config                   |  |    | emod_api.serialization.dtkFileUtility                            |
| module, 7  |  |    | module, 33   |
| emod_api.demographics                              |  |    | emod_api.serialization.SerializedPopulation                      |
| module, 7  |  |    | module, 28   |
| emod_api.demographics.BaseInputFile                |  |    | emod_api.spatialreports  |
| module, 7  |  |    | module, 33   |
| emod_api.demographics.Demographics                 |  |    | emod_api.spatialreports.spatial                                  |
| module, 8  |  |    | module, 33   |
| emod_api.demographics.demographics_utils           |  |    | emod_api.tabularoutput   |
| module, 16   |  |    | module, 34   |
| emod_api.demographics.DemographicsGenerator        |  |    | emod_api.weather   |
| module, 9  |  |    | module, 34   |
| emod_api.demographics.DemographicsInputDataParsers |  |    | emod_api.weather.weather   |
| module, 13   |  |    | module, 34   |
| emod_api.demographics.DemographicsTemplates        |  |    | EquilibriumAgeDistFromBirthAndMortRates()                        |
| module, 13   |  |    | (in module <i>emod_api.demographics.DemographicsTemplates</i> ), |
| emod_api.demographics.grid_construction            |  |    | 15   |
| module, 17   |  |    | EveryoneInitiallySusceptible() (in module                        |
| emod_api.demographics.Node                         |  |    | <i>emod_api.demographics.DemographicsTemplates</i> ),            |
| module, 15   |  |    | 14   |
| emod_api.interventions                             |  |    | examine_file() (in module  |
| module, 18   |  |    | <i>emod_api.migration.migration</i> ), 27                        |
| emod_api.interventions.common                      |  |    | experiment, 39   |
| module, 18   |  |    |  |
| emod_api.interventions.import_pressure             |  |    |  |
| module, 23   |  |    |  |

## F

FAMILY (*emod\_api.migration.migration.Migration* attribute), 26

FEMALE (*emod\_api.migration.migration.Migration* attribute), 26

fill\_nodes\_legacy() (in module *emod\_api.demographics.DemographicsInputDataParsers*), 13

finalize() (*emod\_api.schema\_to\_class.ReadOnlyDict* method), 37

find() (in module *emod\_api.serialization.SerializedPopulation*), 30

flattenConfig() (in module *emod\_api.config.from\_overrides*), 6

flush() (*emod\_api.serialization.SerializedPopulation.SerializedPopulation* method), 29

from\_csv() (*emod\_api.weather.weather.Weather* class method), 36

from\_csv() (in module *emod\_api.demographics.Demographics*), 8

from\_data() (*emod\_api.demographics.Node.Node* class method), 15

from\_dataframe() (in module *emod\_api.demographics.DemographicsGenerator*), 10

from\_demog\_and\_param\_gravity() (in module *emod\_api.migration.migration*), 27

from\_file() (*emod\_api.weather.weather.Metadata* class method), 35

from\_file() (in module *emod\_api.demographics.Demographics*), 8

from\_file() (in module *emod\_api.demographics.DemographicsGenerator*), 12

from\_file() (in module *emod\_api.migration.migration*), 27

from\_params() (in module *emod\_api.demographics.Demographics*), 8

from\_params() (in module *emod\_api.migration.migration*), 27

from\_pop\_csv() (in module *emod\_api.demographics.Demographics*), 8

from\_template\_node() (in module *emod\_api.demographics.Demographics*), 8

FullRisk() (in module *emod\_api.demographics.DemographicsTemplates*), 13

## G

GenderDataType() (*emod\_api.migration.migration.Migration* property), 26

generate\_demographics() (*emod\_api.demographics.DemographicsGenerator.DemographicsGenerator* method), 10

generate\_file() (*emod\_api.demographics.BaseInputFile.BaseInputFile* method), 7

generate\_file() (*emod\_api.demographics.Demographics.DemographicsGenerator* method), 8

generate\_headers() (*emod\_api.demographics.BaseInputFile.BaseInputFile* method), 7

generate\_metadata() (*emod\_api.demographics.DemographicsGenerator.DemographicsGenerator* method), 10

generate\_nodes() (*emod\_api.demographics.DemographicsGenerator.DemographicsGenerator* method), 10

get\_adhocs() (in module *emod\_api.campaign*), 36

get\_bbox() (in module *emod\_api.demographics.grid\_construction*), 18

get\_class\_with\_defaults() (in module *emod\_api.schema\_to\_class*), 37

get\_config\_from\_default\_and\_params() (in module *emod\_api.config.default\_from\_schema\_no\_validation*), 5

get\_default\_for\_complex\_type() (in module *emod\_api.schema\_to\_class*), 37

get\_event() (in module *emod\_api.campaign*), 36

get\_fert\_dist() (in module *emod\_api.demographics.DemographicsTemplates*), 14

get\_grid\_cell\_id() (in module *emod\_api.demographics.grid\_construction*), 17

get\_next\_individual\_suid() (*emod\_api.serialization.SerializedPopulation.SerializedPopulation* method), 29

get\_next\_infection\_suid() (*emod\_api.serialization.SerializedPopulation.SerializedPopulation* method), 29

get\_node() (*emod\_api.demographics.Demographics.DemographicsGenerator* method), 8

get\_node\_ids\_from\_file() (in module *emod\_api.demographics.Demographics*), 8

get\_node\_offsets() (*emod\_api.migration.migration.Migration* method), 27

get\_node\_pops\_from\_params() (in module *emod\_api.demographics.Demographics*), 8

get\_parameters() (in module *emod\_api.serialization.SerializedPopulation*),

30  
 get\_recv\_trigger() (in module *emod\_api.campaign*), 36  
 get\_schema() (in module *emod\_api.campaign*), 36  
 get\_send\_trigger() (in module *emod\_api.campaign*), 36  
 get\_trigger\_list() (in module *emod\_api.campaign*), 36  
 get\_waning\_from\_params() (in module *emod\_api.interventions.utils*), 25  
 get\_xpix\_ypix() (in module *emod\_api.demographics.Node*), 15

## H

Header (class in *emod\_api.channelreports.channels*), 3  
 header() (*emod\_api.channelreports.channels.ChannelReport* property), 4  
 header() (*emod\_api.serialization.dtkFileTools.DtkFile* property), 31  
 high-performance computing (HPC), 39  
 HSB() (in module *emod\_api.interventions.common*), 19

## I

id() (*emod\_api.demographics.Node.Node* property), 15  
 id() (*emod\_api.spatialreports.spatial.SpatialNode* property), 33  
 id() (*emod\_api.weather.weather.WeatherNode* property), 34  
 id\_reference() (*emod\_api.weather.weather.Metadata* property), 35  
 id\_reference() (*emod\_api.weather.weather.Weather* property), 35  
 IDREF\_GRUMP1DEGREE (*emod\_api.migration.migration.Migration* attribute), 26  
 IDREF\_GRUMP2PT5ARCMIN (*emod\_api.migration.migration.Migration* attribute), 26  
 IDREF\_GRUMP30ARCSEC (*emod\_api.migration.migration.Migration* attribute), 26  
 IDREF\_LEGACY (*emod\_api.migration.migration.Migration* attribute), 26  
 IdReference() (*emod\_api.migration.migration.Migration* property), 26  
 init\_resolution\_from\_file() (*emod\_api.demographics.Node.Node* class method), 15  
 InitAgeUniform() (in module *emod\_api.demographics.DemographicsTemplates*), 15  
 InitPrevUniform() (in module *emod\_api.demographics.DemographicsTemplates*), 14  
 InitRiskUniform() (in module *emod\_api.demographics.DemographicsTemplates*), 13  
 InitSusceptConstant() (in module *emod\_api.demographics.DemographicsTemplates*), 14  
 InterpolationType() (*emod\_api.migration.migration.Migration* property), 26  
 interval() (*emod\_api.spatialreports.spatial.SpatialReport* property), 34  
 INTERVENTION (*emod\_api.migration.migration.Migration* attribute), 26  
 InvalidResolution, 9

## L

lat\_lon\_from\_nodeid() (in module *emod\_api.demographics.Node*), 15  
 Layer (class in *emod\_api.migration.migration*), 25  
 LINEAR\_INTERPOLATION (*emod\_api.migration.migration.Migration* attribute), 26  
 load\_default\_config\_as\_rod() (in module *emod\_api.config.default\_from\_schema\_no\_validation*), 5  
 LOCAL (*emod\_api.migration.migration.Migration* attribute), 26  
 lon\_lat\_2\_point() (in module *emod\_api.demographics.grid\_construction*), 18

## M

make\_config\_from\_poi() (in module *emod\_api.config.from\_poi\_and\_binary*), 6  
 make\_config\_from\_poi\_and\_config\_dict() (in module *emod\_api.config.from\_poi\_and\_binary*), 6  
 make\_config\_from\_poi\_and\_config\_file() (in module *emod\_api.config.from\_poi\_and\_binary*), 6  
 make\_config\_from\_poi\_and\_schema() (in module *emod\_api.config.from\_poi\_and\_binary*), 6  
 MALE (*emod\_api.migration.migration.Migration* attribute), 26  
 MAX\_AGE (*emod\_api.migration.migration.Migration* attribute), 26  
 Metadata (class in *emod\_api.weather.weather*), 34  
 metadata() (*emod\_api.weather.weather.Weather* property), 35  
 Migration (class in *emod\_api.migration.migration*), 25

[MigrationType\(\)](#) (*emod\_api.migration.migration.MigrationType* property), 26  
 module  
   [emod\\_api](#), 3  
   [emod\\_api.campaign](#), 36  
   [emod\\_api.channelreports](#), 3  
   [emod\\_api.channelreports.channels](#), 3  
   [emod\\_api.config](#), 4  
   [emod\\_api.config.default\\_from\\_schema](#), 4  
   [emod\\_api.config.default\\_from\\_schema\\_no\\_validation](#), 5  
   [emod\\_api.config.dtk\\_post\\_process\\_adhoc\\_events](#), 6  
   [emod\\_api.config.dtk\\_pre\\_process\\_adhoc\\_events](#), 6  
   [emod\\_api.config.dtk\\_pre\\_process\\_w5ml](#), 6  
   [emod\\_api.config.from\\_overrides](#), 6  
   [emod\\_api.config.from\\_poi\\_and\\_binary](#), 6  
   [emod\\_api.config.from\\_schema](#), 7  
   [emod\\_api.config.schema\\_to\\_config](#), 7  
   [emod\\_api.demographics](#), 7  
   [emod\\_api.demographics.BaseInputFile](#), 7  
   [emod\\_api.demographics.Demographics](#), 8  
   [emod\\_api.demographics.demographics\\_utils](#), 16  
   [emod\\_api.demographics.DemographicsGenerator](#), 23  
   [emod\\_api.demographics.DemographicsInputDataParameters](#), 13  
   [emod\\_api.demographics.DemographicsTemplates](#), 13  
   [emod\\_api.demographics.grid\\_construction](#), 17  
   [emod\\_api.demographics.Node](#), 15  
   [emod\\_api.interventions](#), 18  
   [emod\\_api.interventions.common](#), 18  
   [emod\\_api.interventions.import\\_pressure](#), 23  
   [emod\\_api.interventions.node\\_multiplier](#), 23  
   [emod\\_api.interventions.outbreak](#), 24  
   [emod\\_api.interventions.simple\\_vaccine](#), 24  
   [emod\\_api.interventions.utils](#), 25  
   [emod\\_api.migration](#), 25  
   [emod\\_api.migration.migration](#), 25  
   [emod\\_api.schema](#), 28  
   [emod\\_api.schema.dtk\\_post\\_process\\_schema](#), 28  
   [emod\\_api.schema.get\\_schema](#), 28  
   [emod\\_api.schema\\_to\\_class](#), 37  
   [emod\\_api.serialization](#), 28  
   [emod\\_api.serialization.CensusAndModPop](#), 28  
   [emod\\_api.serialization.dtkFileSupport](#), 31  
   [emod\\_api.serialization.dtkFileTools](#), 31  
   [emod\\_api.serialization.dtkFileUtility](#), 31  
   [emod\\_api.serialization.SerializedPopulation](#), 31  
   [emod\\_api.spatialreports](#), 33  
   [emod\\_api.spatialreports.spatial](#), 33  
   [emod\\_api.tabularoutput](#), 34  
   [emod\\_api.weather](#), 34  
   [emod\\_api.weather.weather](#), 34  
   [MortalityRateByAge\(\)](#) (in module *emod\_api.demographics.DemographicsTemplates*), 14  
   [MortalityStructureNigeriaDHS\(\)](#) (in module *emod\_api.demographics.DemographicsTemplates*), 14  
   [MultiInterventionDistributor\(\)](#) (in module *emod\_api.interventions.common*), 18  
   [N](#)  
   [new\\_intervention\(\)](#) (in module *emod\_api.interventions.import\_pressure*), 23  
   [new\\_intervention\(\)](#) (in module *emod\_api.interventions.node\_multiplier*), 23  
   [new\\_intervention\(\)](#) (in module *emod\_api.interventions.outbreak*), 24  
   [new\\_intervention\(\)](#) (in module *emod\_api.interventions.simple\_vaccine*), 24  
   [new\\_intervention2\(\)](#) (in module *emod\_api.interventions.simple\_vaccine*), 24  
   [new\\_intervention\\_as\\_file\(\)](#) (in module *emod\_api.interventions.import\_pressure*), 23  
   [new\\_intervention\\_as\\_file\(\)](#) (in module *emod\_api.interventions.node\_multiplier*), 24  
   [new\\_intervention\\_as\\_file\(\)](#) (in module *emod\_api.interventions.outbreak*), 24  
   [new\\_intervention\\_as\\_file\(\)](#) (in module *emod\_api.interventions.simple\_vaccine*), 25  
   [new\\_scheduled\\_event\(\)](#) (in module *emod\_api.interventions.node\_multiplier*), 24

NLHTI() (in module *emod\_api.interventions.common*), 19  
 Node (class in *emod\_api.demographics.Node*), 15  
 node\_count() (*emod\_api.demographics.Demographics.Demographics* property), 8  
 node\_count() (*emod\_api.spatialreports.spatial.SpatialReport* property), 33  
 node\_count() (*emod\_api.weather.weather.Metadata* property), 35  
 node\_count() (*emod\_api.weather.weather.Weather* property), 35  
 node\_ID\_from\_lat\_long() (in module *emod\_api.demographics.DemographicsInputDataParsers*), 13  
 node\_ids() (*emod\_api.demographics.Demographics.Demographics* property), 8  
 node\_ids() (*emod\_api.spatialreports.spatial.SpatialReport* property), 33  
 node\_ids() (*emod\_api.weather.weather.Metadata* property), 35  
 node\_ids() (*emod\_api.weather.weather.Weather* property), 35  
 NodeCount() (*emod\_api.migration.migration.Layer* property), 25  
 NodeCount() (*emod\_api.migration.migration.Migration* property), 27  
 nodeid\_from\_lat\_lon() (in module *emod\_api.demographics.Node*), 15  
 NodeOffsets() (*emod\_api.migration.migration.Migration* property), 27  
 Nodes() (*emod\_api.migration.migration.Migration* property), 27  
 nodes() (*emod\_api.serialization.dtkFileTools.DtkFile* property), 32  
 nodes() (*emod\_api.serialization.SerializedPopulation.SerializedPopulation* property), 29  
 nodes() (*emod\_api.spatialreports.spatial.SpatialReport* property), 33  
 nodes() (*emod\_api.weather.weather.Metadata* property), 35  
 nodes() (*emod\_api.weather.weather.Weather* property), 36  
 nodes\_for\_DTK() (in module *emod\_api.demographics.Node*), 15  
 NoInitialPrevalence() (in module *emod\_api.demographics.DemographicsTemplates*), 14  
 NoRisk() (in module *emod\_api.demographics.DemographicsTemplates*), 13  
 num\_channels() (*emod\_api.channelreports.channels.ChannelReport* property), 4  
 num\_channels() (*emod\_api.channelreports.channels.Header* property), 3  
 num\_time\_steps() (*emod\_api.channelreports.channels.ChannelReport* property), 4  
 num\_time\_steps() (*emod\_api.channelreports.channels.Header* property), 3  
 ONE\_FOR\_EACH\_GENDER (*emod\_api.migration.migration.Migration* attribute), 26  
 P  
 PIECEWISE\_CONSTANT (*emod\_api.migration.migration.Migration* attribute), 26  
 point\_2\_grid\_cell\_id\_lookup() (in module *emod\_api.demographics.grid\_construction*), 18  
 PropertyValueChanger() (in module *emod\_api.interventions.common*), 20  
 provenance() (*emod\_api.weather.weather.Metadata* property), 35  
 provenance() (*emod\_api.weather.weather.Weather* property), 35  
 R  
 read() (in module *emod\_api.serialization.dtkFileTools*), 33  
 ReadOnlyDict (class in *emod\_api.schema\_to\_class*), 37  
 recursor() (in module *emod\_api.schema.dtk\_post\_process\_schema*), 28  
 REGIONAL (*emod\_api.migration.migration.Migration* attribute), 26  
 report\_type() (*emod\_api.channelreports.channels.ChannelReport* property), 4  
 report\_type() (*emod\_api.channelreports.channels.Header* property), 3  
 report\_version() (*emod\_api.channelreports.channels.ChannelReport* property), 4  
 report\_version() (*emod\_api.channelreports.channels.Header* property), 3  
 res\_in\_degrees (*emod\_api.demographics.Node.Node* attribute), 15  
 S  
 SAME\_FOR\_BOTH\_GENDERS (*emod\_api.migration.migration.Migration* attribute), 26  
 save() (in module *emod\_api.campaign*), 36  
 ScheduledCampaignEvent() (in module *emod\_api.interventions.common*), 20



|                                  |  |   |
|----------------------------------|--|---|
| schema_to_config()               | (in module<br>emod_api.config.from_poi_and_binary),<br>6                         | (emod_api.demographics.Demographics.Demographics<br>method), 8  |
| schema_to_config_subnode()       | (in module<br>emod_api.config.default_from_schema_no_validation),<br>5           | SetDefaultProperties()<br>(emod_api.demographics.Demographics.Demographics<br>method), 9                |
| SchemaConfigBuilder              | (class in<br>emod_api.config.from_schema), 7                                     | SetDefaultPropertiesFertMort()<br>(emod_api.demographics.Demographics.Demographics<br>method), 9        |
| SchemaConfigBuilder              | (class in<br>emod_api.config.schema_to_config), 7                                | SetIndividualAttributesWithFertMort()<br>(emod_api.demographics.Demographics.Demographics<br>method), 8 |
| SEA                              | (emod_api.migration.migration.Migration at-<br>tribute), 26                      | SetInfectivityMultiplierByNode()<br>(emod_api.demographics.Demographics.Demographics<br>method), 9      |
| seed_by_coverage()               | (in module<br>emod_api.interventions.outbreak), 24                               | SetMinimalNodeAttributes()<br>(emod_api.demographics.Demographics.Demographics<br>method), 8            |
| SerializedPopulation             | (class in<br>emod_api.serialization.SerializedPopulation),<br>28                 | SetNodeDefaultFromTemplate()<br>(emod_api.demographics.Demographics.Demographics<br>method), 9          |
| SerialObject                     | (class in<br>emod_api.serialization.dtkFileSupport), 31                          | SetOverdispersion()<br>(emod_api.demographics.Demographics.Demographics<br>method), 9                   |
| set_demog_distributions()        | (in module<br>emod_api.demographics.demographics_utils),<br>16                   | SimpleSusceptibilityDistribution() (in<br>module emod_api.demographics.DemographicsTemplates),<br>14    |
| set_growing_demographics()       | (in module<br>emod_api.demographics.demographics_utils),<br>17                   | simulation() (emod_api.serialization.dtkFileTools.DtkFileV1<br>property), 32                            |
| set_immune_mod()                 | (in module<br>emod_api.demographics.demographics_utils),<br>16                   | simulation() (emod_api.serialization.dtkFileTools.DtkFileV2<br>property), 32                            |
| set_resolution()                 | (emod_api.demographics.DemographicsGenerator.DemographicsGenerator<br>method), 9 | simulation() (emod_api.serialization.dtkFileTools.DtkFileV3<br>property), 32                            |
| set_risk_mod()                   | (in module<br>emod_api.demographics.demographics_utils),<br>16                   | Snappy (class in emod_api.serialization.dtkFileSupport),<br>31  |
| set_schema()                     | (emod_api.schema_to_class.ReadOnlyDict<br>method), 37                            | SpatialNode (class in<br>emod_api.spatialreports.spatial), 33   |
| set_schema()                     | (in module<br>emod_api.config.from_poi_and_binary),<br>6                         | SpatialReport (class in<br>emod_api.spatialreports.spatial), 33   |
| set_static_demographics()        | (in module<br>emod_api.demographics.demographics_utils),<br>17                   | StandardDiagnostic() (in module<br>emod_api.interventions.common), 23                                   |
| SetConstantSusceptibility()      | (emod_api.demographics.Demographics.Demographics<br>method), 9                   | start() (emod_api.spatialreports.spatial.SpatialReport<br>property), 33                                 |
| SetDefaultFromTemplate()         | (emod_api.demographics.Demographics.Demographics<br>method), 9                   | start_time() (emod_api.channelreports.channels.ChannelReport<br>property), 4                            |
| SetDefaultIndividualAttributes() | (emod_api.demographics.Demographics.Demographics<br>method), 8                   | start_time() (emod_api.channelreports.channels.Header<br>property), 3                                   |
| SetDefaultIndividualProperties() | (emod_api.demographics.Demographics.Demographics<br>method), 8                   | STATIC (emod_api.demographics.DemographicsGenerator.Demographics<br>attribute), 9                       |
| SetDefaultNodeAttributes()       |  | step_size() (emod_api.channelreports.channels.ChannelReport<br>property), 4                             |
|                                  |  | step_size() (emod_api.channelreports.channels.Header<br>property), 3                                    |
|                                  |  | StepFunctionSusceptibility() (in module<br>emod_api.demographics.DemographicsTemplates),                |

14

## T

task, 39

template, 39

time\_stamp() (emod\_api.channelreports.channels.ChannelReport property), 4

time\_stamp() (emod\_api.channelreports.channels.Header property), 3

time\_steps() (emod\_api.spatialreports.spatial.SpatialReport property), 33

title() (emod\_api.channelreports.channels.Channel property), 4

to\_csv() (in module emod\_api.migration.migration), 27

to\_dict() (emod\_api.demographics.Node.Node method), 15

to\_file() (emod\_api.migration.migration.Migration method), 27

to\_file() (emod\_api.schema\_to\_class.ReadOnlyDict method), 37

to\_tuple() (emod\_api.demographics.Node.Node method), 15

Tool() (emod\_api.migration.migration.Migration property), 27

tool() (emod\_api.serialization.dtkFileTools.DtkFile property), 32

TriggeredCampaignEvent() (in module emod\_api.interventions.common), 21

## U

uncompress() (emod\_api.serialization.dtkFileSupport.EllZeeFour class method), 31

uncompress() (emod\_api.serialization.dtkFileSupport.Snappy class method), 31

uncompress() (emod\_api.serialization.dtkFileSupport.Uncompressed class method), 31

uncompress() (in module emod\_api.serialization.dtkFileTools), 31

Uncompressed (class in emod\_api.serialization.dtkFileSupport), 31

units() (emod\_api.channelreports.channels.Channel property), 4

update\_resolution() (emod\_api.weather.weather.Metadata property), 35

update\_resolution() (emod\_api.weather.weather.Weather property), 35

## V

validate\_res\_in\_arcsec() (in module emod\_api.demographics.DemographicsGenerator), 9

version() (emod\_api.serialization.dtkFileTools.DtkFile property), 32

## W

Weather (class in emod\_api.weather.weather), 35

WeatherNode (class in emod\_api.weather.weather), 34

write() (emod\_api.serialization.SerializedPopulation.SerializedPopulation method), 29

write() (in module emod\_api.serialization.dtkFileTools), 33

write\_config\_from\_default\_and\_params() (in module emod\_api.config.default\_from\_schema\_no\_validation), 5

write\_default\_from\_schema() (in module emod\_api.config.default\_from\_schema), 4

write\_default\_from\_schema() (in module emod\_api.config.default\_from\_schema\_no\_validation), 5

write\_file() (emod\_api.channelreports.channels.ChannelReport method), 4

write\_file() (emod\_api.spatialreports.spatial.SpatialReport method), 34

write\_file() (emod\_api.weather.weather.Metadata method), 35

write\_file() (emod\_api.weather.weather.Weather method), 36

## X

xpix\_ypix\_from\_lat\_lon() (in module emod\_api.demographics.Node), 15