

---

**emod-api**

**Institute for Disease Modeling**

**Mar 08, 2022**



# CONTENTS

- 1 emod-api installation 3**
  - 1.1 Prerequisites . . . . . 3
  - 1.2 Installation instructions . . . . . 3
  - 1.3 Windows . . . . . 4
- 2 Frequently asked questions 5**
- 3 API reference 7**
  - 3.1 emod\_api package . . . . . 7
    - 3.1.1 Subpackages . . . . . 7
    - 3.1.2 Submodules . . . . . 58
- 4 Glossary 61**
- Python Module Index 63**
- Index 65**



emod-api is the interface for Epidemiological MODELing software (EMOD) that users of idmtools interact with to create and modify EMOD simulations. Additional functionality for interacting with EMOD is provided in the [emodpy](#) package and [idmtools](#).

See [Welcome to idmtools](#) for a diagram showing how idmtools and each of the related packages are used in an end-to-end workflow using EMOD as the disease transmission model.



## EMOD-API INSTALLATION

Follow the steps below to install emod-api.

### 1.1 Prerequisites

First, ensure the following prerequisites are met.

- Windows 10 Pro or Enterprise, Linux, or Mac
- Python 3.9 64-bit (<https://www.python.org/downloads/release>)
- A file that indicates the pip index-url:
  - Windows
  - Linux

In C:\Users\Username\pip\pip.ini, containing the following:

```
[global]
index-url = https://packages.idmod.org/api/pypi/pypi-production/simple
```

In \$HOME/.config/pip/pip.conf, containing the following:

```
[global]
index-url = https://packages.idmod.org/api/pypi/pypi-production/simple
```

### 1.2 Installation instructions

1. Open a command prompt and create a virtual environment in any directory you choose. The command below names the environment “v-emod-api”, but you may use any desired name:

```
python -m venv v-emod-api
```

2. Activate the virtual environment:

- Windows
- Linux

Enter the following:

```
v-emod-api\Scripts\activate
```

Enter the following:

```
source v-emod-api/bin/activate
```

3. Install emod-api packages:

```
pip install emod-api
```

If you are on Linux, also run:

```
pip install keyrings.alt
```

4. When you are finished, deactivate the virtual environment by entering the following at a command prompt:

```
deactivate
```

## 1.3 Windows

To properly install Shapely on Windows and/or if Snappy compression support is desired or needed, consider downloading and installing the latest python-snappy package for Windows from Christoph Gohlke's python package [web-site](#).



## FREQUENTLY ASKED QUESTIONS

As you get started with emod-api, you may have questions. The most common questions are answered below. If you are using emodpy packages, see the FAQs from those packages for additional guidance.

**I notice that I can import `emod_api.campaign` and use that as an object. I haven't seen that before.** Sure.

Python modules are a lot like singletons. There's no need to add a static class inside that module in many cases.

Think of the module (which can have variables and methods) as a static class.



## API REFERENCE

### 3.1 emod\_api package

**To generate a config.json from a param\_overrides.json (or params-of-interest.json):** python -m emod\_api.config.from\_overrides </path/to/po.json>

**To generate a default config.json based on the schema for a given Eradication binary:** python -m emod\_api.config.from\_schema -e </path/to/Eradication.[exe]> ...

**To generate a schema.json:** python -m emod\_api.schema.get\_schema </path/to/Eradication[.exe]>

For rest of emod-api documentation, please go to <https://github.com/InstituteForDiseaseModeling/emod-api>

#### 3.1.1 Subpackages

##### emod\_api.channelreports package

##### Submodules

##### emod\_api.channelreports.channels module

Module for reading InsetChart.json channels.

```
class emod_api.channelreports.channels.Header (**kwargs)
    Bases: object

    property num_channels
    property dtk_version
    property time_stamp
    property report_type
    property report_version
    property step_size
        >= 1
    property start_time
        >= 0
    property num_time_steps
        >= 1
    as_dictionary() → dict
```

```
class emod_api.channelreports.channels.Channel (title, units, data)
    Bases: object

    property title
    property units
    property data
    as_dictionary() → dict

class emod_api.channelreports.channels.ChannelReport (filename: str = None,
                                                         **kwargs)
    Bases: object

    property header
    property dtk_version
    property time_stamp
    property report_type
    property report_version
        major.minor
    property step_size
        >= 1
    property start_time
        >= 0
    property num_time_steps
        > 0
    property num_channels
    property channel_names
    property channels
        Channel objects keyed on channel name/title
    as_dataframe()
    write_file (filename: str, indent: int = 0, separators=(',', ':'))
        Write inset chart to specified text file.
```

## emod\_api.config package

### Submodules

#### emod\_api.config.default\_from\_schema module

emod\_api.config.default\_from\_schema.**write\_default\_from\_schema** (path\_to\_schema)  
This module is deprecated. Please use default\_from\_schema\_no\_validation.

## emod\_api.config.default\_from\_schema\_no\_validation module

emod\_api.config.default\_from\_schema\_no\_validation.**schema\_to\_config\_subnode**(*schema\_path\_in*,  
*subnode\_list*)

This is the code from regular schema\_to\_config:

```
config = json.load(open("default_config.json"), object_hook=s2c.ReadOnlyDict) os.remove("default_config.json")
```

emod\_api.config.default\_from\_schema\_no\_validation.**get\_default\_config\_from\_schema**(*path\_to\_schema*,  
*schema\_node*,  
*as\_rod=False*,  
*output\_filename*)

This returns a default config object as defined from reading a schema file.

**Parameters** **output\_filename** (*str*) – if not None, the path to write the loaded config to

emod\_api.config.default\_from\_schema\_no\_validation.**write\_default\_from\_schema**(*path\_to\_schema*,  
*output\_filename*,  
*output\_filename*='default\_config.json',  
*schema\_node=True*)

DEPRECATED: This function simply calls get\_default\_config\_from\_schema with specific arguments.

This function writes out a default config file as defined from reading a schema file. It's as good as the schema it's given. Note that this is designed to work with a schema from a disease-specific build, otherwise it may contain a lot of params from other disease types.

emod\_api.config.default\_from\_schema\_no\_validation.**load\_default\_config\_as\_rod**(*config*)

**Parameters** **config** (*string/path*) – path to default or base config.json

**Returns** config (as ReadOnlyDict) with schema ready for schema-verified param sets.

emod\_api.config.default\_from\_schema\_no\_validation.**get\_config\_from\_default\_and\_params**(*config\_path*,  
*set\_fn*,  
*config*,  
*fig=None*)

Use this function to create a valid config.json file from a schema-derived base config, a callback that sets your parameters of interest

**Parameters**

- **config\_path** (*string/path*) – Path to valid config.json
- **config** – read-only dict configuration object. Pass this XOR the config\_path.
- **set\_fn** (*function*) – Callback that sets params with implicit schema enforcement.

**Returns** read-only dict

**Return type** config

emod\_api.config.default\_from\_schema\_no\_validation.**write\_config\_from\_default\_and\_params**(*config\_path*,  
*set\_fn*,  
*config*,  
*fig\_output\_path*)

Use this function to create a valid config.json file from a schema-derived base config, a callback that sets your parameters of interest, and an output path.

**Parameters**

- **config\_path** (*string/path*) – Path to valid config.json

- **set\_fn** (*function*) – Callback that sets params with implicit schema enforcement.
- **config\_out\_path** – (string/path) Path to write new config.json

**Returns** Nothing

### **emod\_api.config.dtk\_post\_process\_adhocevents module**

`emod_api.config.dtk_post_process_adhocevents.application(output_path)`

### **emod\_api.config.dtk\_pre\_process\_adhocevents module**

`emod_api.config.dtk_pre_process_adhocevents.do_mapping_from_events(config, ad-  
hoc_events)`

Given a config file, a campaign file, and a list of `ad_hoc_events`, do the mappings. The `ad_hoc_event` list originally came from scraping an existing campaign file but now comes from `emod_api.campaign`.

`emod_api.config.dtk_pre_process_adhocevents.application(config)`

This is the public interface function to the submodule.

### **emod\_api.config.dtk\_pre\_process\_w5ml module**

`emod_api.config.dtk_pre_process_w5ml.application(filename)`

### **emod\_api.config.from\_overrides module**

`emod_api.config.from_overrides.flattenConfig(configjson_path,  
new_config_name='config.json')`

Historically called ‘flattening’ but really a function that takes a parameter override json config that includes a `Default_Config_Path` and produces a `config.json` from the two.

### **emod\_api.config.from\_poi\_and\_binary module**

`emod_api.config.from_poi_and_binary.schema_to_config(schema_path_in)`

Purpose: Take a `schema.json` and return a “smart” config object that can be assigned to with schema-enforcement. Use in conjunction with `to_file()`. Params: `schema_path_in` (str/path) Returns: config (smart dict)

`emod_api.config.from_poi_and_binary.set_schema(schema_path_in)`

`emod_api.config.from_poi_and_binary.make_config_from_poi_and_config_dict(start_config_dict,  
poi_set_param_fn)`

Use this function to create a `config.json` from an existing param dict (defaults or base) and a function with your parameter overrides or parameters of interest.

`emod_api.config.from_poi_and_binary.make_config_from_poi_and_config_file(start_config_path,  
poi_set_param_fn)`

Use this function to create a `config.json` from an existing config json file (defaults or base) and a function with your parameter overrides or parameters of interest.

`emod_api.config.from_poi_and_binary.make_config_from_poi_and_schema(schema_path,  
poi_set_param_fn)`

Use this function to create a `config.json` from an existing schema json file and a function with your parameter overrides or parameters of interest.

`emod_api.config.from_poi_and_binary.make_config_from_poi(eradication_path,  
poi_set_param_fn)`

This function uses `emod_api` to produce a guaranteed working config starting with an Eradication binary and a parameters-of-interest python function. This is a usable and useful function.

#### Parameters

- **eradication\_path** (*string*) – Fully-qualified path to Eradication binary that can be invoked to get a schema.
- **poi\_set\_param\_fn** (*function*) – User-provided function/callback/hook that looks like:
- **set\_params** (*def*) – `config.parameters.<param_name> = <schema valid param_value>`  
`<repeat for each param> return config`

**Returns** Hardcoded configuration filename written to pwd.

**Return type** “config.json” (string)

### emod\_api.config.from\_schema module

argparse for command-line usage -s schema file -m model name -c config file

**Sample code:** `from emod_api.config import schema_to_config as s2c builder = s2c.SchemaConfigBuilder()  
builder.enumerate_params() builder.validate_dependent_params() builder.write_config_file()`

That will look for a local file called `schema.json` and produce a file called `config.json` that should work with an Eradication binary that produced the `schema.json`.

**To build a default config for MALARIA\_SIM, do:** `builder = s2c.SchemaConfigBuilder(model="MALARIA_SIM")`

To generate a `schema.json` file from a binary, see help text for `emod_api.schema`.

```
class emod_api.config.from_schema.SchemaConfigBuilder (schema_name='schema.json',
                                                         model='GENERIC_SIM',
                                                         config_out='config.json',
                                                         debug=False)
```

Bases: `object`

### emod\_api.config.schema\_to\_config module

```
class emod_api.config.schema_to_config.SchemaConfigBuilder (schema_name='schema.json',
                                                             model='GENERIC_SIM',
                                                             con-
                                                             fig_out='config.json',
                                                             debug=False)
```

Bases: `emod_api.config.from_schema.SchemaConfigBuilder`

Deprecated in API v.1. Supported temporarily as pass-through functionality to `emod_api.config.from_schema`.

## emod\_api.demographics package

### Submodules

#### emod\_api.demographics.BaseInputFile module

```
class emod_api.demographics.BaseInputFile.BaseInputFile (idref)
    Bases: object

    abstract generate_file (name)

    generate_headers (extra=None)
```

#### emod\_api.demographics.Demographics module

```
emod_api.demographics.Demographics.from_template_node (lat=0, lon=0, pop=1000000,  
                                                         name='Erewhon',  
                                                         forced_id=1)
```

Create a single-node Demographics instance from a few params.

```
emod_api.demographics.Demographics.from_file (base_file)
    Create a Demographics instance from an existing demographics file.
```

```
emod_api.demographics.Demographics.get_node_ids_from_file (demographics_file)
    Get a list of node ids from a demographics file.
```

```
emod_api.demographics.Demographics.get_node_pops_from_params (tot_pop,  
                                                                num_nodes,  
                                                                frac_rural)

    Get a list of node populations from the params used to create a sparsely parameterized multi-node Demographics instance.
```

```
emod_api.demographics.Demographics.from_params (tot_pop=1000000, num_nodes=100,  
                                                  frac_rural=0.3, id_ref='from_params')

    Create an EMOD-compatible Demographics object with the population and number of nodes specified. frac_rural determines what fraction of the population gets put in the 'rural' nodes, which means all nodes besides node 1. Node 1 is the 'urban' node.
```

```
emod_api.demographics.Demographics.from_csv (input_file, res=0.008333333333333333,  
                                              id_ref='from_csv')

    Create an EMOD-compatible Demographics instance from a csv population-by-node file.
```

```
emod_api.demographics.Demographics.from_pop_csv (pop_filename_in,  
                                                  pop_filename_out='spatial_gridded_pop_dir',  
                                                  site='No_Site')
```

```
class emod_api.demographics.Demographics.Demographics (nodes, idref='Gridded  
                                                         world grump2.5arcmin,  
                                                         base_file=None)
```

Bases: *emod\_api.demographics.BaseInputFile.BaseInputFile*

This class is a container of data necessary to produce a EMOD-valid demographics input file. It can be initialized from an existing valid demographics.json type file or from an array of valid Nodes.

**apply\_overlay** (*overlay\_nodes: list*)

Parameters **overlay\_nodes** – Overlay list of nodes over existing nodes in demographics

Returns



**to\_dict ()**

**generate\_file** (*name='demographics.json'*)

Write the contents of the instance to an EMOD-compatible (JSON) file.

**property\_node\_ids**

Return the list of (geographic) node ids.

**property\_nodes**

**property\_node\_count**

Return the number of (geographic) nodes.

**get\_node** (*nodeid*)

Return the node identified by nodeid. Search either name or actual id :param nodeid: :return:

**SetIndividualAttributesWithFertMort** (*CrudeBirthRate=0.04, CrudeMortRate=0.02*)

**AddIndividualPropertyAndHINT** (*Property: str, Values: List[str], InitialDistribution: List[float] = None, TransmissionMatrix: List[List[float]] = None, Transitions: List = None*)

Add Individual Properties, including an optional HINT configuration matrix.

#### Parameters

- **Property** – property (if property already exists an exception is raised).
- **Values** – property values.
- **InitialDistribution** – initial distribution.
- **TransmissionMatrix** – transmission matrix.

**Returns** N/A/

**AddAgeDependentTransmission** (*Age\_Bin\_Edges\_In\_Years=[0, 1, 2, - 1], TransmissionMatrix=[[1.0, 1.0, 1.0], [1.0, 1.0, 1.0], [1.0, 1.0, 1.0]]*)

Set up age-based HINT. Since ages are a first class property of an agent, Age\_Bin is a special case of HINT. We don't specify a distribution, but we do specify the age bin edges, in units of years. So if Age\_Bin\_Edges\_In\_Years = [ 0, 10, 65, -1 ] it means you'll have 3 age buckets: 0-10, 10-65, & 65+. Always 'book-end' with 0 and -1.

#### Parameters

- **Age\_Bin\_Edges\_In\_Years** – array (or list) of floating point values, representing the age bucket boundaries.
- **TransmissionMatrix** – 2-D array of floating point values, representing epi connect-edness of the age buckets.

**SetDefaultIndividualAttributes ()**

NOTE: This is very Measles-ish. We might want to move into MeaslesDemographics

**SetMinimalNodeAttributes ()**

**SetBirthRate** (*birth\_rate*)

Set Default birth rate to birth\_rate. Turn on Vital Dynamics and Births implicitly.

**SetMortalityRate** (*mortality\_rate, node\_ids: List[int] = None*)

Set constant mortality rate to mort\_rate. Turn on Enable\_Natural\_Mortality implicitly.

**SetMortalityDistribution** (*distribution: emod\_api.demographics.PropertiesAndAttributes.IndividualAttributes.MortalityDistribution = None, node\_ids: List[int] = None*)

Set a default mortality distribution for all nodes or per node. Turn on Enable\_Natural\_Mortality implicitly.  
:param distribution: distribution :param node\_ids: a list of node\_ids

**Returns** None

**SetAgeDistribution** (*distribution: emod\_api.demographics.PropertiesAndAttributes.IndividualAttributes.AgeDistribution, node\_ids: List[int] = None*)

Set a default age distribution for all nodes or per node. Sets distribution type to COMPLEX implicitly.  
:param distribution: age distribution :param node\_ids: a list of node\_ids

**Returns** None

**SetDefaultNodeAttributes** (*birth=True*)

Set the default NodeAttributes (Altitude, Airport, Region, Seaport), optionally including birth, which is most important actually.

**SetDefaultIndividualProperties** ()

Initialize Individual Properties to empty.

**SetDefaultProperties** ()

Set a bunch of defaults (age structure, initial susceptibility and initial prevalence) to sensible values.

**SetDefaultPropertiesFertMort** (*CrudeBirthRate=0.04, CrudeMortRate=0.02*)

Set a bunch of defaults (birth rates, death rates, age structure, initial susceptibility and initial prevalence) to sensible values.

**SetDefaultFromTemplate** (*template, setter\_fn=None*)

Add to the default IndividualAttributes using the input template (raw json) and set corresponding config values per the setter\_fn. The template should always be constructed by a function in DemographicsTemplates. Eventually this function will be hidden and only accessed via separate application-specific API functions such as the ones below.

**SetNodeDefaultFromTemplate** (*template, setter\_fn*)

Add to the default NodeAttributes using the input template (raw json) and set corresponding config values per the setter\_fn. The template should always be constructed by a function in DemographicsTemplates. Eventually this function will be hidden and only accessed via separate application-specific API functions such as the ones below.

**SetEquilibriumAgeDistFromBirthAndMortRates** (*CrudeBirthRate=0.04, CrudeMortRate=0.02*)

Set the initial ages of the population to a sensible equilibrium profile based on the specified input birth and death rates. Note this does not set the fertility and mortality rates.

**SetInitialAgeExponential** (*rate=0.0001068, description=""*)

Set the initial age of the population to an exponential distribution with a specified rate. :param rate: rate :param description: description, why was this distribution chosen

**SetInitialAgeLikeSubSaharanAfrica** (*description=""*)

Set the initial age of the population to a overly simplified structure that sort of looks like sub-Saharan Africa. This uses the SetInitialAgeExponential. :param description: description, why was this age chosen?

**SetOverdispersion** (*new\_overdispersion\_value, nodes=[]*)

Set the overdispersion value for the specified nodes (all if empty).

**SetConstantSusceptibility** ()

Set the initial susceptibilty for each new individual to a constant value of 1.0.

**SetInitPrevFromUniformDraw** (*min\_init\_prev, max\_init\_prev, description=""*)

Set Initial Prevalence (one value per node) drawn from an uniform distribution. :param min\_init\_prev: minimal initial prevalence :param max\_init\_prev: maximal initial prevalence :param description: description, why were these parameters chosen?

**SetConstantRisk** (*risk=1, description=""*)

Set the initial risk for each new individual to the same value, defaults to full risk :param risk: risk :param description: description, why was this parameter chosen?

**SetHeteroRiskUniformDist** (*min\_risk=0, max\_risk=1*)

Set the initial risk for each new individual to a value drawn from a uniform distribution.

**SetHeteroRiskLognormalDist** (*mean=1.0, sigma=0*)

Set the initial risk for each new individual to a value drawn from a log-normal distribution.

**SetHeteroRiskExponDist** (*mean=1.0*)

Set the initial risk for each new individual to a value drawn from an exponential distribution.

**infer\_natural\_mortality** (*file\_male, file\_female, interval\_fit=[1970, 1980],  
which\_point='mid', predict\_horizon=2050, csv\_out=False, n=0,  
results\_scale\_factor=0.0027397260273972603*)

Calculate and set the expected natural mortality by age, sex, and year from data, predicting what it would have been without disease (usually HIV).

```
class emod_api.demographics.Demographics.DemographicsOverlay (nodes=None,
                                                                meta_data: dict
                                                                = None, individual_attributes=None,
                                                                node_attributes=None,
                                                                mortality_distribution=None)

Bases: object

to_dict ()

to_file (file_name='demographics_overlay.json')
```

## emod\_api.demographics.DemographicsGenerator module

**exception** emod\_api.demographics.DemographicsGenerator.InvalidResolution

Bases: `BaseException`

Custom Exception

**class** emod\_api.demographics.DemographicsGenerator.DemographicsType (*value*)

Bases: `enum.Enum`

**STATIC** = 'static'

emod\_api.demographics.DemographicsGenerator.arcsec\_to\_deg (*arcsec: float*) → `float`

Arc second to degrees :param arcsec: arcsecond as float

**Returns** arc second converted to degrees

emod\_api.demographics.DemographicsGenerator.validate\_res\_in\_arcsec (*res\_in\_arcsec*)

Validate that the resolution is valid :param res\_in\_arcsec: Resolution in arsecond. Supported values can be found in VALID\_RESOLUTIONS

**Returns** None.

**Raise:** `KeyError`: If the resolution is invalid, a key error is raised

```
class emod_api.demographics.DemographicsGenerator.DemographicsGenerator (nodes,
                                                                    con-
                                                                    cerns:
                                                                    Op-
                                                                    tional[Union[emod_api.dtk
                                                                    List[emod_api.dtk_tools.de
                                                                    =
                                                                    None,
                                                                    res_in_arcsec='custom',
                                                                    node_id_from_lat_long=Fa
```

Bases: `object`

Generates demographics file based on population input file. The population input file is csv with structure

node\_label\*, lat, lon, pop\*

\*-ed columns are optional

**set\_resolution** (res\_in\_arcsec)

The canonical way to set arcsecond/degree resolutions on a DemographicsGenerator object. Verifies everything is set properly

**Parameters** **res\_in\_arcsec** – The requested resolution. e.g. 30, 250, ‘custom’

Returns: No return value.

**generate\_nodes** (defaults)

generate demographics file nodes

The process for generating nodes starts with looping through the loaded demographics nodes. For each node, we: 1. First determine the node’s id. If the node has a forced id set, we use that. If we are using a custom resolution, we use the index (ie 1, 2, 3...). Lastly, we build the node id from the lat and lon id of the node

2. We then start to populate the node\_attributes and individual attributes for the current node. The node\_attributes will have data loaded from the initial nodes fed into DemographicsGenerator. The individual attributes start off as an empty dict.

3. We next determine the birthrate for the node. If the node attributes contains a Country element, we first lookup the birthrate from the World Pop data. We then build a MortalityDistribution configuration with country specific configuration elements and add that to the individual attributes. If there is no Country element in the node attributes, we set the birth rate to the default\_birth\_rate. This value was set in initialization of the DemographicsGenerator to the birth rate of the specified country from the world pop data

4. We then calculate the per\_node\_birth\_rate using get\_per\_node\_birth\_rate and then set the birth rate on the node attributes

5. We then calculate the equilibrium\_age\_distribution and use that to create the AgeDistribution in individual\_attributes

6. We then add each new demographic node to a list to end returned at the end of the function

**generate\_metadata** ()

generate demographics file metadata

**generate\_demographics** ()

return all demographics file components in a single dictionary; a valid DTK demographics file when dumped as json

```

emod_api.demographics.DemographicsGenerator.from_dataframe(df, demographics_filename: Optional[str] = None, concerns: Optional[Union[emod_api.dtk_tools.demographics.DemographicsNodeGeneratorConcern, List[emod_api.dtk_tools.demographics.DemographicsNodeGeneratorConcern]]] = None, res_in_arcsec='custom', node_id_from_lat_long=True, default_population: int = 1000, load_other_columns_as_attributes=False, include_columns: Optional[List[str]] = None, exclude_columns: Optional[List[str]] = None, nodeid_column_name: Optional[str] = None, latitude_column_name: str = 'lat', longitude_column_name: str = 'lon', population_column_name: str = 'pop')

```

Generates a demographics file from a dataframe

#### Parameters

- **df** – pandas DataFrame containing demographics information. Must contain all the columns specified by latitude\_column\_name, longitude\_column\_name. The population\_column\_name is optional. If not found, we fall back to default\_population
- **demographics\_filename** – demographics file to save the demographics file too. This is optional
- **concerns** (*Optional[DemographicsNodeGeneratorConcern]*) – What DemographicsNodeGeneratorConcern should
- **apply**. If not specified, we use the DefaultWorldBankEquilibriumConcern (we) –
- **res\_in\_arcsec** – Resolution in Arcseconds
- **node\_id\_from\_lat\_long** – Determine if we should calculate the node id from the lat long. By default this is true unless you also set res\_in\_arcsec to CUSTOM\_RESOLUTION. When not using lat/long for ids, the first fallback it to check the node for a forced id. If that is not found, we assign it an index as id
- **load\_other\_columns\_as\_attributes** – Load additional columns from a csv file as node attributes
- **include\_columns** – A list of columns that should be added as node attributes from the csv file. To be used in conjunction with load\_other\_columns\_as\_attributes.
- **exclude\_columns** – A list of columns that should be ignored as attributes when

`load_other_columns_as_attributes` is enabled. This cannot be combined with `include_columns`

- **default\_population** – Default population. Only used if `population_column_name` does not exist
- **nodeid\_column\_name** – Column name to load nodeid values from
- **latitude\_column\_name** – Column name to load latitude values from
- **longitude\_column\_name** – Column name to load longitude values from
- **population\_column\_name** – Column name to load population values from

**Returns** demographics file as a dictionary

```
emod_api.demographics.DemographicsGenerator.from_file(population_input_file:
    str,          demographics_filename: Optional[str]
    = None, concerns: Optional[Union[emod_api.dtk_tools.demographics.DemographicsNodeGeneratorConcern,
    List[emod_api.dtk_tools.demographics.DemographicsNodeGeneratorConcern]]]
    = None,
    res_in_arcsec='custom',
    node_id_from_lat_long=True,
    default_population:
    int          = 1000,
    load_other_columns_as_attributes=False,
    include_columns: Optional[List[str]] = None,
    exclude_columns: Optional[List[str]] = None,
    nodeid_column_name: Optional[str] = None,
    latitude_column_name: str = 'lat', longitude_column_name: str = 'lon', population_column_name: str = 'pop')
```

Generates a demographics file from a CSV population

#### Parameters

- **population\_input\_file** – CSV population file. Must contain all the columns specified by `latitude_column_name`, `longitude_column_name`. The `population_column_name` is optional. If not found, we fall back to `default_population`
- **demographics\_filename** – demographics file to save the demographics file too. This is optional
- **concerns** (*Optional[DemographicsNodeGeneratorConcern]*) – What `DemographicsNodeGeneratorConcern` should
- **apply**. If not specified, we use the `DefaultWorldBankEquilibriumConcern` (we) –
- **res\_in\_arcsec** – Resolution in Arcseconds
- **node\_id\_from\_lat\_long** – Determine if we should calculate the node id from the lat long. By default this is true unless you also set `res_in_arcsec` to `CUSTOM_RESOLUTION`.

When not using lat/long for ids, the first fallback is to check the node for a forced id. If that is not found, we assign it an index as id

- **load\_other\_columns\_as\_attributes** – Load additional columns from a csv file as node attributes
- **include\_columns** – A list of columns that should be added as node attributes from the csv file. To be used in conjunction with load\_other\_columns\_as\_attributes.
- **exclude\_columns** – A list of columns that should be ignored as attributes when load\_other\_columns\_as\_attributes is enabled. This cannot be combined with include\_columns
- **default\_population** – Default population. Only used if population\_column\_name does not exist
- **nodeid\_column\_name** – Column name to load nodeid values from
- **latitude\_column\_name** – Column name to load latitude values from
- **longitude\_column\_name** – Column name to load longitude values from
- **population\_column\_name** – Column name to load population values from

**Returns** demographics file as a dictionary

### emod\_api.demographics.DemographicsInputDataParsers module

This file contains functions used to read, parse, and process input data files and convert the data into Nodes. Plus utility support function that are part of that process. There is no fixed fileformat for the incoming data. Any file format that is supported by a function here is a supported format. You can add to this.

```
emod_api.demographics.DemographicsInputDataParsers.node_ID_from_lat_long (lat,
                                                                              long,
                                                                              res=0.008333333333333333)

emod_api.demographics.DemographicsInputDataParsers.duplicate_nodeID_check (nodelist)

emod_api.demographics.DemographicsInputDataParsers.fill_nodes_legacy (node_info,
                                                                          De-
                                                                          moDf,
                                                                          res=0.008333333333333333)

emod_api.demographics.DemographicsInputDataParsers.ConstructNodesFromDataFrame (node_info,
                                                                                    ex-
                                                                                    tra_data_column
                                                                                    res=0.008333333333333333)
```

### emod\_api.demographics.DemographicsTemplates module

```
emod_api.demographics.DemographicsTemplates.NoRisk ()
    NoRisk puts everyone at 0 risk.

emod_api.demographics.DemographicsTemplates.FullRisk (demog, description="")
    FullRisk puts everyone at 100% risk.

emod_api.demographics.DemographicsTemplates.InitRiskUniform (demog, min_lim=0,
                                                                max_lim=1, descrip-
                                                                tion="")
    InitRiskUniform puts everyone at somewhere between 0% risk and 100% risk, drawn uniformly.
```

**Parameters**

- **min** (*float*) – Low end of uniform distribution. Must be  $\geq 0$ ,  $< 1$ .
- **max** (*float*) – High end of uniform distribution. Must be  $\geq \text{min}$ ,  $\leq 1$ .
- **description** – Why were these values chosen?

**Returns** json object aka python dict that can be directly passed to `Demographics::SetDefaultFromTemplate`

**Raises** None –

```
emod_api.demographics.DemographicsTemplates.InitRiskLogNormal(demog,  
                                                             mean=0.0,  
                                                             sigma=1.0)
```

`InitRiskLogNormal` puts everyone at somewhere between 0% risk and 100% risk, drawn from LogNormal.

**Parameters**

- **mean** (*float*) – Mean of lognormal distribution.
- **sigma** (*float*) – Sigma of lognormal distribution.

**Returns** json object aka python dict that can be directly passed to `Demographics::SetDefaultFromTemplate`

**Raises** None –

```
emod_api.demographics.DemographicsTemplates.InitRiskExponential(demog,  
                                                                    mean=1.0)
```

`InitRiskExponential` puts everyone at somewhere between 0% risk and 100% risk, drawn from Exponential.

**Parameters** **mean** (*float*) – Mean of exponential distribution.

**Returns** json object aka python dict that can be directly passed to `Demographics::SetDefaultFromTemplate`

**Raises** None –

```
emod_api.demographics.DemographicsTemplates.NoInitialPrevalence(demog)
```

`NoInitialPrevalence` disables initial prevalence; outbreak seeding must be done from an Outbreak intervention (or serialized population).

**Parameters** **demog** – `emod-api.demographics.Demographics` instance.

**Returns** None

**Raises** None –

```
emod_api.demographics.DemographicsTemplates.InitPrevUniform(demog, low_prev,  
                                                             high_prev, descrip-  
                                                             tion="")
```

```
emod_api.demographics.DemographicsTemplates.InitSusceptConstant(demog)
```

```
emod_api.demographics.DemographicsTemplates.EveryoneInitiallySusceptible(demog,  
                                                                              set-  
                                                                              ting=1.0)
```

```
emod_api.demographics.DemographicsTemplates.StepFunctionSusceptibility(demog,  
                                                                           pro-  
                                                                           tected_setting=0.0,  
                                                                           thresh-  
                                                                           old_age=1825.0)
```



```
emod_api.demographics.DemographicsTemplates.SimpleSusceptibilityDistribution(demog,
                                                                              mean-
AgeAt-
In-
fec-
tion=2.5)
```

```
emod_api.demographics.DemographicsTemplates.DefaultSusceptibilityDistribution(demog)
```

```
emod_api.demographics.DemographicsTemplates.MortalityRateByAge(demog,
                                                                  age_bins,
                                                                  mort_rates)
```

Set (non-disease) mortality rates by age bins. No checks are done on input arrays.

#### Parameters

- **age\_bins** – list of age bins, with ages in years.
- **mort\_rates** – list of mortality rates, where mortality rate is daily probability of dying..

**Returns** N/A.

```
emod_api.demographics.DemographicsTemplates.MortalityStructureNigeriaDHS(demog)
```

```
emod_api.demographics.DemographicsTemplates.get_fert_dist(path_to_csv)
```

This function takes a fertility csv file (by year and age bin) and populates a DTK demographics.json file, and the corresponding config file to do individual pregnancies by age and year from data.

#### Parameters

- **demog** – emod\_api.demographics.Demographics instance.
- **path\_to\_csv** – absolute path to csv input file. The file should have columns for 5-year age bins
- **"15-19", etc. up to "45-49", and a column named "Years" with values like "1950-1955". (labelled) –**
- **can be extra columns and the columns can be anywhere. (There) –**

**Returns** (complex) dictionary. fertility distribution, ready to be added to demographics file.

```
emod_api.demographics.DemographicsTemplates.InitAgeUniform(demog)
```

```
emod_api.demographics.DemographicsTemplates.AgeStructureUNWPP(demog)
```

## emod\_api.demographics.Node module

```
class emod_api.demographics.Node.Node(lat, lon, pop, name: str = None, area: float =
                                     None, forced_id: int = None, individual_attributes:
                                     emod_api.demographics.PropertiesAndAttributes.IndividualAttributes
                                     = None, individual_properties:
                                     emod_api.demographics.PropertiesAndAttributes.IndividualProperties
                                     = None, node_attributes:
                                     emod_api.demographics.PropertiesAndAttributes.NodeAttributes
                                     = None, meta: dict = None)
```

Bases: *emod\_api.demographics.Updateable.Updateable*

**default\_population** = 1000

**res\_in\_degrees** = 0.041666666666666664

**to\_dict**() → *dict*

```
to_tuple()
property id
classmethod init_resolution_from_file(fn)
classmethod from_data(data: dict)
    Function used to create the node object from data (most likely coming from a demographics file) :param
    data: :return:
property pop
property lon
property lat
property birth_rate
class emod_api.demographics.Node.OverlayNode(node_id, latitude=None, longitude=None,
                                              initial_population=None, **kwargs)
    Bases: emod_api.demographics.Node.Node
    Node that only requires an ID. Use to overlay a Node.
emod_api.demographics.Node.get_xpix_ypix(nodeid)
emod_api.demographics.Node.lat_lon_from_nodeid(nodeid, res_in_deg=0.041666666666666664)
emod_api.demographics.Node.xpix_ypix_from_lat_lon(lat, lon,
                                                  res_in_deg=0.041666666666666664)
emod_api.demographics.Node.nodeid_from_lat_lon(lat, lon,
                                                res_in_deg=0.041666666666666664)
emod_api.demographics.Node.nodes_for_DTK(filename, nodes)
emod_api.demographics.Node.basicNode(lat: float = 0, lon: float = 0, pop: int = 1000000, name:
                                     str = 'node_name', forced_id: int = 1)
```

### emod\_api.demographics.PreDefinedDistributions module

```
class emod_api.demographics.PreDefinedDistributions.ConstantDistribution(distribution)
    Bases: object
    Wrapping this class around a Distributions disables __setattr__ and makes the wrapped objects constant.
to_dict()
    Calls the to_dict() method of the wrapped distribution.
copy()
    Creates a deepcopy of the wrapped Distribution object.
```

## emod\_api.demographics.PropertiesAndAttributes module

```
class emod_api.demographics.PropertiesAndAttributes.IndividualProperty (initial_distribution:
    List[float]
    =
    None,
    prop-
erty=None,
    val-
ues:
    List[float]
    =
    None,
    tran-
si-
tions:
    List[float]
    =
    None,
    trans-
mis-
sion_matrix:
    List[float]
    =
    None)
```

Bases: *emod\_api.demographics.Updateable.Updateable*

**to\_dict**() → dict

```
class emod_api.demographics.PropertiesAndAttributes.IndividualProperties (individual_property:
    emod_api.demographics.F
    =
    None)
```

Bases: *emod\_api.demographics.Updateable.Updateable*

**add**(*individual\_property*)

**add\_parameter**(*key, value*)

Adds a user defined key-value pair to demographics. :param key: Key :param value: Value :return: None

**to\_dict**() → dict

```
class emod_api.demographics.PropertiesAndAttributes.IndividualAttributes (age_distribution_flag=None,
age_distribution1=None,
age_distribution2=None,
age_distribution=None,
prevalence_distribution_flag=None,
prevalence_distribution1=None,
prevalence_distribution2=None,
immunity_distribution_flag=None,
immunity_distribution1=None,
immunity_distribution2=None,
risk_distribution_flag=None,
risk_distribution1=None,
risk_distribution2=None,
migration_heterogeneity_distribution=None,
migration_heterogeneity_distribution1=None,
migration_heterogeneity_distribution2=None,
mortality_distribution=None,
susceptibility_distribution=None)

Bases: emod_api.demographics.Updateable.Updateable

class SusceptibilityDistribution (distribution_values: List[float] = None, result_scale_factor=None, result_values=None)
Bases: emod_api.demographics.Updateable.Updateable
to_dict() → dict

class AgeDistribution (distribution_values=None, result_scale_factor=None, result_values=None)
Bases: emod_api.demographics.Updateable.Updateable
to_dict() → dict
from_dict(age_distribution: dict)
```

```
class MortalityDistribution (axis_names: List[str] = None, axis_scale_factors: List[float]
                             = None, axis_units=None, num_distribution_axes=None,
                             num_population_axes=None, num_population_groups=None,
                             population_groups=None, result_scale_factor=None, re-
                             sult_units=None, result_values=None)
    Bases: emod_api.demographics.Updateable.Updateable
    to_dict () → dict
    from_dict (mortality_distribution: dict)

to_dict () → dict
from_dict (individual_attributes: dict)
```

```
class emod_api.demographics.PropertiesAndAttributes.NodeAttributes (airport:
    int =
    None, alti-
    tude=None,
    area: float
    = None,
    birth_rate:
    float =
    None,
    coun-
    try=None,
    growth_rate:
    float =
    None,
    name: str
    = None,
    latitude:
    float =
    None,
    longitude:
    float =
    None,
    metadata:
    dict =
    None, ini-
    tial_population:
    int =
    None,
    region: int
    = None,
    seaport:
    int =
    None, lar-
    val_habitat_multiplier:
    List[float]
    = None,
    ini-
    tial_vectors_per_species=None,
    infectiv-
    ity_multiplier:
    float =
    None, ex-
    tra_attributes:
    dict =
    None)

Bases: emod_api.demographics.Updateable.Updateable

from_dict (node_attributes: dict)

to_dict () → dict
```

## emod\_api.demographics.Updateable module

**class** emod\_api.demographics.Updateable.Updateable

Bases: `object`

(Base) class that provides update() method for each class that inherits from this class.

**to\_dict** () → `dict`

**update** (overlay\_object)

Updates an object with the values from overlay\_object. :param overlay\_object: Object that is used to update self :return: None

**add\_parameter** (key, value)

Adds a user defined key-value pair to demographics. :param key: Key :param value: Value :return: None

## emod\_api.demographics.demographics\_utils module

emod\_api.demographics.demographics\_utils.**set\_risk\_mod**(filename, distribution, par1, par2)

Set the RiskDistributionFlag, RiskDistribution1 and RiskDistribution2 in a demographics file.

### Parameters

- **filename** – The demographics file location
- **distribution** – The selected distribution (need to come from `distribution_types`)
- **par1** – Parameter 1 of the distribution
- **par2** – Parameter 2 of the distribution (may be unused depending on the selected distribution)

**Returns** Nothing

emod\_api.demographics.demographics\_utils.**set\_immune\_mod**(filename, distribution, par1, par2)

Set the ImmunityDistributionFlag, ImmunityDistribution1 and ImmunityDistribution2 in a demographics file.

### Parameters

- **filename** – The demographics file location
- **distribution** – The selected distribution (need to come from `distribution_types`)
- **par1** – Parameter 1 of the distribution
- **par2** – Parameter 2 of the distribution (may be unused depending on the selected distribution)

**Returns** Nothing

emod\_api.demographics.demographics\_utils.**apply\_to\_defaults\_or\_nodes**(demog, fn, \*args)

Apply the fn function either to the Defaults dictionary or to each of the nodes depending if the IndividualAttributes parameter is present in the Defaults or not.

### Parameters

- **demog** – The demographic file represented as a dictionary
- **fn** – The function to apply the Defaults or individual nodes
- **args** – Argument list needed by fn

**Returns** Nothing

`emod_api.demographics.demographics_utils.set_demog_distributions` (*filename, distributions*)

Apply distributions to a given demographics file. The distributions needs to be formatted as a list of (name, distribution, par1, par2) with:

- **name:** Immunity, Risk, Age, Prevalence or MigrationHeterogeneity
- **distribution:** One distribution contained in `distribution_types`
- **par1, par2:** the values for the distribution parameters

```
# Set the PrevalenceDistribution to a uniform distribution with 0.1 and 0.2
# and the ImmunityDistributionFlag to a constant distribution with 1
demog = json.load(open("demographics.json", "r"))
distributions = list()
distributions.add(("Prevalence", "UNIFORM_DISTRIBUTION", 0.1, 0.2))
distributions.add(("Immunity", "CONSTANT_DISTRIBUTION", 1, 0))
set_demog_distribution(demog, distributions)
```

#### Parameters

- **filename** – the demographics file as json
- **distributions** – the different distributions to set contained in a list

**Returns** Nothing

`emod_api.demographics.demographics_utils.set_static_demographics` (*cb, use\_existing=False*)

Create a static demographics based on the demographics file specified in the config file of the DTKConfigBuilder object passed to the function.

This function takes the current demographics file and adjust the birth rate/death rate to get a static population (the deaths are always compensated by new births).

#### Parameters

- **cb** – The config builder object
- **use\_existing** – If True will only take the demographics file name and add the .static to it. If False will create a static demographics file based on the specified demographics file.

**Returns** Nothing

`emod_api.demographics.demographics_utils.set_growing_demographics` (*cb, use\_existing=False*)

This function creates a growing population. It works the same way as the `set_static_demographics` but with a birth rate more important than the death rate which leads to a growing population.

#### Parameters

- **cb** – The DTKConfigBuilder object



- **use\_existing** – If `True` will only take the demographics file name and add the `.growing` to it. If `False` will create a growing demographics file based on the specified demographics file.

**Returns** Nothing

## emod\_api.demographics.grid\_construction module

- construct a grid from a bounding box
- label a collection of points by grid cells
- input: - points csv file with required columns lat,lon # see example input files (structures\_households.csv)
- **output: - csv file of grid locations**
  - csv with grid cell id added for each point record

`emod_api.demographics.grid_construction.get_grid_cell_id(idx, idy)`

`emod_api.demographics.grid_construction.construct(x_min, y_min, x_max, y_max)`  
Creating grid

`emod_api.demographics.grid_construction.get_bbox(data)`

`emod_api.demographics.grid_construction.lon_lat_2_point(lon, lat)`

`emod_api.demographics.grid_construction.point_2_grid_cell_id_lookup(point,  
grid_id_2_cell_id,  
origin)`

## emod\_api.interventions package

### Submodules

### emod\_api.interventions.common module

`emod_api.interventions.common.BroadcastEvent(camp, Event_Trigger: str = 'Births')`

Wrapper function to create and return a BroadcastEvent intervention.

#### Parameters

- **camp** – emod\_api.campaign object with schema\_path set.
- **Event\_Trigger** – A valid trigger/event/signal.

**Returns** Schema-based smart dictionary representing a new BroadcastEvent intervention ready to be added to a campaign.

**Return type** *ReadOnlyDict*

`emod_api.interventions.common.BroadcastEventToOtherNodes(camp, Event_Trigger,  
Node_Selection_Type='DISTANCE_ONLY',  
Max_Distance_To_Other_Nodes_Km=-  
1, Include_My_Node=1)`

Wrapper function to create and return a BroadcastEventToOtherNodes intervention.

#### Parameters

- **camp** – emod\_api.campaign object with schema\_path set.

- **Event\_Trigger** – A valid trigger/event/signal.
- **Node\_Selection\_Type** – TBD.
- **Max\_Distance\_To\_Other\_Nodes\_Km** – TBD.
- **Include\_My\_Node** – TBD.

**Returns** Schema-based smart dictionary representing a new BroadcastEvent intervention ready to be added to a campaign.

**Return type** *ReadOnlyDict*

`emod_api.interventions.common.MultiInterventionDistributor` (*camp*, *Intervention\_List*)

Wrapper function to create and return a MultiInterventionDistributor intervention.

**Parameters**

- **camp** – `emod_api.campaign` object with `schema_path` set.
- **Intervention\_List** – List of 1 or more valid intervention dictionaries to be
- **together.** (*distributed*) –

**Returns** Schema-based smart dictionary representing a new MultiInterventionDistributor intervention ready to be added to a campaign.

**Return type** *ReadOnlyDict*

`emod_api.interventions.common.DelayedIntervention` (*camp*, *Configs*, *Delay\_Dict=None*)

Wrapper function to create and return a DelayedIntervention intervention.

**Parameters**

- **camp** – `emod_api.campaign` object with `schema_path` set.
- **Config** – Valid intervention config.
- **Delay\_Dict** – Dictionary of 1 or 2 params that are the literal `Delay_Distribution`
- **but without the distribution, which is inferred. E.g.,**  
(*parameters,*) –
- **"Delay\_Period\_Exponential" ({} – 5 }**

**Returns** Schema-based smart dictionary representing a new DelayedIntervention intervention ready to be added to a campaign.

**Return type** *ReadOnlyDict*

`emod_api.interventions.common.HSB` (*camp*, *Event\_Or\_Config='Event'*, *Config=None*,  
*Event='NoTrigger'*, *Tendency=1.0*, *Single\_Use=True*,  
*Name='HSB'*)

Wrapper function to create and return a HealthSeekingBehaviour intervention.

**Parameters**

- **camp** – `emod_api.campaign` object with `schema_path` set.
- **Event\_Or\_Config** – “Event” or “Config”.
- **Config** – Complete, valid intervention configuration to be distributed.
- **Event** – Event/Trigger/Signal to be broadcast, alternative to an intervention.
- **Tendency** – Daily probability of ‘seeking care’ aka distributing payload intervention.
- **Single\_Use** – One-and-done, or continuous?

- **Name** – Intervention Name. Useful if you want to provide uniqueness and not worry about
- **intervention management**. (*duplicate*) –

**Returns** Schema-based smart dictionary representing a new HSB intervention ready to be added to a campaign.

**Return type** *ReadOnlyDict*

```
emod_api.interventions.common.NLHTI (camp, Triggers, Interventions, Property_Restrictions=None, Demo-
                                     graphic_Coverage=1.0, Target_Age_Min=0, Tar-
                                     get_Age_Max=45625, Target_Gender='All', Tar-
                                     get_Residents_Only=False, Duration=- 1, Black-
                                     out_Event_Trigger=None, Blackout_Period=None,
                                     Blackout_On_First_Occurrence=None, Disqualify-
                                     ing_Properties=None)
```

Wrapper function to create and return a NodeLevelHealthTriggeredIntervention intervention.

#### Parameters

- **camp** – emod\_api.campaign object with schema\_path set.
- **Triggers** – List of Triggers/Events/Signals
- **Interventions** – List of interventions to distribute when signal is heard.
- **Property\_Restrictions** – Individual Properties that an agent must have to qualify for intervention.
- **Demographic\_Coverage** – Percentage of individuals to receive intervention.
- **Target\_Age\_Min** – Minimum age (in years).
- **Target\_Age\_Max** – Maximum age (in years).
- **Target\_Gender** – All, Male, or Female.
- **Target\_Residents\_Only** – Not used.
- **Duration** – How long this listen-and-distribute should last.
- **Blackout\_Event\_Trigger** – Not used.
- **Blackout\_Period** – Not used.
- **Blackout\_On\_First\_Occurrence** – Not used.
- **Disqualifying\_Properties** – Not used.

**Returns** Schema-based smart dictionary representing a new NLHTI intervention ready to be added to a campaign.

**Return type** *ReadOnlyDict*

```
emod_api.interventions.common.PropertyValueChanger (camp, Target_Property_Key,
                                                       Target_Property_Value,
                                                       Daily_Probability=1.0, Max-
                                                       imum_Duration=1, Revert=-
                                                       1, Intervention_Name="",
                                                       Event_Trigger_Distributed="",
                                                       Event_Trigger_Expired="")
```

Wrapper function to create and return a PropertyValueChanger intervention.

#### Parameters

- **camp** – emod\_api.campaign object with schema\_path set.
- **The key part of the new key-value pair of the IP.** (*Target\_Property\_Key.*)–
- **The value part of the new key-value pair of the IP.** (*Target\_Property\_Value.*)–
- **Optional IP key** (*New\_Property\_Value..*) – value part to be set, common to all interventions.
- **The daily probability that an individual will move to the Target\_Property\_Value.** (*Daily\_Probability.*)–
- **The maximum amount of time individuals have to move to a new group. This timing works in conjunction with Daily\_Probability.** (*Maximum\_Duration.*)–
- **The number of days before an individual moves back to their original group.** (*Revert.*)–
- **Optional Intervention\_Name.** Useful if managing a replacement policy. (*Intervention\_Name.*)–
- **Optional broadcast trigger to be published when PVC is distributed.** (*Event\_Trigger\_Distributed.*)–
- **Optional broadcast trigger to be published when PVC is expired.** (*Event\_Trigger\_Expired.*)–

**Returns** Schema-based smart dictionary representing a new PropertyValueChanger intervention ready to be added to a campaign.

**Return type** *ReadOnlyDict*

```
emod_api.interventions.common.ScheduledCampaignEvent (camp, Start_Day: int,
                                                         Node_Ids=None, Node-
                                                         set_Config=None, Num-
                                                         ber_Repetitions: int = 1,
                                                         Timesteps_Between_Repetitions:
                                                         int = - 1, Event_Name: str =
                                                         'Scheduled_Campaign_Event',
                                                         Property_Restrictions=None,
                                                         Demographic_Coverage: float
                                                         = 1.0, Target_Age_Min=0,
                                                         Target_Age_Max=45625,
                                                         Target_Gender: str = 'All',
                                                         Target_Residents_Only:
                                                         bool = False, Interven-
                                                         tion_List=None)
```

Wrapper function to create and return a ScheduledCampaignEvent intervention. The alternative to a Scheduled-CampaignEvent is a TriggeredCampaignEvent.

#### Parameters

- **camp** – emod\_api.campaign object with schema\_path set.
- **Start\_Day** – When to start.
- **Event\_Name** – Name for overall campaign event, of no functional meaning. Not in schema and not yet used.
- **Node\_Ids** – Nodes to target with this intervention

- **Nodeset\_Config** – Nodes to target with this intervention, return from `utils.do_nodes()`.  
Deprecated since version 2.x: Use parameter `Node_Ids` instead
- **Property\_Restrictions** – Individual Properties a person must have to receive the intervention(s).
- **Number\_Repetitions** – N/A
- **Timesteps\_Between\_Repetitions** – N/A
- **Demographic\_Coverage** – Percentage of individuals to receive intervention.
- **Target\_Age\_Min** – Minimum age (in years).
- **Target\_Age\_Max** – Maximum age (in years).
- **Target\_Gender** – All, Male, or Female.
- **Intervention\_List** – List of 1 or more valid intervention dictionaries to be
- **together.** (*distributed*) –

**Returns** Schema-based smart dictionary representing a new `ScheduledCampaignEvent` intervention ready to be added to a campaign.

**Return type** *ReadOnlyDict*

```
emod_api.interventions.common.TriggeredCampaignEvent (camp, Start_Day: int,
Event_Name: str, Triggers:
List[str], Intervention_List:
List[dict], Node_Ids=None,
Nodeset_Config=None,
Node_Property_Restrictions=None,
Property_Restrictions=None,
Number_Repetitions: int = 1,
Timesteps_Between_Repetitions:
int = - 1, Demo-
graphic_Coverage: float
= 1.0, Target_Age_Min=0,
Target_Age_Max=45625,
Target_Gender: str = 'All', Tar-
get_Residents_Only=False,
Duration=- 1, Black-
out_Event_Trigger: str = None,
Blackout_Period=0, Black-
out_On_First_Occurrence=0,
Disqualify-
ing_Properties=None, De-
lay=None)
```

Wrapper function to create and return a `TriggeredCampaignEvent` intervention. The alternative to a `TriggeredCampaignEvent` is a `ScheduledCampaignEvent`.

#### Parameters

- **camp** – `emod_api.campaign` object with `schema_path` set.
- **Start\_Day** – When to start.
- **Event\_Name** – Name for overall campaign event, of no functional meaning. Not in schema and not yet used.
- **Node\_Ids** – Nodes to target with this intervention

- **Nodeset\_Config** – Nodes to target with this intervention, return from `utils.do_nodes()`.  
Deprecated since version 2.x: Use parameter `Node_Ids` instead
- **Triggers** – List of triggers/events/signals to listen to in order to trigger distribution.
- **Intervention\_List** – List of 1 or more valid intervention dictionaries to be
- **together.** (*distributed*) –
- **Node\_Property\_Restrictions** – N/A.
- **Property\_Restrictions** – Individual Properties a person must have to receive the intervention(s).
- **Demographic\_Coverage** – Percentage of individuals to receive intervention.
- **Target\_Age\_Min** – Minimum age (in years).
- **Target\_Age\_Max** – Maximum age (in years).
- **Target\_Gender** – All, Male, or Female.
- **Target\_Residents\_Only** – TBD.
- **Duration** – How long this listen-and-distribute should last.
- **Blackout\_Event\_Trigger** – Not used.
- **Blackout\_Period** – Not used.
- **Blackout\_On\_First\_Occurrence** – Not used.
- **Disqualifying\_Properties** – Not used.
- **delay** – Optional delay between trigger and actual distribution.

**Returns** Schema-based smart dictionary representing a new `TriggeredCampaignEvent` intervention ready to be added to a campaign.

**Return type** *ReadOnlyDict*

```
emod_api.interventions.common.StandardDiagnostic(camp, Base_Sensitivity: float = 1.0, Base_Specificity: float = 1.0, Days_To_Diagnosis: float = 0.0, Event_Trigger_Distributed: str = None, Event_Trigger_Expired: str = None, Positive_Diagnosis_Intervention=None, Positive_Diagnosis_Event: str = 'PositiveResult', Negative_Diagnosis_Intervention=None, Negative_Diagnosis_Event: str = 'NegativeResult', Treatment_Fraction: float = 1.0)
```

Wrapper function to create and return a `StandardDiagnostic` intervention.

#### Parameters

- **camp** – `emod_api.campaign` object with `schema_path` set.
- **Base\_Sensitivity** – base sensitivity [0..1]
- **Base\_Specificity** – base specificity [0..1]
- **Days\_To\_Diagnosis** – days to diagnosis

- **Event\_Trigger\_Distributed** – A trigger that is fired when intervention was distributed
- **Event\_Trigger\_Expired** – A trigger that is fired when intervention has expired
- **Positive\_Diagnosis\_Intervention** – Intervention that is distributed in case of a positive diagnosis. If set, no events may be configured.
- **Positive\_Diagnosis\_Event** – A trigger that is fired in case of a positive diagnosis
- **Negative\_Diagnosis\_Intervention** – Intervention that is distributed in case of a Negative diagnosis. If set, no events may be configured. Not used outside of Malaria-Ongoing yet.
- **Negative\_Diagnosis\_Event** – A trigger that is fired in case of a Negative diagnosis. Not used outside of Malaria-Ongoing yet.
- **Treatment\_Fraction** – treatment fraction [0..1]

**Returns** Schema-based smart dictionary representing a new MultiInterventionDistributor intervention ready to be added to a campaign.

**Return type** *ReadOnlyDict*

```
emod_api.interventions.common.triggered_campaign_delay_event (camp, start_day,
                                                             trigger, delay,
                                                             intervention,
                                                             ip_targeting=[],
                                                             coverage=1.0)
```

Create and return a campaign event that responds to a trigger after a delay with an intervention.

#### Parameters

- **camp** – emod\_api.campaign object with schema\_path set.
- **start\_day** – When to start.
- **delay** – Dictionary of 1 or 2 params that are the literal Delay\_Distribution parameters,
- **without the distribution, which is inferred. E.g., { "Delay\_Period\_Exponential" (but) – 5 }.**
- **trigger** – E.g., “NewInfection”.
- **intervention** – List of 1 or more valid intervention dictionaries to be distributed together.
- **ip\_targeting** – Optional Individual Properties required for someone to receive the intervention(s).

**Returns** Campaign event.

```
emod_api.interventions.common.triggered_campaign_event_with_optional_delay(camp,  
                                                                           start_day,  
                                                                           trig-  
                                                                           gers,  
                                                                           in-  
                                                                           ter-  
                                                                           ven-  
                                                                           tion,  
                                                                           de-  
                                                                           lay=None,  
                                                                           duration=-  
  
                                                                           1,  
                                                                           ip_targeting=None,  
                                                                           cov-  
                                                                           er-  
                                                                           age=1.0,  
                                                                           tar-  
                                                                           get_age_min=0,  
                                                                           tar-  
                                                                           get_age_max=45625,  
                                                                           tar-  
                                                                           get_sex='All',  
                                                                           tar-  
                                                                           get_residents_only=False,  
                                                                           black-  
                                                                           out=True,  
                                                                           check_at_trigger=False)
```

Create and return a campaign event that responds to a trigger after a delay with an intervention.

#### Parameters

- **camp** – emod\_api.campaign object with schema\_path set.
- **start\_day** – When to start.
- **triggers** – List of signals to listen for/trigger on. E.g., “NewInfection”.
- **intervention** – List of 1 or more valid intervention dictionaries to be distributed together.
- **delay** – Optional dictionary of 1 or 2 params that are the literal Delay\_Distribution parameters,
- **without the distribution, which is inferred. E.g., { "Delay\_Period\_Exponential" (but) – 5 }**. If omitted,
- **is immediate. (intervention) –**
- **duration** – How long to listen.
- **ip\_targeting** – Optional Individual Properties required for someone to receive the intervention(s).
- **coverage** – Fraction of target population to reach.
- **target\_age\_min** – Minimum age to target.
- **target\_age\_max** – Maximum age to target.
- **target\_sex** – Optional target just “MALE” or “FEMALE” individuals.



- **target\_residents\_only** – Set to True to target only the individuals who started the simulation in this node and are still in the node.
- **blackout** – Set to True if you don't want the triggered intervention to be distributed to the same person more than once a day.
- **check\_at\_trigger** – if triggered event is delayed, you have an option to check individual/node's eligibility at the initial trigger or when the event is actually distributed after delay.

**Returns** Campaign event.

```
emod_api.interventions.common.change_individual_property_at_age(camp,  
                                                                new_ip_key,  
                                                                new_ip_value,  
                                                                change_age_in_days,  
                                                                re-  
                                                                vert_in_days,  
                                                                ip_targeting_key,  
                                                                ip_targeting_value,  
                                                                cover-  
                                                                age=1.0)
```

Create and return a campaign event that changes a person's Individual Properties once they turns a certain age. e.g., `change_individual_property_at_age(cb, 'ForestGoing', 'LovesForest', coverage=0.6, change_age_in_days=15*365, revert=20*365)`

#### Parameters

- **camp** – emod\_api.campaign object with schema\_path set.
- **new\_ip\_key** – The new IP key.
- **new\_ip\_value** – The new IP value.
- **change\_age\_in\_days** – The age at which the individual transitions (in units of days).
- **revert\_in\_days** – How many days they remain with the new property.
- **ip\_targeting\_key** – The IP key a person must have to receive this.
- **ip\_targeting\_value** – The IP value a person must have to receive this.
- **coverage** – Optional fraction to limit this to a subset of the target population.

**Returns** Campaign event.

```
emod_api.interventions.common.change_individual_property_triggered(camp,
                                                                    trig-
                                                                    gers: list,
                                                                    new_ip_key:
                                                                    str,
                                                                    new_ip_value:
                                                                    str,
                                                                    start_day:
                                                                    int = 0,
                                                                    daily_prob:
                                                                    float = 1,
                                                                    max_duration:
                                                                    int =
                                                                    9.3228e+35,
                                                                    re-
                                                                    vert_in_days:
                                                                    int = - 1,
                                                                    node_ids:
                                                                    list =
                                                                    None,
                                                                    ip_restrictions:
                                                                    list =
                                                                    None,
                                                                    coverage:
                                                                    float =
                                                                    1.0, tar-
                                                                    get_age_min:
                                                                    float =
                                                                    0, tar-
                                                                    get_age_max:
                                                                    float =
                                                                    45625,
                                                                    tar-
                                                                    get_sex:
                                                                    str =
                                                                    'All', tar-
                                                                    get_residents_only:
                                                                    bool =
                                                                    False, de-
                                                                    lay=None,
                                                                    listen-
                                                                    ing_duration:
                                                                    int = - 1,
                                                                    black-
                                                                    out: bool
                                                                    = True,
                                                                    check_at_trigger:
                                                                    bool =
                                                                    False)
```

Change Individual Properties when a certain trigger is observed.

#### Parameters

- **camp** – The instance containing the campaign builder and accumulator.

- **triggers** – A list of the events that will trigger the intervention.
- **new\_ip\_key** – The individual property key to assign to the individual. For example, `InterventionStatus`.
- **new\_ip\_value** – The individual property value to assign to the individual. For example, `RecentDrug`.
- **start\_day** – The day on which to start distributing the intervention (**Start\_Day** parameter).
- **node\_ids** – The list of nodes to apply this intervention to. If not provided, defaults to all nodes.
- **daily\_prob** – The daily probability that an individual’s property value will be updated (**Daily\_Probability** parameter).
- **max\_duration** – The maximum amount of time individuals have to move to a new **daily\_prob**; individuals not moved to the new value by the end of **max\_duration** keep the same value.
- **revert\_in\_days** – The number of days before a node reverts to its original property value. Default of 0 means the new value is kept forever.
- **ip\_restrictions** – The IndividualProperty key:value pairs to target.
- **coverage** – The proportion of the population that will receive the intervention (**Demographic\_Coverage** parameter).
- **target\_age\_min** – Minimum age to target.
- **target\_age\_max** – Maximum age to target.
- **target\_sex** – Optional target just “MALE” or “FEMALE” individuals.
- **target\_residents\_only** – Set to True to target only the individuals who started the simulation in this node and are still in the node.
- **delay** – The number of days the campaign is delayed after being triggered.
- **listening\_duration** – The number of time steps that the triggered campaign will be active for. Default is -1, which is indefinitely.
- **blackout** (*advanced*) – Set to True if you don’t want the triggered intervention to be distributed to the same person more than once a day.
- **check\_at\_trigger** (*advanced*) – if triggered event is delayed, you have an option to check individual/node’s eligibility at the initial trigger or when the event is actually distributed after delay.
- **Returns** – N/A.

```
emod_api.interventions.common.change_individual_property_scheduled(camp,  
                                                                    new_ip_key,  
                                                                    new_ip_value,  
                                                                    start_day:  
                                                                    int =  
                                                                    0, num-  
                                                                    ber_repetitions:  
                                                                    int = 1,  
                                                                    timesteps_between_reps:  
                                                                    int = - 1,  
                                                                    node_ids:  
                                                                    list =  
                                                                    None,  
                                                                    daily_prob:  
                                                                    float = 1,  
                                                                    max_duration:  
                                                                    int =  
                                                                    9.3228e+35,  
                                                                    re-  
                                                                    vert_in_days:  
                                                                    int = - 1,  
                                                                    ip_restrictions:  
                                                                    list =  
                                                                    None,  
                                                                    coverage:  
                                                                    float =  
                                                                    1.0, tar-  
                                                                    get_age_min:  
                                                                    float =  
                                                                    0, tar-  
                                                                    get_age_max:  
                                                                    float =  
                                                                    45625,  
                                                                    tar-  
                                                                    get_sex:  
                                                                    str =  
                                                                    'All', tar-  
                                                                    get_residents_only:  
                                                                    bool =  
                                                                    False)
```

Change Individual Properties at a given time.

#### Parameters

- **camp** – The instance containing the campaign builder and accumulator.
- **new\_ip\_key** – The individual property key to assign to the individual. For example, InterventionStatus.
- **new\_ip\_value** – The individual property value to assign to the individual. For example, RecentDrug.
- **start\_day** – The day on which to start distributing the intervention (**Start\_Day** parameter).
- **node\_ids** – The list of nodes to apply this intervention to. If not provided, defaults to all

nodes.

- **daily\_prob** – The daily probability that an individual’s property value will be updated (**Daily\_Probability** parameter).
- **max\_duration** – The maximum amount of time individuals have to move to a new **daily\_prob**; individuals not moved to the new value by the end of **max\_duration** keep the same value.
- **revert\_in\_days** – The number of days before an individual reverts to its original property value. Default of -1 means the new value is kept forever.
- **ip\_restrictions** – The IndividualProperty key:value pairs to target.
- **coverage** – The proportion of the population that will receive the intervention (**Demographic\_Coverage** parameter).
- **target\_age\_min** – Minimum age to target.
- **target\_age\_max** – Maximum age to target.
- **target\_sex** – Optional target just “MALE” or “FEMALE” individuals.
- **target\_residents\_only** – Set to True to target only the individuals who started the simulation in this node and are still in the node.
- **Returns** – N/A.

```
emod_api.interventions.common.change_individual_property(camp,
                                                         get_property_name: str,
                                                         target_property_value:
                                                         str,
                                                         start_day:
                                                         int = 0,
                                                         number_repetitions: int = 1,
                                                         timesteps_between_reps:
                                                         int = -1,
                                                         node_ids: list =
                                                         None,
                                                         daily_prob: float
                                                         = 1,
                                                         max_duration: int
                                                         = 9.3228e+35,
                                                         revert:
                                                         int = -1,
                                                         coverage: float
                                                         = 1,
                                                         ip_restrictions:
                                                         list = None,
                                                         target_age_min: float
                                                         = 0,
                                                         target_age_max:
                                                         float = 45625,
                                                         target_sex: str = 'All',
                                                         target_residents_only:
                                                         bool = False,
                                                         trigger_condition_list:
                                                         list = None,
                                                         triggered_campaign_delay:
                                                         int = 0,
                                                         listening_duration: int
                                                         = -1,
                                                         black-out_flag: bool = True,
                                                         check_eligibility_at_trigger:
                                                         bool = False)
```

Add an intervention that changes the individual property value to another on a particular day OR after a triggering event using the **PropertyValueChanger** class. Deprecated. Prefer

change\_individual\_property\_scheduled or change\_individual\_property\_triggered depending on the use case.

### Parameters

- **camp** – emod\_api.campaign object with schema\_path set.
- **target\_property\_name** – The individual property key to assign to the individual. For example, Risk.
- **target\_property\_value** – The individual property value to assign to the individual. For example, High.
- **start\_day** – The day on which to start distributing the intervention.
- **number\_repetitions** – Optional repeater value. Does not work with triggers.
- **timesteps\_between\_reps** – Gap between repetitions, optional. Does not work with triggers.
- **node\_ids** – The list of nodes to apply this intervention to. Defaults to all.
- **daily\_prob** – The daily probability that an individual's property value will be updated (**Daily\_Probability** parameter).
- **max\_duration** – The number of days to continue the intervention after **start\_day**.
- **revert** – The number of days before an individual reverts to its original property value. Default of -1 means the new value is kept forever.
- **coverage** – The proportion of the population that will receive the intervention (**Demographic\_Coverage** parameter).
- **ip\_restrictions** – The IndividualProperty key:value pairs to target. Usually this will be the same key but different from the target\_property\_xxx entries.
- **target\_residents\_only** – Set to True to target only the individuals who started the simulation in this node and are still in the node.
- **target\_age\_min** – Optional minimum age, defaults to 0.
- **target\_age\_max** – Optional maximum age, defaults to inf.
- **target\_sex** – Optional target sex, defaults to both.
- **triggered\_campaign\_delay** – The number of days the campaign is delayed after being triggered.
- **trigger\_condition\_list** – A list of the events that will trigger the intervention. If included, **start\_day** is the day when monitoring for triggers begins.
- **listening\_duration** – The number of time steps that the triggered campaign will be active for. Default is -1, which is indefinitely.
- **blackout\_flag** – Set to True if you don't want the triggered intervention to be distributed to the same person more than once a day.
- **check\_eligibility\_at\_trigger** – if triggered event is delayed, you have an option to check individual/node's eligibility at the initial trigger or when the event is actually distributed after delay.

**Returns** None

## emod\_api.interventions.import\_pressure module

```
emod_api.interventions.import_pressure.new_intervention(timestep, durs=[], dips=[],
                                                         nods=[])
emod_api.interventions.import_pressure.new_intervention_as_file(timestep, file-
                                                                name=None)
```

## emod\_api.interventions.migration module

```
emod_api.interventions.migration.add_migration_event(camp, nodeto, start_day:
                                                    int = 0, coverage: float
                                                    = 1, repetitions: int = 1,
                                                    tsteps_btwn: int = 365, du-
                                                    ration_at_node: dict = None,
                                                    duration_before_leaving: dict
                                                    = None, target_age: dict
                                                    = None, nodes_from_ids:
                                                    List[int] = None,
                                                    ind_property_restrictions=None,
                                                    node_property_restrictions=None,
                                                    triggered_campaign_delay=0,
                                                    trigger_condition_list=None,
                                                    listening_duration=- 1)
```

Add a migration event to a campaign that moves individuals from one node to another.

### Parameters

- **camp** – emod\_api.campaign object with schema\_path set.
- **nodeto** – The NodeID that the individuals will travel to.
- **start\_day** – A day when intervention is distributed
- **coverage** – The proportion of the population covered by the intervention
- **repetitions** – The number of times to repeat the intervention
- **tsteps\_btwn** – The number of time steps between repetitions.
- **duration\_before\_leaving** – Dictionary of parameters that define the distribution for duration before leaving node, including the distribution. Durations are in days. .. rubric:: Examples

```
{“Duration_Before_Leaving_Distribution”:”GAUSSIAN_DISTRIBUTION”,
“Duration_Before_Leaving_Gaussian_Mean”:          14,          “Du-
ration_Before_Leaving_Gaussian_Std_Dev”          3}          {“Dura-
tion_Before_Leaving_Distribution”:”POISSON_DISTRIBUTION”,          “Dura-
tion_Before_Leaving_Poisson_Mean” 30}
```

- **duration\_at\_node** – Dictionary of parameters that define the distribution for duration at node, including the distribution Durations are in days. .. rubric:: Examples

```
{“Duration_At_Node_Distribution”:”GAUSSIAN_DISTRIBUTION”,          “Dura-
tion_At_Node_Gaussian_Mean”:          14,          “Duration_At_Node_Gaussian_Std_Dev”
3}          {“Duration_At_Node_Distribution”:”POISSON_DISTRIBUTION”,          “Dura-
tion_At_Node_Poisson_Mean” 30}
```

- **target\_age** – The individuals to target with the intervention. To restrict by age, provide a dictionary of {‘agemin’ : x, ‘agemax’ : y}. Default is targeting everyone.

- **nodes\_from\_ids** – The list of node ids to apply this intervention to.
- **ind\_property\_restrictions** – The IndividualProperty key:value pairs that individuals must have to receive the intervention (**Property\_Restrictions\_Within\_Node** parameter). In the format [{"BitingRisk": "High"}, {"IsCool": "Yes"}].
- **node\_property\_restrictions** – The NodeProperty key:value pairs that nodes must have to receive the intervention. In the format [{"Place": "RURAL"}, {"ByALake": "Yes"}].
- **triggered\_campaign\_delay** – After the trigger is received, the number of time steps until distribution starts. Eligibility of people or nodes for the campaign is evaluated on the start day, not the triggered day.
- **trigger\_condition\_list** – A list of the events that will trigger the intervention. If included, **start\_days** is then used to distribute **NodeLevelHealthTriggeredIV**.
- **listening\_duration** – The number of time steps that the distributed event will monitor for triggers. Default is -1, which is indefinitely.

**Returns** None

### Example

```
from emod_api import campaign as camp
dan = {"Duration_At_Node_Distribution": "POISSON_DISTRIBUTION",
      "Duration_At_Node_Poisson_Mean": 30}
dbl = {"Duration_Before_Leaving_Distribution": "GAUSSIAN_DISTRIBUTION",
      "Duration_Before_Leaving_Gaussian_Mean": 14,
      "Duration_Before_Leaving_Gaussian_Std_Dev": 3}

add_migration_event(camp, node_to=5, start_day=1, coverage=0.75, duration_at_node = dan,
                   duration_before_leaving = dbl, repetitions=1, tsteps_btwn=90, target='Everyone', nodesfrom={"class":
                   "NodeSetAll"}, node_property_restrictions=[{"Place": "Rural"}])
```

### emod\_api.interventions.node\_multiplier module

```
emod_api.interventions.node_multiplier.new_intervention(camp, new_infectivity=1.0,
                                                         profile='CONST',
                                                         **kwargs)
```

Create new NodeInfectivityModifying intervention.

#### Parameters

- **profile** – multiplier options include:
  - **CONST(ANT)**
    - \* new\_infectivity lasts forever (or until replaced).
  - **TRAP(EZOID)**
    - \* rise\_duration
    - \* peak\_duration
    - \* fall\_duration
  - **EXP(ONENTIAL) (not implemented yet)**
    - \* rise duration
    - \* rise rate
  - **SIN(USOIDAL) (not implemented yet)**



\* period

- **do boxcar**, specify 0 rise and fall durations (*To*) –

**Returns** new NodeInfectivityMult intervention dictionary.

```
emod_api.interventions.node_multiplier.new_scheduled_event(camp, start_day=1,
                                                           new_infectivity=1.0,
                                                           profile='CONST',
                                                           node_ids=None,
                                                           recurring=True,
                                                           **kwargs)
```

Create new NodeInfectivityModifying intervention as scheduled campaign event.

```
emod_api.interventions.node_multiplier.new_intervention_as_file(camp,
                                                                timestep, file-
                                                                name=None)
```

Create new NodeInfectivityModifying intervention as sole scheduled campaign event inside working campaign json file.

## emod\_api.interventions.outbreak module

```
emod_api.interventions.outbreak.seed_by_coverage(campaign_builder, timestep, cover-
                                                  age=0.01, ignore_immunity=None,
                                                  intervention_only=False)
```

This simple function provides a very common piece of functionality to seed an infection. A future version will support targeted nodesets.

```
emod_api.interventions.outbreak.new_intervention(campaign_builder, timestep,
                                                  cases=1)
```

Create EMOD-ready Outbreak intervention.

### Parameters

- **timestep** (*float*) – timestep at which outbreak should occur.
- **cases** (*integer*) – new parameter that specifies maximum number of cases. May not be supported.

**Returns** event as dict (json)

**Return type** event (json)

```
emod_api.interventions.outbreak.new_intervention_as_file(camp, timestep, cases=1,
                                                         filename=None)
```

## emod\_api.interventions.simple\_vaccine module

```
emod_api.interventions.simple_vaccine.new_intervention(timestep, v_type='Generic',
                                                         efficacy=1.0,
                                                         sv_name='Vaccine',
                                                         waning_duration=100,
                                                         d_a_d=None,
                                                         cost_to_consumer=None,
                                                         e_i_r=None, interven-
                                                         tion_only=False)
```

This is mostly an example but also potentially useful. With this you get a Vaccine with working defaults but 2 configurables: type and efficacy. The duration is fixed at box. You of course must specify the timestep and you can add a vaccine name which is mostly useful if you're managing a duplicate policy.

```
emod_api.interventions.simple_vaccine.new_intervention2(timestep)
```

This version lets you invoke the function sans-parameters. You get the module-level params which you can set before calling this. This is designed to support a more data-oriented way of using this API, with everything like “a.b=c”, and avoid “churn” on the API itself (constantly changing function signature). TBD: Make sure that if this is called twice, we understand whether we have copies or references going on.

```
emod_api.interventions.simple_vaccine.new_intervention_as_file(timestep, file-  
                                                                name=None)
```

## **emod\_api.interventions.utils module**

```
emod_api.interventions.utils.do_nodes(schema_path, node_ids)
```

Create and return a NodeSetConfig based on node\_ids list.

```
emod_api.interventions.utils.get_waning_from_params(schema_path, initial=1.0,  
                                                    box_duration=365,  
                                                    decay_rate=0, decay_time_constant=None)
```

Get well configured waning structure. Default is 1-year full efficacy box. Note that an infinite decay rate (0 or even -1) is same as Box. Note that an infinite box duration (-1) is same as constant. Note that a zero box duration is same as Exponential.

### **Parameters**

- **schema\_path** – Path to schema.json file.
- **initial** – Initial efficacy value, defaults to 1.0.
- **box\_duration** – Number of timesteps efficacy remains at initial before decay. Defaults to 365.
- **decay\_rate** – Rate at which efficacy decays after box\_duration. Defaults to 0.
- **decay\_time\_constant** – 1/decay\_rate. Defaults to None. Use this or decay\_rate, not both. If this is specified, decay\_rate is ignored.

## **emod\_api.migration package**

### **Subpackages**

#### **emod\_api.migration.client package**

### **Submodules**

#### **emod\_api.migration.client.client module**

```
emod_api.migration.client.client.run(input_file: pathlib.Path, parameters: dict) → None
```

Run a client that tries to connect the url given in parameters. The client will do a Post operation with the parameters given in parameters.

### **Parameters**

- **input\_file** – Path to the demographics file.
- **parameters** – Dictionary containing the server url and the parameters for model calculation.

## Submodules

### emod\_api.migration.migration module

**class** emod\_api.migration.migration.Layer

Bases: dict

The Layer object represents a mapping from source node (IDs) to destination node (IDs) for a particular age, gender, age+gender combination, or all users if no age or gender dependence. Users will not generally interact directly with Layer objects.

**property DatavalueCount**

Get (maximum) number of data values for any node in this layer

**Returns** Maximum number of data values for any node in this layer

**property NodeCount**

Get the number of (source) nodes with rates in this layer

**Returns** Number of (source) nodes with rates in this layer

**class** emod\_api.migration.migration.Migration

Bases: object

Represents migration data in a mapping from source node (IDs) to destination node (IDs) with rates for each pairing.

Migration data may be age dependent, gender dependent, both, or the same for all ages and genders. A migration file (along with JSON metadata) can be loaded from the static method Migration.from\_file() and inspected and/or modified. Migration objects can be started from scratch with Migration(), and populated with appropriate source-dest rate data and saved to a file with the to\_file() method. Given migration = Migration(), syntax is as follows:

age and gender agnostic: migration[source\_id][dest\_id] age dependent: migration[source\_id:age] # age should be >= 0, ages > last bucket value use last bucket value gender dependent: migration[source\_id:gender] # gender one of Migration.MALE or Migration.FEMALE age and gender dependent: migration[source\_id:gender:age] # gender one of Migration.MALE or Migration.FEMALE

EMOD/DTK format migration files (and associated metadata files) can be written with migration.to\_file(<filename>). EMOD/DTK format migration files (with associated metadata files) can be read with migration.from\_file(<filename>).

**SAME\_FOR\_BOTH\_GENDERS = 0**

**ONE\_FOR\_EACH\_GENDER = 1**

**LINEAR\_INTERPOLATION = 0**

**PIECEWISE\_CONSTANT = 1**

**LOCAL = 1**

**AIR = 2**

**REGIONAL = 3**

**SEA = 4**

**FAMILY = 5**

**INTERVENTION = 6**

**IDREF\_LEGACY = 'Legacy'**

**IDREF\_GRUMP30ARCSEC** = 'Gridded world grump30arcsec'

**IDREF\_GRUMP2PT5ARCMIN** = 'Gridded world grump2.5arcmin'

**IDREF\_GRUMP1DEGREE** = 'Gridded world grump1degree'

**MALE** = 0

**FEMALE** = 1

**MAX\_AGE** = 125

**property AgesYears**

List of ages - ages < first value use first bucket, ages > last value use last bucket.

**property Author**

str: Author value for metadata for this migration datafile

**property DatavalueCount**

int: Maximum data value count for any layer in this migration datafile

**property DateCreated**

datetime: date/time stamp of this datafile

**property GenderDataType**

int: gender data type for this datafile - SAME\_FOR\_BOTH\_GENDERS or ONE\_FOR\_EACH\_GENDER

**property IdReference**

str: ID reference metadata value

**property InterpolationType**

int: interpolation type for this migration data file - LINEAR\_INTERPOLATION or PIECEWISE\_CONSTANT

**property MigrationType**

int: migration type for this migration data file - LOCAL | AIR | REGIONAL | SEA | FAMILY | INTERVENTION

**property Nodes**

**property NodeCount**

int: maximum number of source nodes in any layer of this migration data file

**get\_node\_offsets** (*limit: int = 100*) → dict

**property NodeOffsets**

dict: mapping from source node id to offset to destination and rate data in binary data

**property Tool**

str: tool metadata value

**to\_file** (*binaryfile: pathlib.Path, metafile: pathlib.Path = None, value\_limit: int = 100*)

Write current data to given file (and .json metadata file)

#### Parameters

- **binaryfile** (*Path*) – path to output file (metadata will be written to same path with “.json” appended)
- **metafile** (*Path*) – override standard metadata file naming
- **value\_limit** (*int*) – limit on number of destination values to write for each source node (default = 100)

**Returns** path to binary file

**Return type** (Path)

`emod_api.migration.migration.from_file` (binaryfile: *pathlib.Path*, metafile: *pathlib.Path* = *None*)

Reads migration data file from given binary (and associated JSON metadata file)

**Parameters**

- **binaryfile** (*Path*) – path to binary file (metadata file is assumed to be at same location with “.json” suffix)
- **metafile** (*Path*) – use given metafile rather than inferring metafile name from the binary file name

**Returns** Migration object representing binary data in the given file.

`emod_api.migration.migration.examine_file` (filename)

`emod_api.migration.migration.from_params` (demographics\_file\_path=None, pop=1000000.0, num\_nodes=100, mig\_factor=1.0, frac\_rural=0.3, id\_ref='from\_params', migration\_type=1)

This function is for creating a migration file that goes with a (multinode) demographics file created from a few parameters, as opposed to one from real-world data. Note that the ‘demographics\_file\_path’ input param is not used at this time but in future will be exploited to ensure nodes, etc., match.

`emod_api.migration.migration.from_demog_and_param_gravity_webservice` (demographics\_file\_path: *str*, params: *str*, id\_ref: *str*, migration\_type=1) →

*emod\_api.migration.migration.*

Calls a webservice (running on a GPU) to calculate the migration patterns quickly.

**Parameters**

- **demographics\_file\_path** – Path to the demographics file.
- **params** – Path to the json file with parameters for gravity calculation and server url.
- **id\_ref** – Metadata tag that needs to match corresponding value in demographics file.
- **migration\_type** – Migration type.

**Returns** Migration object

`emod_api.migration.migration.from_demog_and_param_gravity` (demographics\_file\_path, gravity\_params, id\_ref, migration\_type=1)

Create migration files from a gravity model and an input demographics file.

`emod_api.migration.migration.to_csv` (filename: *pathlib.Path*)

`emod_api.migration.migration.from_csv` (filename: *pathlib.Path*)

Create migration from csv file. The file should have columns ‘source’ for the source node, ‘destination’ for the destination node, and ‘rate’ for the migration rate.

**Parameters** filename – csv file

**Returns** Migration object

### emod\_api.schema package

#### Submodules

#### emod\_api.schema.dtk\_post\_process\_schema module

`emod_api.schema.dtk_post_process_schema.recurser` (*in\_json*)

`emod_api.schema.dtk_post_process_schema.application` (*schema\_file*)

#### emod\_api.schema.get\_schema module

`emod_api.schema.get_schema.dtk_to_schema` (*path\_to\_binary*, *path\_to\_write\_schema*='schema.json')  
Runs /path/to/Eradication --get-schema --schema-path=schema.json and then post-processes the schema into something more useful. Error cases handled: - schema.json file already exists in cwd; does not overwrite. Asks users to move and retry. - Specified binary fails to run to completion. - Specified binary fails to produce a schema.json

### emod\_api.serialization package

#### Submodules

#### emod\_api.serialization.CensusAndModPop module

`emod_api.serialization.CensusAndModPop.change_ser_pop` (*input\_serpop\_path*,  
*mod\_fn*=None,  
*save\_file\_path*=None)

This function loads a serialization population file, iterates over each person, calls a user-provided callback with each individuals, and saves the population as manipulated by the user.

The mod function can act at will on the population object. There are no checks.

The new file is saved to a name provided by user. Interactive if none provided to function.

Assuming a single node file for now.

#### emod\_api.serialization.SerializedPopulation module

Class to load and manipulate a saved population.

**class** `emod_api.serialization.SerializedPopulation.SerializedPopulation` (*file*:  
*str*)

Bases: `object`

Opens the passed file and reads in all the nodes.

**Parameters** `file` – serialized population file

## Examples

Create an instance of SerializedPopulation:

```
import emod_api.serialization.SerializedPopulation as SerPop
ser_pop = SerPop.SerializedPopulation('state-00001.dtk')
```

### property nodes

All nodes.

## Examples

Delete number\_of\_ind individuals from node 0:

```
node = ser_pop.nodes[0]
del node.individualHumans[0:number_of_ind]
```

Only keep individuals with a certain condition:

```
node.individualHumans = [ind for ind in node.individualHumans if keep_
    ↳ fct(ind)]
```

Change susceptibility of an individual:

```
print(node.individualHumans[0].susceptibility)
new_susceptibility = {"age": 101.01, "mod_acquire": 0}
node.individualHumans[0].susceptibility.update(new_susceptibility)
```

Copy individual[0] from node 0, change properties and add individual as new individual:

```
import copy
individual_properties={"m_age": 1234}
individual = copy.deepcopy(node.individualHumans[0])
individual["suid"] = ser_pop.get_next_individual_suid(0)
individual.update(individual_properties)
ser_pop.nodes[0].individualHumans.append(individual)
```

Infect an individual with an infection copied from another individual:

```
infection = node["individualHumans"][0]["infections"][0]
infection["suid"] = self.get_next_infection_suid()
node["individualHumans"][1]["infections"].append(infection)
node["individualHumans"][1].m_is_infected = True
```

### flush()

Save all made changes to the node(s).

### write(output\_file: str = 'my\_sp\_file.dtk')

Write the population to a file.

**Parameters** output\_file – output file

### get\_next\_infection\_suid()

Each infection needs a unique identifier, this function returns one.

### get\_next\_individual\_suid(node\_id: int) → dict

Each individual needs a unique identifier, this function returns one.

**Parameters** node\_id – The first parameter.

**Returns** The return value. True for success, False otherwise.

## Examples

To get a unique id for an individual:

```
print(sp.get_next_individual_suid(0))
{'id': 2}
```

`emod_api.serialization.SerializedPopulation.find(name: str, handle, currentlevel='dtk.nodes')`

Recursively searches for a paramters that matches or is close to name and prints out where to find it in the file.

### Parameters

- **name** – the paramter you are looking for e.g. “age”, “gender”.
- **handle** – some iterable data structure, can be a list of nodes, a node, list of individuals, etc  
**currentlevel**: just a string to print out where the found item is located e.g. “dtk.nodes” or “dtk.node.individuals”

## Examples

What is the exact paramteter name used for the age of an individual?:

```
SerPop.find("age", node)
...
1998 Found in: dtk.nodes.individualHumans[999].m_age
1999 Found in: dtk.nodes.individualHumans[999].susceptibility.age
2000 Found in: dtk.nodes.m_vectorpopulations[0].EggQueues[0].age
2001 Found in: dtk.nodes.m_vectorpopulations[0].EggQueues[1].age
...
```

`emod_api.serialization.SerializedPopulation.get_parameters(handle, currentlevel='dtk.nodes')`

Return a set of all parameters in the serialized population file. Helpful to get an overview about what is in the serialized population file.

### Parameters

- **handle** – some iterable data structure, can be a list of nodes, a node, list of individuals, etc
- **currentlevel** – just a string to print out where the found item is located e.g. “dtk.nodes”or “dtk.node.individuals

## Examples

Print all parameters in serialized population file:

```
for n in sorted(SerPop.get_parameters(node)):
    print(n)
```



**emod\_api.serialization.dtkFileSupport module**

```

class emod_api.serialization.dtkFileSupport.Uncompressed
    Bases: object

    classmethod compress (data)

    classmethod uncompress (data)

class emod_api.serialization.dtkFileSupport.EllZeeFour
    Bases: object

    classmethod compress (data)

    classmethod uncompress (data)

class emod_api.serialization.dtkFileSupport.Snappy
    Bases: object

    classmethod compress (data)

    classmethod uncompress (data)

class emod_api.serialization.dtkFileSupport.SerialObject (dictionary={})
    Bases: dict

class emod_api.serialization.dtkFileSupport.NullPtr
    Bases: emod_api.serialization.dtkFileSupport.SerialObject

```

**emod\_api.serialization.dtkFileTools module**

Support for three formats of serialized population files: 1. “Original version”: single payload chunk with simulation and all nodes, uncompressed or snappy or LZ4 2. “First chunked version”: multiple payload chunks, one for simulation and one each for nodes 3. “Second chunked version”: multiple payload chunks, simulation and node objects are “root” objects in each chunk 4. “Metadata update”: compressed: true/false + engine: NONE|LZ4|SNAPPY replaced with compression: NONE|LZ4|SNAPPY

```

emod_api.serialization.dtkFileTools.uncompress (data, engine)

emod_api.serialization.dtkFileTools.compress (data, engine)

class emod_api.serialization.dtkFileTools.DtkHeader (dictionary={'author': 'unknown',
                                                                    'bytecount': 0, 'chunkcount': 0,
                                                                    'chunksizes': [], 'compressed':
                                                                    True, 'date': 'Tue Mar 08
                                                                    20:15:58 2022', 'engine': 'LZ4',
                                                                    'tool': 'dtkFileTools.py', 'ver-
                                                                    sion': 1})
    Bases: emod_api.serialization.dtkFileSupport.SerialObject

class emod_api.serialization.dtkFileTools.DtkFile (header)
    Bases: object

    class Contents (parent)
        Bases: object

        append (item)

    class Objects (parent)
        Bases: object

        append (item)

```

```
property header
property compressed
property compression
property byte_count
property chunk_count
property chunk_sizes
property author
property date
property tool
property version
property chunks
property nodes

class emod_api.serialization.dtkFileTools.DtkFileV1 (header=None, filename="", handle=None)
    Bases: emod_api.serialization.dtkFileTools.DtkFile
    property simulation

class emod_api.serialization.dtkFileTools.DtkFileV2 (header=None, filename="", handle=None)
    Bases: emod_api.serialization.dtkFileTools.DtkFile
    class NodesV2 (parent)
        Bases: object
        property simulation

class emod_api.serialization.dtkFileTools.DtkFileV3 (header=None, filename="", handle=None)
    Bases: emod_api.serialization.dtkFileTools.DtkFile
    class NodesV3 (parent)
        Bases: object
        property simulation

class emod_api.serialization.dtkFileTools.DtkFileV4 (header=None, filename="", handle=None)
    Bases: emod_api.serialization.dtkFileTools.DtkFileV3

emod_api.serialization.dtkFileTools.read(filename)
emod_api.serialization.dtkFileTools.write(dtk_file, filename)
```

**emod\_api.serialization.dtkFileUtility module****emod\_api.spatialreports package****Submodules****emod\_api.spatialreports.spatial module**

emod-api spatial report module. Exposes SpatialReport and SpatialNode objects.

**class** emod\_api.spatialreports.spatial.**SpatialNode** (*node\_id: int, data*)

Bases: `object`

Class representing a single node of a spatial report.

**property id**

Node ID

**property data**

Time series data for this node.

**class** emod\_api.spatialreports.spatial.**SpatialReport** (*filename: str = None, node\_ids: List[int] = None, data: numpy.array = None, start: int = 0, interval: int = 1*)

Bases: `object`

Class for reading (and, optionally, writing) spatial reports in EMOD/DTK format. “Filtered” reports will have `start > 0` and/or reporting interval `> 1`.

**property data**

Returns full 2 dimensional NumPy array with report data. Shape is (#values, #nodes).

**property node\_ids**

Returns list of node IDs (integers) for nodes in the report.

**property nodes**

Returns dictionary of SpatialNodes keyed on node ID.

**property node\_count**

Number of nodes in the report.

**property time\_steps**

Number of samples in the report.

**property start**

Time step of first sample.

**property interval**

Interval, in time steps, between samples.

**write\_file** (*filename: str*)

Save current nodes and timeseries data to given file.

## emod\_api.tabularoutput package

## emod\_api.weather package

### Submodules

## emod\_api.weather.weather module

emod-api Weather module - Weather, Metadata, and WeatherNode objects along with IDREF and CLIMATE\_UPDATE constants.

```
class emod_api.weather.weather.WeatherNode (node_id: int, data)
    Bases: object
```

Represents information for a single node: ID and timeseries data.

```
property id
    Node ID
```

```
property data
    Time series data for this node.
```

```
class emod_api.weather.weather.Metadata (node_ids: List[int], datavalue_count: int, author:
                                         str = None, created: datetime.datetime = None, fre-
                                         quency: str = None, provenance: str = None, refer-
                                         ence: str = None)
```

Bases: *object*

Metadata:

- [DateCreated]
- [Author]
- [OriginalDataYears]
- [StartDayOfYear]
- [DataProvenance]
- IdReference
- NodeCount
- DatavalueCount
- UpdateResolution
- NodeOffsets

```
property author
    Author of this file.
```

```
property creation_date
    Creation date of this file.
```

```
property datavalue_count
    Number of data values in each timeseries, should be > 0.
```

```
property id_reference
    ‘Schema’ for node IDs. Commonly Legacy, Gridded world grump2.5arcmin, and Gridded world
    grump30arcsec.
    Legacy usually indicates a 0 or 1 based scheme with increasing ID numbers.
```

*Gridded world grump2.5arcmin* and *Gridded world grump30arcsec* encode latitude and longitude values in the node ID with the following formula:

```
latitude = ((nodeid - 1) & 0xFFFF) * resolution) - 90
longitude = ((nodeid >> 16) * resolution) - 180
# nodeid = 90967271 @ 2.5 arcmin resolution
# longitude = -122.1667, latitude = 47.5833
```

**property node\_count**

**property node\_ids**

**property provenance**

**property update\_resolution**

**property nodes**

WeatherNodes offsets keyed by node id.

**write\_file** (filename: *str*) → *None*

**classmethod from\_file** (filename: *str*)

Read weather metadata file. Metadata' and 'NodeOffsets' keys required. DatavalueCount', 'UpdateResolution', and 'IdReference' required in 'Metadata'.

```
class emod_api.weather.weather.Weather (filename: str = None, node_ids: List[int] = None,
                                         datavalue_count: int = None, author: str = None,
                                         created: datetime.datetime = None, frequency: str
                                         = None, provenance: str = None, reference: str =
                                         None, data: numpy.array = None)
```

Bases: *object*

**property data**

Raw data as numpy array[node index, time step].

**property metadata**

**property author**

**property creation\_date**

**property datavalue\_count**

≥ 1

**property id\_reference**

**property node\_count**

≥ 1

**property node\_ids**

**property provenance**

**property update\_resolution**

**property nodes**

WeatherNodes indexed by node id.

**write\_file** (filename: *str*) → *None*

Writes data to filename and metadata to filename.json.

**classmethod from\_csv** (filename: *str*, var\_column: *str* = 'airtemp', id\_column: *str* = 'node\_id',  
step\_column: *str* = 'step', author: *str* = None, provenance: *str* = None)

Create weather from CSV file with specified variable column, node id column, and time step column.

---

**Note:**

- Column order in the CSV file is not significant, but columns names must match what is passed to this function.
  - Because a CSV might hold air temperature (may be negative and well outside 0-1 values), relative humidity (must *\_not\_* be negative, must be in the interval [0-1]), or rainfall (must *\_not\_* be negative, likely > 1), this function does not validate incoming data.
- 

### 3.1.2 Submodules

#### emod\_api.campaign module

You use this simple campaign builder by importing it, adding valid events via “add”, and writing it out with “save”.

```
emod_api.campaign.reset()
```

```
emod_api.campaign.set_schema(schema_path_in)
```

Set the (path to) the schema file. And reset all campaign variables. This is essentially a “start\_building\_campaign” function. :param schema\_path\_in. The path to a schema.json.:

**Returns** N/A.

```
emod_api.campaign.add(event, name=None, first=False)
```

Add a complete campaign event to the campaign builder. The new event is assumed to be a Python dict, and a valid event. The new event is not validated here. Set the first flag to True if this is the first event in a campaign because it functions as an accumulator and in some situations like sweeps it might have been used recently.

```
emod_api.campaign.get_trigger_list()
```

```
emod_api.campaign.save(filename='campaign.json')
```

Save ‘camapign\_dict’ as ‘filename’.

```
emod_api.campaign.get_adhocs()
```

```
emod_api.campaign.get_schema()
```

```
emod_api.campaign.get_recv_trigger(trigger, old=False)
```

Get the correct representation of a trigger (also called signal or even event) that is being listened to.

```
emod_api.campaign.get_send_trigger(trigger, old=False)
```

Get the correct representation of a trigger (also called signal or even event) that is being broadcast.

```
emod_api.campaign.get_event(event, old=False)
```

Basic placeholder functionality for now. This will map new ad-hoc events to GP\_EVENTS and manage that ‘cache’ If event in built-ins, return event, else if in adhoc map, return mapped event, else add to adhoc\_map and return mapped event.

### emod\_api.schema\_to\_class module

**class** emod\_api.schema\_to\_class.ReadOnlyDict

Bases: `collections.OrderedDict`

**set\_schema** (*schema*)

Add schema node.

**to\_file** (*config\_name*='config.json')

Write 'clean' config file out to disk as json. Param: *config\_name* (defaults to 'config.json')

**finalize** ()

Remove all params that are disabled by depends-on param being off and schema node.

emod\_api.schema\_to\_class.**get\_default\_for\_complex\_type** (*schema*, *idmtype*)

This function used to be more involved and dumb but now it's a passthrough to `get_class_with_defaults`. If this approach proves robust, it can probably be deprecated. Depends a bit on completeness of schema.

emod\_api.schema\_to\_class.**get\_class\_with\_defaults** (*classname*, *schema\_path*=None)

Returns the default config for a datatype in the schema.





## **GLOSSARY**

The following terms describe both the features and functionality of the emod-api software, as well as information relevant to using emod-api.

**asset collection** The set of specific input files (such as input parameters, weather or migration data, or other configuration settings) required for running a simulation.

**assets** See asset collection.

**builder** TBD

**experiment** A collection of multiple simulations, typically sent to an HPC.

**high-performance computing (HPC)** The use of parallel processing for running advanced applications efficiently, reliably, and quickly.

**task** TBD

**template** TBD



## PYTHON MODULE INDEX

### e

`emod_api`, 7

`emod_api.campaign`, 58

`emod_api.channelreports`, 7

`emod_api.channelreports.channels`, 7

`emod_api.config`, 8

`emod_api.config.default_from_schema`, 8

`emod_api.config.default_from_schema_no_validation`, 9

`emod_api.config.dtk_post_process_adhoc_events`, 10

`emod_api.config.dtk_pre_process_adhoc_events`, 10

`emod_api.config.dtk_pre_process_w5ml`, 10

`emod_api.config.from_overrides`, 10

`emod_api.config.from_poi_and_binary`, 10

`emod_api.config.from_schema`, 11

`emod_api.config.schema_to_config`, 11

`emod_api.demographics`, 12

`emod_api.demographics.BaseInputFile`, 12

`emod_api.demographics.Demographics`, 12

`emod_api.demographics.demographics_utils`, 27

`emod_api.demographics.DemographicsGenerator`, 15

`emod_api.demographics.DemographicsInputDataParsers`, 19

`emod_api.demographics.DemographicsTemplates`, 19

`emod_api.demographics.grid_construction`, 29

`emod_api.demographics.Node`, 21

`emod_api.demographics.PreDefinedDistributions`, 22

`emod_api.demographics.PropertiesAndAttributes`, 23

`emod_api.demographics.Updateable`, 27

`emod_api.interventions`, 29

`emod_api.interventions.common`, 29

`emod_api.interventions.import_pressure`, 43

`emod_api.interventions.migration`, 43

`emod_api.interventions.node_multiplier`, 44

`emod_api.interventions.outbreak`, 45

`emod_api.interventions.simple_vaccine`, 45

`emod_api.interventions.utils`, 46

`emod_api.migration`, 46

`emod_api.migration.client`, 46

`emod_api.migration.client.client`, 46

`emod_api.migration.migration`, 47

`emod_api.schema`, 50

`emod_api.schema.dtk_post_process_schema`, 50

`emod_api.schema.get_schema`, 50

`emod_api.schema_to_class`, 59

`emod_api.serialization`, 50

`emod_api.serialization.CensusAndModPop`, 50

`emod_api.serialization.dtkFileSupport`, 53

`emod_api.serialization.dtkFileTools`, 53

`emod_api.serialization.dtkFileUtility`, 55

`emod_api.serialization.SerializedPopulation`, 50

`emod_api.spatialreports`, 55

`emod_api.spatialreports.spatial`, 55

`emod_api.tabularoutput`, 56

`emod_api.weather`, 56

`emod_api.weather.weather`, 56



## INDEX

### A

`add()` (*emod\_api.demographics.PropertiesAndAttributes.IndividualProperties* method), 23  
`add()` (in module *emod\_api.campaign*), 58  
`add_migration_event()` (in module *emod\_api.interventions.migration*), 43  
`add_parameter()` (*emod\_api.demographics.PropertiesAndAttributes.IndividualProperties* method), 23  
`add_parameter()` (*emod\_api.demographics.Updateable.Updateable* method), 27  
`AddAgeDependentTransmission()` (*emod\_api.demographics.Demographics.Demographics* method), 13  
`AddIndividualPropertyAndHINT()` (*emod\_api.demographics.Demographics.Demographics* method), 13  
`AgeStructureUNWPP()` (in module *emod\_api.demographics.DemographicsTemplates*), 21  
`AgessYears()` (*emod\_api.migration.migration.Migration* property), 48  
**AIR** (*emod\_api.migration.migration.Migration* attribute), 47  
`append()` (*emod\_api.serialization.dtkFileTools.DtkFile.CommonInputFile* method), 53  
`append()` (*emod\_api.serialization.dtkFileTools.DtkFile.Objects* method), 53  
`application()` (in module *emod\_api.config.dtk\_post\_process\_adhoc\_events*), 10  
`application()` (in module *emod\_api.config.dtk\_pre\_process\_adhoc\_events*), 10  
`application()` (in module *emod\_api.config.dtk\_pre\_process\_w5ml*), 10  
`application()` (in module *emod\_api.schema.dtk\_post\_process\_schema*), 50  
`apply_overlay()` (*emod\_api.demographics.Demographics.Demographics* method), 12  
`apply_to_defaults_or_nodes()` (in module *emod\_api.demographics.demographics\_utils*), 27  
`arcsec_to_deg()` (in module *emod\_api.demographics.DemographicsGenerator*), 15  
`as_dataframe()` (*emod\_api.channelreports.channels.ChannelReport* method), 8  
`as_dictionary()` (*emod\_api.channelreports.channels.Channel* method), 8  
`as_dictionary()` (*emod\_api.channelreports.channels.Header* method), 7  
`asset collection`, 61  
`assets`, 61  
`Author()` (*emod\_api.migration.migration.Migration* property), 48  
`author()` (*emod\_api.serialization.dtkFileTools.DtkFile* property), 54  
`author()` (*emod\_api.weather.weather.Metadata* property), 56  
`author()` (*emod\_api.weather.weather.Weather* property), 57  

### B

`BaseInputFile` (class in *emod\_api.demographics.BaseInputFile*), 12  
`basicNode()` (in module *emod\_api.demographics.Node*), 22  
`birth_rate()` (*emod\_api.demographics.Node.Node* property), 22  
`BroadcastEvent()` (in module *emod\_api.interventions.common*), 29  
`BroadcastEventToOtherNodes()` (in module *emod\_api.interventions.common*), 29  
`builder`, 61  
`byte_count()` (*emod\_api.serialization.dtkFileTools.DtkFile* property), 54  

### C

`change_individual_property()` (in module *emod\_api.interventions.common*), 41

change\_individual\_property\_at\_age() (in module *emod\_api.interventions.common*), 37

change\_individual\_property\_scheduled() (in module *emod\_api.interventions.common*), 39

change\_individual\_property\_triggered() (in module *emod\_api.interventions.common*), 37

change\_ser\_pop() (in module *emod\_api.serialization.CensusAndModPop*), 50

Channel (class in *emod\_api.channelreports.channels*), 7

channel\_names() (*emod\_api.channelreports.channels.ChannelReport* property), 8

ChannelReport (class in *emod\_api.channelreports.channels*), 8

channels() (*emod\_api.channelreports.channels.ChannelReport* property), 8

chunk\_count() (*emod\_api.serialization.dtkFileTools.DtkFile* property), 54

chunk\_sizes() (*emod\_api.serialization.dtkFileTools.DtkFile* property), 54

chunks() (*emod\_api.serialization.dtkFileTools.DtkFile* property), 54

compress() (*emod\_api.serialization.dtkFileSupport.EllZeeFour* class method), 53

compress() (*emod\_api.serialization.dtkFileSupport.Snappy* class method), 53

compress() (*emod\_api.serialization.dtkFileSupport.Uncompressed* class method), 53

compress() (in module *emod\_api.serialization.dtkFileTools*), 53

compressed() (*emod\_api.serialization.dtkFileTools.DtkFile* property), 54

compression() (*emod\_api.serialization.dtkFileTools.DtkFile* property), 54

ConstantDistribution (class in *emod\_api.demographics.PreDefinedDistributions*), 22

construct() (in module *emod\_api.demographics.grid\_construction*), 29

ConstructNodesFromDataFrame() (in module *emod\_api.demographics.DemographicsInputDataParsers*), 19

copy() (*emod\_api.demographics.PreDefinedDistributions.ConstantDistribution* method), 22

creation\_date() (*emod\_api.weather.weather.Metadata* property), 56

creation\_date() (*emod\_api.weather.weather.Weather* property), 57

**D**

data() (*emod\_api.channelreports.channels.Channel* property), 8

data() (*emod\_api.spatialreports.spatial.SpatialNode* property), 55

data() (*emod\_api.spatialreports.spatial.SpatialReport* property), 55

data() (*emod\_api.weather.weather.Weather* property), 57

data() (*emod\_api.weather.weather.WeatherNode* property), 56

datavalue\_count() (*emod\_api.weather.weather.Metadata* property), 56

datavalue\_count() (*emod\_api.weather.weather.Weather* property), 57

DataValueCount() (*emod\_api.migration.migration.Layer* property), 47

DataValueCount() (*emod\_api.migration.migration.Migration* property), 48

date() (*emod\_api.serialization.dtkFileTools.DtkFile* property), 54

DateCreated() (*emod\_api.migration.migration.Migration* property), 48

default\_population (*emod\_api.demographics.Node.Node* attribute), 21

DefaultSusceptibilityDistribution() (in module *emod\_api.demographics.DemographicsTemplates*), 21

DelayedIntervention() (in module *emod\_api.interventions.common*), 30

Demographics (class in *emod\_api.demographics.Demographics*), 12

DemographicsGenerator (class in *emod\_api.demographics.DemographicsGenerator*), 15

DemographicsOverlay (class in *emod\_api.demographics.Demographics*), 15

DemographicsType (class in *emod\_api.demographics.DemographicsGenerator*), 15

do\_mapping\_from\_events() (in module *emod\_api.config.dtk\_pre\_process\_adhoc\_events*), 10

do\_nodes() (in module *emod\_api.interventions.utils*), 46

dtk\_to\_schema() (in module *emod\_api.schema.get\_schema*), 50

dtk\_version() (*emod\_api.channelreports.channels.ChannelReport* property), 8

`dtk_version()` (*emod\_api.channelreports.channels.Header* module, 11  
*property*), 7  
`DtkFile` (class in *emod\_api.serialization.dtkFileTools*), 53  
`DtkFile.Contents` (class in *emod\_api.serialization.dtkFileTools*), 53  
`DtkFile.Objects` (class in *emod\_api.serialization.dtkFileTools*), 53  
`DtkFileV1` (class in *emod\_api.serialization.dtkFileTools*), 54  
`DtkFileV2` (class in *emod\_api.serialization.dtkFileTools*), 54  
`DtkFileV2.NodesV2` (class in *emod\_api.serialization.dtkFileTools*), 54  
`DtkFileV3` (class in *emod\_api.serialization.dtkFileTools*), 54  
`DtkFileV3.NodesV3` (class in *emod\_api.serialization.dtkFileTools*), 54  
`DtkFileV4` (class in *emod\_api.serialization.dtkFileTools*), 54  
`DtkHeader` (class in *emod\_api.serialization.dtkFileTools*), 53  
`duplicate_nodeID_check()` (in module *emod\_api.demographics.DemographicsInputDataParsers*), 19  
**E**  
`EllZeeFour` (class in *emod\_api.serialization.dtkFileSupport*), 53  
`emod_api` module, 7  
`emod_api.campaign` module, 58  
`emod_api.channelreports` module, 7  
`emod_api.channelreports.channels` module, 7  
`emod_api.config` module, 8  
`emod_api.config.default_from_schema` module, 8  
`emod_api.config.default_from_schema_no_validation` module, 9  
`emod_api.config.dtk_post_process_adhoc_events` module, 10  
`emod_api.config.dtk_pre_process_adhoc_events` module, 10  
`emod_api.config.dtk_pre_process_w5ml` module, 10  
`emod_api.config.from_overrides` module, 10  
`emod_api.config.from_poi_and_binary` module, 10  
`emod_api.config.from_schema` module, 11  
`emod_api.config.schema_to_config` module, 11  
`emod_api.demographics` module, 12  
`emod_api.demographics.BaseInputFile` module, 12  
`emod_api.demographics.Demographics` module, 12  
`emod_api.demographics.demographics_utils` module, 27  
`emod_api.demographics.DemographicsGenerator` module, 15  
`emod_api.demographics.DemographicsInputDataParsers` module, 19  
`emod_api.demographics.DemographicsTemplates` module, 19  
`emod_api.demographics.grid_construction` module, 29  
`emod_api.demographics.Node` module, 21  
`emod_api.demographics.PreDefinedDistributions` module, 22  
`emod_api.demographics.PropertiesAndAttributes` module, 23  
`emod_api.demographics.Updateable` module, 27  
`emod_api.interventions` module, 29  
`emod_api.interventions.common` module, 29  
`emod_api.interventions.import_pressure` module, 43  
`emod_api.interventions.migration` module, 43  
`emod_api.interventions.node_multiplier` module, 44  
`emod_api.interventions.outbreak` module, 45  
`emod_api.interventions.simple_vaccine` module, 45  
`emod_api.interventions.utils` module, 46  
`emod_api.migration` module, 46  
`emod_api.migration.client` module, 46  
`emod_api.migration.client.client` module, 46  
`emod_api.migration.migration` module, 47  
`emod_api.schema` module, 50  
`emod_api.schema.dtk_post_process_schema` module, 50

module, 50  
 emod\_api.schema.get\_schema  
     module, 50  
 emod\_api.schema\_to\_class  
     module, 59  
 emod\_api.serialization  
     module, 50  
 emod\_api.serialization.CensusAndModPop  
     module, 50  
 emod\_api.serialization.dtkFileSupport  
     module, 53  
 emod\_api.serialization.dtkFileTools  
     module, 53  
 emod\_api.serialization.dtkFileUtility  
     module, 55  
 emod\_api.serialization.SerializedPopulation  
     module, 50  
 emod\_api.spatialreports  
     module, 55  
 emod\_api.spatialreports.spatial  
     module, 55  
 emod\_api.tabularoutput  
     module, 56  
 emod\_api.weather  
     module, 56  
 emod\_api.weather.weather  
     module, 56  
 EveryoneInitiallySusceptible() (in module  
     emod\_api.demographics.DemographicsTemplates), 20  
 examine\_file() (in module  
     emod\_api.migration.migration), 49  
 experiment, 61

## F

FAMILY (emod\_api.migration.migration.Migration attribute), 47  
 FEMALE (emod\_api.migration.migration.Migration attribute), 48  
 fill\_nodes\_legacy() (in module  
     emod\_api.demographics.DemographicsInputDataParsers), 19  
 finalize() (emod\_api.schema\_to\_class.ReadOnlyDict method), 59  
 find() (in module emod\_api.serialization.SerializedPopulation), 52

## G

flattenConfig() (in module  
     emod\_api.config.from\_overrides), 10  
 flush() (emod\_api.serialization.SerializedPopulation method), 51  
 from\_csv() (emod\_api.weather.weather.Weather class method), 57  
 from\_csv() (in module  
     emod\_api.demographics.Demographics), 12  
 from\_csv() (in module  
     emod\_api.migration.migration), 49  
 from\_data() (emod\_api.demographics.Node.Node class method), 22  
 from\_dataframe() (in module  
     emod\_api.demographics.DemographicsGenerator), 16  
 from\_demog\_and\_param\_gravity() (in module  
     emod\_api.migration.migration), 49  
 from\_demog\_and\_param\_gravity\_webservice() (in module emod\_api.migration.migration), 49  
 from\_dict() (emod\_api.demographics.PropertiesAndAttributes.Individual method), 25  
 from\_dict() (emod\_api.demographics.PropertiesAndAttributes.Individual method), 24  
 from\_dict() (emod\_api.demographics.PropertiesAndAttributes.Individual method), 25  
 from\_dict() (emod\_api.demographics.PropertiesAndAttributes.NodeAttribute method), 26  
 from\_file() (emod\_api.weather.weather.Metadata class method), 57  
 from\_file() (in module  
     emod\_api.demographics.Demographics), 12  
 from\_file() (in module  
     emod\_api.demographics.DemographicsGenerator), 18  
 from\_file() (in module  
     emod\_api.migration.migration), 49  
 from\_params() (in module  
     emod\_api.demographics.Demographics), 12  
 from\_params() (in module  
     emod\_api.migration.migration), 49  
 from\_pop\_csv() (in module  
     emod\_api.demographics.Demographics), 12  
 from\_template\_node() (in module  
     emod\_api.demographics.Demographics), 12  
 FullRisk() (in module  
     emod\_api.demographics.DemographicsTemplates), 19

## GenderDataType()

(emod\_api.migration.migration.Migration property), 48

## generate\_file()

(emod\_api.demographics.DemographicsGenerator.Demographics method), 16

## generate\_file()

(emod\_api.demographics.BaseInputFile.BaseInputFile method), 12



`generate_file()` (*emod\_api.demographics.Demographics.DemographicsGenerator.DemographicsGenerator*), 58  
     *method*), 13      `get_trigger_list()` (in module *emod\_api.campaign*), 58  
`generate_headers()` (*emod\_api.demographics.BaseInputFile.BaseInputFile*), 58  
     *method*), 12      `get_waning_from_params()` (in module *emod\_api.interventions.utils*), 46  
`generate_metadata()` (*emod\_api.demographics.DemographicsGenerator.DemographicsGenerator*), 22  
     *method*), 16      `get_xpix_ypix()` (in module *emod\_api.demographics.Node*), 22  
`generate_nodes()` (*emod\_api.demographics.DemographicsGenerator.DemographicsGenerator*), 16  
     *method*), 16      `Header` (class in *emod\_api.channelreports.channels*), 7  
`get_adhocs()` (in module *emod\_api.campaign*), 58      `header()` (*emod\_api.channelreports.channels.ChannelReport*  
     property), 8  
`get_bbox()` (in module *emod\_api.demographics.grid\_construction*), 29      `header()` (*emod\_api.serialization.dtkFileTools.DtkFile*  
     property), 53  
`get_class_with_defaults()` (in module *emod\_api.schema\_to\_class*), 59      high-performance computing (HPC), 61  
`get_config_from_default_and_params()` (in module *emod\_api.config.default\_from\_schema\_no\_validation*), 9  
     9      HSB () (in module *emod\_api.interventions.common*), 30  
`get_default_config_from_schema()` (in module *emod\_api.config.default\_from\_schema\_no\_validation*), 9  
     9      `id()` (*emod\_api.demographics.Node.Node* property), 22  
`get_default_for_complex_type()` (in module *emod\_api.schema\_to\_class*), 59      `id()` (*emod\_api.spatialreports.spatial.SpatialNode*  
     property), 55  
`get_event()` (in module *emod\_api.campaign*), 58      `id()` (*emod\_api.weather.weather.WeatherNode* prop-  
     erty), 56  
`get_fert_dist()` (in module *emod\_api.demographics.DemographicsTemplates*), 21      `id_reference()` (*emod\_api.weather.weather.Metadata*  
     property), 56  
`get_grid_cell_id()` (in module *emod\_api.demographics.grid\_construction*), 29      `id_reference()` (*emod\_api.weather.weather.Weather*  
     property), 57  
`get_next_individual_suid()` (*emod\_api.serialization.SerializedPopulation.SerializedPopulation*), 51      IDREF\_GRUMP1DEGREE  
     (*emod\_api.migration.migration.Migration*  
     attribute), 48  
`get_next_infection_suid()` (*emod\_api.serialization.SerializedPopulation.SerializedPopulation*), 51      IDREF\_GRUMP2PT5ARCMIN  
     (*emod\_api.migration.migration.Migration*  
     attribute), 48  
`get_node()` (*emod\_api.demographics.Demographics.Demographics*), 13      IDREF\_LEGACY (*emod\_api.migration.migration.Migration*  
     attribute), 47  
`get_node_ids_from_file()` (in module *emod\_api.demographics.Demographics*), 12      `IdReference()` (*emod\_api.migration.migration.Migration*  
     property), 48  
`get_node_offsets()` (*emod\_api.migration.migration.Migration*), 48      `IndividualAttributes` (class in *emod\_api.demographics.PropertiesAndAttributes*), 23  
`get_node_pops_from_params()` (in module *emod\_api.demographics.Demographics*), 12      `IndividualAttributes.AgeDistribution`  
     (class in *emod\_api.demographics.PropertiesAndAttributes*), 24  
`get_parameters()` (in module *emod\_api.serialization.SerializedPopulation*), 52      `IndividualAttributes.MortalityDistribution`  
     (class in *emod\_api.demographics.PropertiesAndAttributes*), 24  
`get_recv_trigger()` (in module *emod\_api.campaign*), 58      `IndividualAttributes.SusceptibilityDistribution`  
     (class in *emod\_api.demographics.PropertiesAndAttributes*), 24  
`get_schema()` (in module *emod\_api.campaign*), 58      `IndividualProperties` (class in *emod\_api.demographics.PropertiesAndAttributes*),  
`get_send_trigger()` (in module *emod\_api.campaign*), 58

23  
IndividualProperty (class in *emod\_api.demographics.PropertiesAndAttributes*), 29

23 **M**

infer\_natural\_mortality() (method), 15  
make\_config\_from\_poi() (in module *emod\_api.config.from\_poi\_and\_binary*), 11

init\_resolution\_from\_file() (method), 22  
make\_config\_from\_poi\_and\_config\_dict() (in module *emod\_api.config.from\_poi\_and\_binary*), 10

InitAgeUniform() (in module *emod\_api.demographics.DemographicsTemplates*), 21  
make\_config\_from\_poi\_and\_config\_file() (in module *emod\_api.config.from\_poi\_and\_binary*), 10

InitPrevUniform() (in module *emod\_api.demographics.DemographicsTemplates*), 20  
make\_config\_from\_poi\_and\_schema() (in module *emod\_api.config.from\_poi\_and\_binary*), 10

InitRiskExponential() (in module *emod\_api.demographics.DemographicsTemplates*), 20  
MALE (*emod\_api.migration.migration.Migration* attribute), 48

InitRiskLogNormal() (in module *emod\_api.demographics.DemographicsTemplates*), 20  
MAX\_AGE (*emod\_api.migration.migration.Migration* attribute), 48

InitRiskUniform() (in module *emod\_api.demographics.DemographicsTemplates*), 19  
Metadata (class in *emod\_api.weather.weather*), 56  
metadata() (*emod\_api.weather.weather.Weather* property), 57

InitSusceptConstant() (in module *emod\_api.demographics.DemographicsTemplates*), 20  
Migration (class in *emod\_api.migration.migration*), 47  
MigrationType() (*emod\_api.migration.migration.Migration* property), 48

InterpolationType() (in module *emod\_api.migration.migration*), 48  
emod\_api, 7  
emod\_api.campaign, 58  
emod\_api.channelreports, 7  
emod\_api.channelreports.channels, 7  
emod\_api.config, 8  
emod\_api.config.default\_from\_schema, 8  
emod\_api.config.default\_from\_schema\_no\_validation, 9  
emod\_api.config.dtk\_post\_process\_adhoc\_events, 10  
emod\_api.config.dtk\_pre\_process\_adhoc\_events, 10  
emod\_api.config.dtk\_pre\_process\_w5ml, 10  
emod\_api.config.from\_overrides, 10  
emod\_api.config.from\_poi\_and\_binary, 10  
emod\_api.config.from\_schema, 11  
emod\_api.config.schema\_to\_config, 11  
emod\_api.demographics, 12  
emod\_api.demographics.BaseInputFile, 12  
emod\_api.demographics.Demographics, 12

interval() (*emod\_api.spatialreports.spatial.SpatialReport* property), 55

INTERVENTION (*emod\_api.migration.migration.Migration* attribute), 47

InvalidResolution, 15

**L**

lat() (*emod\_api.demographics.Node.Node* property), 22

lat\_lon\_from\_nodeid() (in module *emod\_api.demographics.Node*), 22

Layer (class in *emod\_api.migration.migration*), 47

LINEAR\_INTERPOLATION (*emod\_api.migration.migration.Migration* attribute), 47

load\_default\_config\_as\_rod() (in module *emod\_api.config.default\_from\_schema\_no\_validation*), 9

LOCAL (*emod\_api.migration.migration.Migration* attribute), 47

lon() (*emod\_api.demographics.Node.Node* property), 22

lon\_lat\_2\_point() (in module

---

```

emod_api.demographics.demographics_utils, 21
27 MortalityStructureNigeriaDHS() (in module
emod_api.demographics.DemographicsGenerator, 21
15 emod_api.demographics.DemographicsTemplates, 21
emod_api.demographics.DemographicsInputDataParsers, 19
19 MigrationDistributor() (in module
emod_api.interventions.common), 30
emod_api.demographics.DemographicsTemplates, 19
N
emod_api.demographics.grid_construction, 29
29 new_intervention() (in module
emod_api.interventions.import_pressure),
emod_api.demographics.Node, 21 43
emod_api.demographics.PreDefinedDistributions, 22
22 new_intervention() (in module
emod_api.interventions.node_multiplier),
emod_api.demographics.PropertiesAndAttributes, 23
23 new_intervention() (in module
emod_api.interventions.outbreak), 45
emod_api.demographics.Updateable, 27
emod_api.interventions, 29 new_intervention() (in module
emod_api.interventions.common, 29 emod_api.interventions.simple_vaccine),
emod_api.interventions.import_pressure, 43
43 new_intervention2() (in module
emod_api.interventions.simple_vaccine),
emod_api.interventions.migration, 43
emod_api.interventions.node_multiplier, 44
44 new_intervention_as_file() (in module
emod_api.interventions.import_pressure), 43
emod_api.interventions.outbreak, 45
emod_api.interventions.simple_vaccine, 45
45 new_intervention_as_file() (in module
emod_api.interventions.node_multiplier), 45
emod_api.interventions.utils, 46
emod_api.migration, 46
emod_api.migration.client, 46
emod_api.migration.client.client, 46
emod_api.migration.migration, 47
emod_api.schema, 50
emod_api.schema.dtk_post_process_schema, 50
50 NLHTI() (in module emod_api.interventions.common),
emod_api.schema.get_schema, 50 31
emod_api.schema_to_class, 50
emod_api.serialization, 50
emod_api.serialization.CensusAndModPop, 50
50 node_count() (emod_api.demographics.Demographics.Demographics
property), 13
emod_api.serialization.dtkFileSupport, 53
53 node_count() (emod_api.spatialreports.spatial.SpatialReport
property), 55
emod_api.serialization.dtkFileTools, 53
53 node_count() (emod_api.weather.weather.Metadata
property), 57
emod_api.serialization.dtkFileUtility, 55
55 node_count() (emod_api.weather.weather.Weather
property), 57
emod_api.serialization.SerializedPopulation, 50
50 node_ID_from_lat_long() (in module
emod_api.demographics.DemographicsInputDataParsers),
emod_api.spatialreports, 55 19
emod_api.spatialreports.spatial, 55
55 node_ids() (emod_api.demographics.Demographics.Demographics
property), 13
emod_api.tabularoutput, 56
emod_api.weather, 56
emod_api.weather.weather, 56
56 node_ids() (emod_api.spatialreports.spatial.SpatialReport
property), 55
MortalityRateByAge() (in module
emod_api.demographics.DemographicsTemplates), 57
57 node_ids() (emod_api.weather.weather.Metadata
property), 57

```

node\_ids() (*emod\_api.weather.weather.Weather* property), 57

NodeAttributes (class in *emod\_api.demographics.PropertiesAndAttributes*), 25

NodeCount() (*emod\_api.migration.migration.Layer* property), 47

NodeCount() (*emod\_api.migration.migration.Migration* property), 48

nodeid\_from\_lat\_lon() (in module *emod\_api.demographics.Node*), 22

NodeOffsets() (*emod\_api.migration.migration.Migration* property), 48

nodes() (*emod\_api.demographics.Demographics.Demographics* property), 13

Nodes() (*emod\_api.migration.migration.Migration* property), 48

nodes() (*emod\_api.serialization.dtkFileTools.DtkFile* property), 54

nodes() (*emod\_api.serialization.SerializedPopulation.SerializedPopulation* property), 51

nodes() (*emod\_api.spatialreports.spatial.SpatialReport* property), 55

nodes() (*emod\_api.weather.weather.Metadata* property), 57

nodes() (*emod\_api.weather.weather.Weather* property), 57

nodes\_for\_DTK() (in module *emod\_api.demographics.Node*), 22

NoInitialPrevalence() (in module *emod\_api.demographics.DemographicsTemplates*), 20

NoRisk() (in module *emod\_api.demographics.DemographicsTemplates*), 19

NullPtr (class in *emod\_api.serialization.dtkFileSupport*), 53

num\_channels() (*emod\_api.channelreports.channels.ChannelReport* property), 8

num\_channels() (*emod\_api.channelreports.channels.Header* property), 7

num\_time\_steps() (*emod\_api.channelreports.channels.ChannelReport* property), 8

num\_time\_steps() (*emod\_api.channelreports.channels.Header* property), 7

**O**

ONE\_FOR\_EACH\_GENDER (*emod\_api.migration.migration.Migration* attribute), 47

OverlayNode (class in *emod\_api.demographics.Node*), 22

## P

PIECEWISE\_CONSTANT

point\_2\_grid\_cell\_id\_lookup() (in module *emod\_api.demographics.grid\_construction*), 29

pop() (*emod\_api.demographics.Node.Node* property), 22

PropertyValueChanger() (in module *emod\_api.interventions.common*), 31

provenance() (*emod\_api.weather.weather.Metadata* property), 57

provenance() (*emod\_api.weather.weather.Weather* property), 57

## R

read() (in module *emod\_api.serialization.dtkFileTools*), 54

ReadOnlyDict (class in *emod\_api.schema\_to\_class*), 59

recursor() (in module *emod\_api.schema.dtk\_post\_process\_schema*), 50

REGIONAL (*emod\_api.migration.migration.Migration* attribute), 47

report\_type() (*emod\_api.channelreports.channels.ChannelReport* property), 8

report\_type() (*emod\_api.channelreports.channels.Header* property), 7

report\_version() (*emod\_api.channelreports.channels.ChannelReport* property), 8

report\_version() (*emod\_api.channelreports.channels.Header* property), 7

res\_in\_degrees(*emod\_api.demographics.Node.Node* attribute), 21

reset() (in module *emod\_api.campaign*), 58

run() (in module *emod\_api.migration.client.client*), 46

## S

SAME\_FOR\_BOTH\_GENDERS

SCHEDULED\_CAMPAGN (*emod\_api.migration.migration.Migration* attribute), 47

save() (in module *emod\_api.campaign*), 58

ScheduledCampaignEvent() (in module *emod\_api.interventions.common*), 32

schema\_to\_config() (in module *emod\_api.config.from\_poi\_and\_binary*), 10

schema\_to\_config\_subnode() (in module *emod\_api.config.default\_from\_schema\_no\_validation*), 9

SchemaConfigBuilder (class in *emod\_api.config.from\_schema*), 11

SchemaConfigBuilder	(class in <i>emod_api.config.schema_to_config</i> ), 11	SetDefaultNodeAttributes()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 14
SEA	( <i>emod_api.migration.migration.Migration</i> attribute), 47	SetDefaultProperties()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 14
seed_by_coverage()	(in module <i>emod_api.interventions.outbreak</i> ), 45	SetDefaultPropertiesFertMort()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 14
SerializedPopulation	(class in <i>emod_api.serialization.SerializedPopulation</i> ), 50	SetEquilibriumAgeDistFromBirthAndMortRates()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 14
SerialObject	(class in <i>emod_api.serialization.dtkFileSupport</i> ), 53	SetHeteroRiskExponDist()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 15
set_demog_distributions()	(in module <i>emod_api.demographics.demographics_utils</i> ), 28	SetHeteroRiskLognormalDist()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 15
set_growing_demographics()	(in module <i>emod_api.demographics.demographics_utils</i> ), 28	SetHeteroRiskUniformDist()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 14
set_immune_mod()	(in module <i>emod_api.demographics.demographics_utils</i> ), 27	SetIndividualAttributesWithFertMort()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 13
set_resolution()	( <i>emod_api.demographics.DemographicsGenerator</i> method), 16	SetInitialAgeExponential()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 14
set_risk_mod()	(in module <i>emod_api.demographics.demographics_utils</i> ), 27	SetInitialAgeLikeSubSaharanAfrica()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 14
set_schema()	( <i>emod_api.schema_to_class.ReadOnlyDict</i> method), 59	SetInitPrevFromUniformDraw()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 14
set_schema()	(in module <i>emod_api.campaign</i> ), 58	SetMinimalNodeAttributes()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 13
set_schema()	(in module <i>emod_api.config.from_poi_and_binary</i> ), 10	SetMortalityDistribution()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 13
set_static_demographics()	(in module <i>emod_api.demographics.demographics_utils</i> ), 28	SetMortalityRate()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 13
SetAgeDistribution()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 14	SetNodeDefaultFromTemplate()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 14
SetBirthRate()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 13	SetOverdispersion()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 14
SetConstantRisk()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 14	SimpleSusceptibilityDistribution()	(in module <i>emod_api.demographics.DemographicsTemplates</i> ), 20
SetConstantSusceptibility()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 14	simulation()	( <i>emod_api.serialization.dtkFileTools.DtkFileV1</i> property), 54
SetDefaultFromTemplate()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 14	simulation()	( <i>emod_api.serialization.dtkFileTools.DtkFileV2</i> property), 54
SetDefaultIndividualAttributes()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 13		
SetDefaultIndividualProperties()	( <i>emod_api.demographics.Demographics.Demographics</i> method), 14		



property), 54  
 simulation() (emod\_api.serialization.dtkFileTools.DtkFileV3  
 property), 54  
 Snappy (class in emod\_api.serialization.dtkFileSupport),  
 53  
 SpatialNode (class in  
 emod\_api.spatialreports.spatial), 55  
 SpatialReport (class in  
 emod\_api.spatialreports.spatial), 55  
 StandardDiagnostic() (in module  
 emod\_api.interventions.common), 34  
 start() (emod\_api.spatialreports.spatial.SpatialReport  
 property), 55  
 start\_time() (emod\_api.channelreports.channels.ChannelReport  
 property), 8  
 start\_time() (emod\_api.channelreports.channels.Header  
 property), 7  
 STATIC (emod\_api.demographics.DemographicsGenerator.DemographicsType  
 attribute), 15  
 step\_size() (emod\_api.channelreports.channels.ChannelReport  
 property), 8  
 step\_size() (emod\_api.channelreports.channels.Header  
 property), 7  
 StepFunctionSusceptibility() (in module  
 emod\_api.demographics.DemographicsTemplates),  
 20  
**T**  
 task, 61  
 template, 61  
 time\_stamp() (emod\_api.channelreports.channels.ChannelReport  
 property), 8  
 time\_stamp() (emod\_api.channelreports.channels.Header  
 property), 7  
 time\_steps() (emod\_api.spatialreports.spatial.SpatialReport  
 property), 55  
 title() (emod\_api.channelreports.channels.Channel  
 property), 8  
 to\_csv() (in module emod\_api.migration.migration),  
 49  
 to\_dict() (emod\_api.demographics.Demographics.DemographicsOverlay  
 method), 12  
 to\_dict() (emod\_api.demographics.Demographics.DemographicsOverlay  
 method), 15  
 to\_dict() (emod\_api.demographics.Node.Node  
 method), 21  
 to\_dict() (emod\_api.demographics.PreDefinedDistributions.ConstantDistribution  
 method), 22  
 to\_dict() (emod\_api.demographics.PropertiesAndAttributes.IndividualAttributes  
 method), 25  
 to\_dict() (emod\_api.demographics.PropertiesAndAttributes.IndividualAttributes  
 method), 24  
 to\_dict() (emod\_api.demographics.PropertiesAndAttributes.IndividualAttributes  
 method), 25  
 to\_dict() (emod\_api.demographics.PropertiesAndAttributes.IndividualAttributes  
 method), 24  
 to\_dict() (emod\_api.demographics.PropertiesAndAttributes.IndividualAttributes  
 method), 23  
 to\_dict() (emod\_api.demographics.PropertiesAndAttributes.IndividualAttributes  
 method), 23  
 to\_dict() (emod\_api.demographics.PropertiesAndAttributes.IndividualAttributes  
 method), 26  
 to\_dict() (emod\_api.demographics.Updateable.Updateable  
 method), 27  
 to\_file() (emod\_api.demographics.Demographics.DemographicsOverlay  
 method), 15  
 to\_file() (emod\_api.migration.migration.Migration  
 method), 48  
 to\_file() (emod\_api.schema\_to\_class.ReadOnlyDict  
 method), 59  
 to\_tuple() (emod\_api.demographics.Node.Node  
 method), 21  
 Tool() (emod\_api.migration.migration.Migration  
 property), 48  
 tool() (emod\_api.serialization.dtkFileTools.DtkFile  
 property), 54  
 triggered\_campaign\_delay\_event() (in mod-  
 ule emod\_api.interventions.common), 35  
 triggered\_campaign\_event\_with\_optional\_delay()  
 (in module emod\_api.interventions.common),  
 35  
 TriggeredCampaignEvent() (in module  
 emod\_api.interventions.common), 33  
**U**  
 uncompress() (emod\_api.serialization.dtkFileSupport.EllZeeFour  
 class method), 53  
 uncompress() (emod\_api.serialization.dtkFileSupport.Snappy  
 class method), 53  
 uncompress() (emod\_api.serialization.dtkFileSupport.Uncompressed  
 class method), 53  
 uncompress() (in module  
 emod\_api.serialization.dtkFileTools), 53  
 Uncompressed (class in  
 emod\_api.serialization.dtkFileSupport), 53  
 units() (emod\_api.channelreports.channels.Channel  
 property), 8  
 update() (emod\_api.demographics.Updateable.Updateable  
 method), 27  
 update\_resolution()  
 (emod\_api.demographics.PreDefinedDistributions.ConstantDistribution  
 method), 22  
 update\_resolution()  
 (emod\_api.weather.weather.Weather  
 property), 57  
 update\_resolution()  
 (emod\_api.weather.weather.Weather  
 property), 57  
 Updateable (class in  
 emod\_api.demographics.Mortality.Distribution), 27

## V

`validate_res_in_arcsec()` (in module *emod\_api.demographics.DemographicsGenerator*), 15

`version()` (*emod\_api.serialization.dtkFileTools.DtkFile* property), 54

## W

`Weather` (class in *emod\_api.weather.weather*), 57

`WeatherNode` (class in *emod\_api.weather.weather*), 56

`write()` (*emod\_api.serialization.SerializedPopulation.SerializedPopulation* method), 51

`write()` (in module *emod\_api.serialization.dtkFileTools*), 54

`write_config_from_default_and_params()` (in module *emod\_api.config.default\_from\_schema\_no\_validation*), 9

`write_default_from_schema()` (in module *emod\_api.config.default\_from\_schema*), 8

`write_default_from_schema()` (in module *emod\_api.config.default\_from\_schema\_no\_validation*), 9

`write_file()` (*emod\_api.channelreports.channels.ChannelReport* method), 8

`write_file()` (*emod\_api.spatialreports.spatial.SpatialReport* method), 55

`write_file()` (*emod\_api.weather.weather.Metadata* method), 57

`write_file()` (*emod\_api.weather.weather.Weather* method), 57

## X

`xpix_ypix_from_lat_lon()` (in module *emod\_api.demographics.Node*), 22