
emodpy-tbhiv

Institute for Disease Modeling

Jan 31, 2022

CONTENTS

1 emodpy-tbhiv installation	3
1.1 Prerequisites	3
1.2 Installation instructions	3
2 emodpy_tbhiv	5
2.1 emodpy_tbhiv package	5
2.1.1 Subpackages	5
Python Module Index	21
Index	23

emodpy-tbhiv is a collection of Python scripts and utilities created to streamline user interactions with EMOD and idmtools for modeling measles. Much of the functionality is inherited from the `emod_api` and `emodpy` packages.

Additional information about how to use idmtools can be found at in [Welcome to idmtools](#). Additional information about EMOD TBHIV parameters for modeling tuberculosis can be found in [EMOD parameter reference](#).

See [Welcome to idmtools](#) for a diagram showing how idmtools and each of the related packages are used in an end-to-end workflow using EMOD as the disease transmission model.

EMODPY-TBHIV INSTALLATION

Follow the steps below to install emodpy-tbhiv.

1.1 Prerequisites

First, ensure the following prerequisites are met.

- Windows 10 Pro or Enterprise, Linux, or Mac
- Python 3.6 64-bit (<https://www.python.org/downloads/release>)
- A file that indicates the pip index-url:
 - Windows
 - Linux

In C:\Users\Username\pip\pip.ini, containing the following:

```
[global]
index-url = https://packages.idmod.org/api/pypi/pypi-production/simple
```

In \$HOME/.config/pip/pip.conf, containing the following:

```
[global]
index-url = https://packages.idmod.org/api/pypi/pypi-production/simple
```

1.2 Installation instructions

1. Open a command prompt and create a virtual environment in any directory you choose. The command below names the environment “v-emodpy-tbhiv”, but you may use any desired name:

```
python -m venv v-emodpy-tbhiv
```

2. Activate the virtual environment:

- Windows
- Linux

Enter the following:

```
v-emodpy-tbhiv\Scripts\activate
```

emodpy-tbhiv

Enter the following:

```
source v-emodpy-tbhiv/bin/activate
```

3. Install emodpy-tbhiv packages:

```
pip install emodpy-tbhiv
```

If you are on Python 3.6, also run:

```
pip install dataclasses
```

If you are on Linux, also run:

```
pip install keyrings.alt
```

4. When you are finished, deactivate the virtual environment by entering the following at a command prompt:

```
deactivate
```

EMODPY_TBHIV

2.1 emodpy_tbhiv package

The emodpy-tbhiv module is intended to house scripts and tools that enable disease modelers to work more easily with the IDM EMOD TBHIV model.

2.1.1 Subpackages

emodpy_tbhiv.demographics package

Submodules

emodpy_tbhiv.demographics.TBHIVDemographics module

```
class emodpy_tbhiv.demographics.TBHIVDemographics(pop,
                                                    nodes=None,
                                                    idref='Gridded'
                                                    world
                                                    grump2.5arcmin',
                                                    base_file=None)
```

Bases: emod_api.demographics.Demographics.Demographics

This class is derived from emod_api.demographics' Demographics class so that we can set certain defaults for TBHIV in construction. Keen observers will note that SetDefaultProperties does not look like a TBHIV-specific function. But as we add other disease types the generalizations and specifics will become clearer. The architectural point is solid.

SetHIVCoInfectionDistribution()

Insert some notion of a default HIVCoInfection distribution.

SetHIVTBCoInfectionMortalityDistribution()

Insert some notion of a default HIVTBCoInfection Mortality distribution.

```
emodpy_tbhiv.demographics.TBHIVDemographics.fromBasicNode(lat=0,          lon=0,
                                                               pop=1000000.0,
                                                               name=1,
                                                               forced_id=1,      im-
                                                               plicit_config_fns=None)
```

This function creates a single-node TBHIVDemographics instance from the params you give it.

```
emodpy_tbhiv.demographics.TBHIVDemographics.fromData(pop=1000000.0, file-
name_male='Malawi_male_mortality.csv',
file-
name_female='Malawi_female_mortality.csv')
```

emodpy_tbhiv.interventions package

```
emodpy_tbhiv.interventions.purge_campaign_event(camp_event)
```

Submodules

emodpy_tbhiv.interventions.active_diagnostic module

```
emodpy_tbhiv.interventions.active_diagnostic.ActiveDiagnostic(camp, trigger_treatment_list,
ac-
tive_sensitivity=1.0,
ac-
tive_specificity=1.0,
pos_event='TBTestPositive',
treat-
ment_fraction=1,
start_day=0,
duration=-
1, prop-
erty_restrictions_list=[],
nodeIDs=[],
black_period=0,
black_trigger='Blackout',
event_name='TB
Diagnosis Active
Simple')
```

Create and return triggered campaign event that issues an ActiveDiagnostic intervention. See [ActiveDiagnostic](#)

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **active_sensitivity** – Sensitivity. Defaults to 1.0.
- **active_specificity** – Specificity. Defaults to 1.0.
- **pos_event** – Signal (or trigger) which is broadcast if the test is positive. Defaults to ‘TBTestPositive’,
- **treatment_fraction** – Fraction of population testing positive you get the positive result effect.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.

- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.active_diagnostic.new_intervention_as_file(camp,
                                                                     start_day=1,
                                                                     file-
                                                                     name=None)
```

emodpy_tbhiv.interventions.art module

```
emodpy_tbhiv.interventions.art.ART(camp, trigger_treatment_list, start_day=0, duration=-
                                     1, property_restrictions_list=[], nodeIDs=[], black_period=0, black_trigger='Blackout',
                                     event_name='ART')
```

Create and return triggered campaign event that issues an ART intervention.

Parameters

- **camp** – Centralized campaign module instance.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.art.new_intervention_as_file(camp,filename='art.json')
```

emodpy_tbhiv.interventions.bcg module

```
emodpy_tbhiv.interventions.bcg.BCG(camp, trigger_treatment_list, initial_efficacy=1.0, vaccine_take=1, age_take_decay=1.0, box_duration=365, immune_decay=3650, start_day=0, duration=- 1, property_restrictions_list=[], nodeIDs=[], black_period=0, black_trigger='Blackout', event_name='Vaccine Health Seeking')
```

Create and return triggered campaign event that issues an BCG vaccine intervention.

Parameters

- **camp** – Centralized campaign module instance.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **initial_efficacy** – Initial efficacy of the vaccine. Defaults to 1.0.
- **vaccine_take** – Fraction of the population receiving the vaccine for whom it is efficacious. Defaults to 1.0.
- **age_take_decay** – . Defaults to 1.0.
- **box_duration** – Period of time over which the initial efficacy persists before decay. Defaults to 1 year.
- **immune_decay** – Period of time over which the efficacy decays to 0. Defaults to 10 years.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.bcg.new_intervention_as_file(camp, filename=None)
```

emodpy_tbhiv.interventions.cd4diag module

```
emodpy_tbhiv.interventions.cd4diag.CD4Diag(camp, trigger_treatment_list, event_200='Below200', event_350='Below350', event_500='Below500', event_above_500='Above500', start_day=0, duration=- 1, property_restrictions_list=[], nodeIDs=[], black_period=0, black_trigger='Blackout', event_name='CD4 Diagnostic')
```

Create and return triggered campaign event that issues an CD4Diagnostic intervention.

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **event_200** – ...
- **event_350** – ...
- **event_500** – ...
- **event_above_500** – ...
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.cd4diag.new_intervention_as_file(camp, file-  
name='cd4.json')
```

emodpy_tbhiv.interventions.diag_treat_neg module

```
emodpy_tbhiv.interventions.diag_treat_neg.DiagnosticTreatNeg(camp, trigger_treatment_list,  
base_sensitivity_smearpos=1.0, base_sensitivity_smearneg=1.0,  
pos_event='TBTestPositive', neg_event='TBTestNegative',  
def_event='TBTestDefault', treat-  
ment_fraction=1, start_day=0, duration=- 1, prop-  
erty_restrictions_list=[], nodeIDs=[], black_period=0,  
black_trigger='Blackout', event_name='TB  
Diagnosis')
```

Create and return triggered campaign event that issues an DiagnosticTreatNeg intervention. See [DiagnosticTreatNeg](#)

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.

- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **base_sensitivity_smearpos** – Sensitivity. Defaults to 1.0.
- **base_sensitivity_smearneg** – Specificity. Defaults to 1.0.
- **pos_event** – Signal (or trigger) which is broadcast if the test is positive. Defaults to ‘TBTestPositive’,
- **neg_event** – Defaults to ‘TBTestNegative’.
- **def_event** – Defaults to ‘TBTestDefault’.
- **treatment_fraction** – Fraction of population testing positive you get the positive result effect.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.diag_treat_neg.new_intervention_as_file(camp, file-
name='dtn.json')
```

emodpy_tbhiv.interventions.hiv_diag module

```
emodpy_tbhiv.interventions.hiv_diag.HIVDiagnostic(camp, trigger_treatment_list,
base_sensitivity=1.0,
base_specificity=1.0,
pos_event='HIVTestedPositive',
neg_event='HIVTestedNegative',
treatment_fraction=1,
start_day=0, duration=- 1,
property_restrictions_list=[],
nodeIDs=[], black_period=0,
black_trigger='Blackout',
event_name='HIV Diagnostic')
```

Create and return triggered campaign event that issues an HIVSimpleDiagnostic intervention. See [HIVSimpleDiagnostic](#)

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **base_sensitivity** – Sensitivity. Defaults to 1.0.

- **base_specificity** – Specificity. Defaults to 1.0.
- **pos_event** – Signal (or trigger) which is broadcast if the test is positive. Defaults to ‘HIVTestedPositive’.
- **neg_event** – Signal (or trigger) which is broadcast if the test is negative. Defaults to ‘HIVTestedNegative’.
- **treatment_fraction** – Fraction of population testing positive you get the positive result effect.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.hiv_diag.new_intervention_as_file(camp, file-
name=None)
```

emodpy_tbhiv.interventions.hiv_seeding module

```
emodpy_tbhiv.interventions.hiv_seeding.HIV(camp, time_offset=0, disease='HIV', reps=-
1, interval=1, start_day=0, nodeIDs=[], event_name='HIV Incidence')
```

Create a scheduled campaign event that issues an OutbreakIndividualTBorHIV intervention. Useful for seeding interventions in TBHIV_SIM.

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **time_offset** – ... Defaults to 0.
- **disease** – “TB” or “HIV”. Default is “HIV”.
- **reps** – Number of repetitions (integer). Defaults to no repetition.
- **interval** – Timesteps between repetitions, if reps is set. Defaults to every day.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.hiv_seeding.new_intervention_as_file(camp,      file-
                                                               name='hiv.json')
```

emodpy_tbhiv.interventions.hsb module

```
emodpy_tbhiv.interventions.hsb.HSB(camp, trigger_treatment_list, output_event, probability_per_step=1.0, start_day=0, duration=-1, property_restrictions_list=[], nodeIDs=[], black_period=0, black_trigger='Blackout', event_name='HSB')
```

Create and return triggered campaign event that issues an SimpleHealthSeekingBehavior intervention. See [SimpleHealthSeekingBehavior](#)

Parameters

- **camp** – The [emod_api.campaign](#) module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **output_event** – Signal to broadcast when ‘health’ is ultimately sought (string).
- **probability_per_step** – Probability of seeking per timestep, default to 1 which means near instantaneous.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.hsb.new_intervention_as_file(camp,      file-
                                                               name='hsb_diag.json')
```

emodpy_tbhiv.interventions.ramp_dtn module

```
emodpy_tbhiv.interventions.ramp_dtn.RampDTN(camp, trigger_treatment_list,
                                              ramp_time=30,
                                              base_sensitivity_smearpos=1.0,
                                              base_sensitivity_smearneg=1.0,
                                              base_sensitivity_smearpos2=1.0,
                                              base_sensitivity_smearneg2=1.0,
                                              treatment_fraction=1.0,
                                              treatment_fraction2=1.0,
                                              pos_event='TBTestPositive',
                                              neg_event='TBTestNegative', de-
                                              faulters_event='TBTestDefault',
                                              pos_event2='TBTestPositive', de-
                                              neg_event2='TBTestNegative', de-
                                              faulters_event2='TBTestDefault',
                                              start_day=0, duration=-1, prop-
                                              erty_restrictions_list=[], nodeIDs=[],
                                              black_period=0, black_trigger='Blackout',
                                              event_name='RampDTN')
```

Create and return triggered campaign event that (TBD).

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **active_sensitivity** – Sensitivity. Defaults to 1.0.
- **active_specificity** – Specificity. Defaults to 1.0.
- **pos_event** – Signal (or trigger) which is broadcast if the test is positive. Defaults to ‘TBTestPositive’,
- **treatment_fraction** – Fraction of population testing positive you get the positive result effect.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.ramp_dtn.new_intervention_as_file(camp, file-
                                                               name='ramp.json')
```

emodpy_tbhiv.interventions.resist_diag module

```
emodpy_tbhiv.interventions.resist_diag.ResistanceDiagnostic(camp, trigger_treatment_list, sensitivity=1.0, specificity=1.0, pos_event='TBMDRTestPositive', neg_event='TBMDRTestNegative', def_event='TBMDRTestDefault', treatment_fraction=1, treatment_fraction_negative_test=1, start_day=0, duration=-1, property_restrictions_list=[], nodeIDs=[], black_period=0, black_trigger='Blackout', event_name='TB Diagnosis MDR')
```

Create and return triggered campaign event that issues an ResistanceDiagnostic intervention.

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **sensitivity** – Sensitivity. Defaults to 1.0.
- **specificity** – Specificity. Defaults to 1.0.
- **pos_event** – Signal (or trigger) which is broadcast if the test is positive. Defaults to ‘TBMDRTestPositive’.
- **neg_event** – Signal (or trigger) which is broadcast if the test is negative. Defaults to ‘TBMDRTestNegative’.
- **def_event** – Signal (or trigger) which is broadcast if the test is default. Defaults to ‘TBMDRTestDefault’.
- **treatment_fraction** – Fraction of population testing positive you get the positive result effect. Defaults to 1.
- **treatment_fraction_negative_test** – ... Defaults to 1.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.

- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.resist_diag.new_intervention_as_file(camp,      file-
                                                               name='resist_diag.json')
```

emodpy_tbhiv.interventions.smear_diag module

```
emodpy_tbhiv.interventions.smear_diag.SmearDiagnostic(camp, trigger_treatment_list,
                                                       base_sensitivity_smearpos=1.0,
                                                       base_sensitivity_smearneg=1.0,
                                                       pos_event='TestPositiveOnSmear',
                                                       treatment_fraction=1,
                                                       start_day=0, duration=- 1,
                                                       property_restrictions_list=[],
                                                       nodeIDs=[], black_period=0,
                                                       black_trigger='Blackout',
                                                       event_name='TB Diagnosis
                                                       Smear Simple')
```

Create and return triggered campaign event that issues an SmearDiagnostic intervention.

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **base_sensitivity_smearpos** – Sensitivity. Defaults to 1.0.
- **base_sensitivity_smearneg** – Specificity. Defaults to 1.0.
- **pos_event** – Signal (or trigger) which is broadcast if the test is positive. Defaults to ‘TBTestPositiveOnSmear’.
- **treatment_fraction** – Fraction of population testing positive you get the positive result effect.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optiional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.smear_diag.new_intervention_as_file(camp,      file-
                                                               name='smear_diag.json')
```

emodpy_tbhiv.interventions.tb_treat_basic module

```
emodpy_tbhiv.interventions.tb_treat_basic.TBDrugTreatment (camp, trigger_treatment_list, drug_name='DOTS', inactivation_rate=0, mortality_rate=0, clearance_rate=0, resistance_rate=0, relapse_rate=0, reduced_transmit=1.0, start_day=0, treatment_duration=180, duration=-1, property_restrictions_list=[], nodeIDs=[], black_period=0, black_trigger='Blackout', event_name='TBDrugTreatment')
```

Create and return triggered campaign event that issues an AntiTBDDrug intervention. See [AntiTBDDrug](#)

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **drug_name** – ... Defaults to ‘DOTS’,
- **inactivation_rate** – ... Defaults to 0,
- **mortality_rate** – ... Defaults to 0,
- **clearance_rate** – ... Defaults to 0,
- **resistance_rate** – ... Defaults to 0,
- **relapse_rate** – ... Defaults to 0,
- **reduced_transmit** – ... Defaults to 1.0,
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.tb_treat_basic.new_intervention_as_file (camp, file_name=None)
```

emodpy_tbhiv.interventions.tbhiv_treat module

```
emodpy_tbhiv.interventions.tbhiv_treat.TBHIVDrugTreatment(camp, trigger_treatment_list, drug_name, latent_multiplier=1.0, active_multiplier=1.0, start_day=0, duration=-1, property_restrictions_list=[], nodeIDs=[], black_period=0, black_trigger='Blackout', event_name='TBHIVDrugTreatment')
```

Create and return triggered campaign event that issues a ‘TBHIVConfigurableTBdrug’ intervention. See [TBHIVConfigurableTBdrug](#)

Parameters

- **camp** – The [emod_api.campaign](#) module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **drug_name** – ...
- **latent_multiplier** – ... Defaults to 1.0.
- **active_multiplier** – ... Defaults to 1.0.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.tbhiv_treat.new_intervention_as_file(camp, file_name='tb_drug_treat.json')
```

emodpy_tbhiv.interventions.triggered_pvc module

```
emodpy_tbhiv.interventions.triggered_pvc.TPVC(camp, trigger_treatment_list, property_to_change, final_prop_value, revert=0, daily_prob=1, start_day=0, duration=-1, property_restrictions_list=[], nodeIDs=[], black_period=0, black_trigger='Blackout', event_name='PropertyValueChanger')
```

Create and return triggered campaign event that issues an PropertyValueChanger intervention. See [PropertyValueChanger](#)

Parameters

- **camp** – The [emod_api.campaign](#) module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **property_to_change** – Individual Property key (string).
- **final_prop_value** – New Individual Property value (string).
- **revert** – ... Defaults to 0.
- **daily_prob** – Daily probability of changing. Defaults to 1.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.triggered_pvc.new_intervention_as_file(camp, filename='tpvc.json')
```

emodpy_tbhiv.interventions.vaccine module

```
emodpy_tbhiv.interventions.vaccine.Vaccine(camp, trigger_treatment_list, initial_efficacy=1.0, vaccine_take=1, vtype='AcquisitionBlocking', box_duration=365, immune_decay=3650, start_day=0, duration=-1, property_restrictions_list=[], nodeIDs=[], black_period=0, black_trigger='Blackout', event_name='Vaccine')
```

Create and return triggered campaign event that issues a (generalized) Vaccine intervention. See [SimpleVaccine](#)

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **initial_efficacy** – Initial efficacy of the vaccine. Defaults to 1.0.
- **vaccine_take** – Fraction of the population receiving the vaccine for whom it is efficacious. Defaults to 1.0.
- **vtype** – ... Defaults to “AcquisitionBlogking”
- **box_duration** – Period of time over which the initial efficacy persists before decay. Defaults to 1 year.
- **immune_decay** – Period of time over which the efficacy decays to 0. Defaults to 10 years.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.vaccine.new_intervention_as_file(camp, file-name='vaccine.json')
```

emodpy_tbhiv.reporters package

Submodules

emodpy_tbhiv.reporters.plugin module

```
class emodpy_tbhiv.reporters.plugin.Report_TBHIV_ByAge(name: str = 'Report_TBHIV_ByAge',  
                                         Enabled: bool = True,  
                                         Reports: list = <factory>,  
                                         dll_file: str = 'libreport_TBHIV_ByAge.dll')  
  
Bases: emodpy.reporters.base.CustomReporter  
  
name: str = 'Report_TBHIV_ByAge'  
dll_file: str = 'libreport_TBHIV_ByAge.dll'  
configure_report(max_age_yrs, min_age_yrs, start_year, stop_year, events=None)
```


PYTHON MODULE INDEX

e

```
emodpy_tbhiv, 5
emodpy_tbhiv.demographics, 5
emodpy_tbhiv.demographics.TBHIVDemographics,
    5
emodpy_tbhiv.interventions, 6
emodpy_tbhiv.interventions.active_diagnostic,
    6
emodpy_tbhiv.interventions.art, 7
emodpy_tbhiv.interventions.bcg, 8
emodpy_tbhiv.interventions.cd4diag, 8
emodpy_tbhiv.interventions.diag_treat_neg,
    9
emodpy_tbhiv.interventions.hiv_diag, 10
emodpy_tbhiv.interventions.hiv_seeding,
    11
emodpy_tbhiv.interventions.hsb, 12
emodpy_tbhiv.interventions.ramp_dtn, 13
emodpy_tbhiv.interventions.resist_diag,
    14
emodpy_tbhiv.interventions.smear_diag,
    15
emodpy_tbhiv.interventions.tb_treat_basic,
    16
emodpy_tbhiv.interventions.tbhiv_treat,
    17
emodpy_tbhiv.interventions.triggered_pvc,
    18
emodpy_tbhiv.interventions.vaccine, 18
emodpy_tbhiv.reporters, 19
emodpy_tbhiv.reporters.plugin, 19
```


INDEX

A

ActiveDiagnostic() (in module `emodpy_tbhiv.interventions.active_diagnostic`), 6

ART() (in module `emodpy_tbhiv.interventions.art`), 7

B

BCG() (in module `emodpy_tbhiv.interventions.bcg`), 8

C

CD4Diag() (in module `emodpy_tbhiv.interventions.cd4diag`), 8

configure_report() (emodpy_tbhiv.reporters.plugin.Report_TBHIV_ByAge method), 19

D

DiagnosticTreatNeg() (in module `emodpy_tbhiv.interventions.diag_treat_neg`), 9

dll_file(emodpy_tbhiv.reporters.plugin.Report_TBHIV_ByAge attribute), 19

E

emodpy_tbhiv module, 5

emodpy_tbhiv.demographics module, 5

emodpy_tbhiv.demographics.TBHIVDemographics module, 5

emodpy_tbhiv.interventions module, 6

emodpy_tbhiv.interventions.active_diagnostic module, 6

emodpy_tbhiv.interventions.art module, 7

emodpy_tbhiv.interventions.bcg module, 8

emodpy_tbhiv.interventions.cd4diag module, 8

emodpy_tbhiv.interventions.diag_treat_neg module, 9

emodpy_tbhiv.interventions.hiv_diag

module, 10
emodpy_tbhiv.interventions.hiv_seeding module, 11
emodpy_tbhiv.interventions.hsb module, 12
emodpy_tbhiv.interventions.ramp_dtn module, 13
emodpy_tbhiv.interventions.resist_diag module, 14
emodpy_tbhiv.interventions.smear_diag module, 15
emodpy_tbhiv.interventions.tb_treat_basic module, 16
emodpy_tbhiv.interventions.tbhiv_treat module, 17
emodpy_tbhiv.interventions.triggered_pvc module, 18
emodpy_tbhiv.interventions.vaccine module, 18
emodpy_tbhiv.reporters module, 19
emodpy_tbhiv.reporters.plugin module, 19

F

fromBasicNode() (in module `emodpy_tbhiv.demographics.TBHIVDemographics`), 5

fromData() (in module `emodpy_tbhiv.demographics.TBHIVDemographics`), 5

H

HIV() (in module `emodpy_tbhiv.interventions.hiv_seeding`), 11
HIVDiagnostic() (in module `emodpy_tbhiv.interventions.hiv_diag`), 10
HSB() (in module `emodpy_tbhiv.interventions.hsb`), 12

M

emodpy_tbhiv, 5

```
emodpy_tbhiv.demographics, 5           new_intervention_as_file() (in module
emodpy_tbhiv.demographics.TBHIVDemographics, emodpy_tbhiv.interventions.hsb), 12
5                                     new_intervention_as_file() (in module
emodpy_tbhiv.interventions, 6           emodpy_tbhiv.interventions.ramp_dtn), 13
emodpy_tbhiv.interventions.active_diagnostic, intervention_as_file() (in module
6                                     emodpy_tbhiv.interventions.resist_diag), 15
emodpy_tbhiv.interventions.art, 7       new_intervention_as_file() (in module
emodpy_tbhiv.interventions.bcg, 8       emodpy_tbhiv.interventions.smear_diag), 15
emodpy_tbhiv.interventions.cd4diag,   new_intervention_as_file() (in module
8                                     emodpy_tbhiv.interventions.tb_treat_basic), 16
emodpy_tbhiv.interventions.diag_treatment, intervention_as_file() (in module
9                                     emodpy_tbhiv.interventions.tbhiv_treat), 17
emodpy_tbhiv.interventions.hiv_diag,  new_intervention_as_file() (in module
10                                    emodpy_tbhiv.interventions.triggered_pvc), 18
emodpy_tbhiv.interventions.hiv_seeding, new_intervention_as_file() (in module
11                                    emodpy_tbhiv.interventions.vaccine), 19
emodpy_tbhiv.interventions.hsb, 12
emodpy_tbhiv.interventions.ramp_dtn, P
13                                     purge_campaign_event() (in module
emodpy_tbhiv.interventions.resist_diag, emodpy_tbhiv.interventions), 6
14
emodpy_tbhiv.interventions.smear_diag, R
15                                     RampDTN() (in module
emodpy_tbhiv.interventions.tb_treat_basic, emodpy_tbhiv.interventions.ramp_dtn), 13
16                                     Report_TBHIV_ByAge (class) in
emodpy_tbhiv.interventions.tbhiv_treat, emodpy_tbhiv.reporters.plugin), 19
17                                     ResistanceDiagnostic() (in module
emodpy_tbhiv.interventions.triggered_pvc, emodpy_tbhiv.interventions.resist_diag),
18                                     14
emodpy_tbhiv.interventions.vaccine,
18
emodpy_tbhiv.reporters, 19
emodpy_tbhiv.reporters.plugin, 19
N
name (emodpy_tbhiv.reporters.plugin.Report_TBHIV_ByAge
attribute), 19
new_intervention_as_file() (in module
emodpy_tbhiv.interventions.active_diagnostic),
7
new_intervention_as_file() (in module
emodpy_tbhiv.interventions.art), 7
new_intervention_as_file() (in module
emodpy_tbhiv.interventions.bcg), 8
new_intervention_as_file() (in module
emodpy_tbhiv.interventions.cd4diag), 9
new_intervention_as_file() (in module
emodpy_tbhiv.interventions.diag_treat_neg),
10
new_intervention_as_file() (in module
emodpy_tbhiv.interventions.hiv_diag), 11
new_intervention_as_file() (in module
emodpy_tbhiv.interventions.hiv_seeding), 12
S
SetHIVCoInfectionDistribution()
(emodpy_tbhiv.demographics.TBHIVDemographics.TBHIVDemographic
method), 5
SetHIVTBCoInfectionMortalityDistribution()
(emodpy_tbhiv.demographics.TBHIVDemographics.TBHIVDemographic
method), 5
SmearDiagnostic() (in module
emodpy_tbhiv.interventions.smear_diag),
15
T
TBDrugTreatment() (in module
emodpy_tbhiv.interventions.tb_treat_basic), 16
TBHIVDemographics (class) in
emodpy_tbhiv.demographics.TBHIVDemographics,
5
TBHIVDrugTreatment() (in module
emodpy_tbhiv.interventions.tbhiv_treat),
17
TPVC() (in module emodpy_tbhiv.interventions.triggered_pvc),
18
```

V

Vaccine() (in module
emodpy_tbhiv.interventions.vaccine), 18