
emodpy-tbhiv

Institute for Disease Modeling

Jun 08, 2022

CONTENTS

- 1 emodpy-tbhiv installation 3**
 - 1.1 Prerequisites 3
 - 1.2 Installation instructions 3
- 2 API reference 5**
 - 2.1 emodpy_tbhiv package 5
 - 2.1.1 Subpackages 5
 - 2.1.2 Submodules 21
- 3 Frequently asked questions 23**
- Python Module Index 25**
- Index 27**

emodpy-tbhiv is a collection of Python scripts and utilities created to streamline user interactions with EMOD and idmtools for modeling measles. Much of the functionality is inherited from the [emod_api](#) package and [emodpy](#) package.

Additional information about how to use idmtools can be found at in [Welcome to idmtools](#). Additional information about EMOD TBHIV parameters for modeling tuberculosis can be found in [EMOD parameter reference](#).

See [Welcome to idmtools](#) for a diagram showing how idmtools and each of the related packages are used in an end-to-end workflow using EMOD as the disease transmission model.

EMODPY-TBHIV INSTALLATION

Follow the steps below to install emodpy-tbhiv.

1.1 Prerequisites

First, ensure the following prerequisites are met.

- Windows 10 Pro or Enterprise, Linux, or Mac
- Python 3.9 64-bit (<https://www.python.org/downloads/release>)
- A file that indicates the pip index-url:
 - Windows
 - Linux

In C:\Users\Username\pip\pip.ini, containing the following:

```
[global]
index-url = https://packages.idmod.org/api/pypi/pypi-production/simple
```

In \$HOME/.config/pip/pip.conf, containing the following:

```
[global]
index-url = https://packages.idmod.org/api/pypi/pypi-production/simple
```

1.2 Installation instructions

1. Open a command prompt and create a virtual environment in any directory you choose. The command below names the environment “v-emodpy-tbhiv”, but you may use any desired name:

```
python -m venv v-emodpy-tbhiv
```

2. Activate the virtual environment:

- Windows
- Linux

Enter the following:

```
v-emodpy-tbhiv\Scripts\activate
```

Enter the following:

```
source v-emodpy-tbhiv/bin/activate
```

3. Install emodpy-tbhiv packages:

```
pip install emodpy-tbhiv
```

If you are on Linux, also run:

```
pip install keyrings.alt
```

4. When you are finished, deactivate the virtual environment by entering the following at a command prompt:

```
deactivate
```


API REFERENCE

2.1 emodpy_tbhiv package

The emodpy-tbhiv module is intended to house scripts and tools that enable disease modelers to work more easily with the IDM EMOD TBHIV model.

2.1.1 Subpackages

emodpy_tbhiv.demographics package

Submodules

emodpy_tbhiv.demographics.TBHIVDemographics module

```
class emodpy_tbhiv.demographics.TBHIVDemographics.TBHIVDemographics(pop=None, nodes=None,  
                                                                    idref='Gridded world  
                                                                    grump2.5arcmin',  
                                                                    base_file=None)
```

Bases: `emod_api.demographics.Demographics.Demographics`

This class is derived from `emod_api.demographics.Demographics` class so that we can set certain defaults for TBHIV in construction. Keen observers will note that `SetDefaultProperties` does not look like a TBHIV-specific function. But as we add other disease types the generalizations and specifics will become clearer. The architectural point is solid.

SetHIVCoInfectionDistribution()

Insert some notion of a default HIVCoInfection distribution.

SetHIVTBCoInfectionMortalityDistribution()

Insert some notion of a default HIVTBCoInfection Mortality distribution.

```
emodpy_tbhiv.demographics.TBHIVDemographics.fromBasicNode(lat=0, lon=0, pop=1000000.0, name=1,  
                                                         forced_id=1, implicit_config_fns=None)
```

This function creates a single-node `TBHIVDemographics` instance from the params you give it.

```
emodpy_tbhiv.demographics.TBHIVDemographics.from_template_node(lat=0, lon=0, pop=1000000.0,  
                                                             name=1, forced_id=1)
```

Create a single-node `TBHIVDemographics` instance from the parameters you supply.

Parameters

- **lat** – Latitude of the centroid of the node to create.

- **lon** – Longitude of the centroid of the node to create.
- **pop** – Human population of the node.
- **name** – The name of the node. This may be a characteristic of the node, such as “rural” or “urban”, or an identifying integer.
- **forced_id** – The node ID for the single node.

Returns A *TBHIVDemographics* instance.

```
emodpy_tbhiv.demographics.TBHIVDemographics.fromData(pop=1000000.0, filename_male=None,  
                                                       filename_female=None)
```

```
emodpy_tbhiv.demographics.TBHIVDemographics.from_csv(pop_file, res=0.008333333333333333,  
                                                       id_ref='from_csv', filename_male=None,  
                                                       filename_female=None)
```

Create a multi-node *TBHIVDemographics* instance from a CSV file describing a population.

Parameters

- **pop_file** – The path to the csv file to ingest.
- **res** – Resolution.
- **id_ref** – A string to identify the file, needs to match other input files.
- **filename_male** – Path to male mortality csv.
- **filename_female** – Path to female mortality csv.

Returns A *TBHIVDemographics* instance

```
emodpy_tbhiv.demographics.TBHIVDemographics.from_params(tot_pop=1000000.0, num_nodes=100,  
                                                         frac_rural=0.3, id_ref='from_params',  
                                                         filename_male=None,  
                                                         filename_female=None)
```

Create a multi-node *TBHIVDemographics* instance as a synthetic population based on a few parameters.

Parameters

- **tot_pop** – The total human population in the node.
- **num_nodes** – The number of nodes to create.
- **frac_rural** – The fraction of the population that is rural.
- **id_ref** – Method describing how the latitude and longitude values are created for each of the nodes in a simulation. “Gridded world” values use a grid overlaid across the globe at some arcsec resolution. You may also generate the grid using another tool or coordinate system. For more information, see [Metadata](#).
- **filename_male** – Path to male mortality csv.
- **filename_female** – Path to female mortality csv.

Returns A *TBHIVDemographics* instance.

emodpy_tbhiv.interventions package

emodpy_tbhiv.interventions.purge_campaign_event(*camp_event*)

Submodules

emodpy_tbhiv.interventions.active_diagnostic module

```
emodpy_tbhiv.interventions.active_diagnostic.ActiveDiagnostic(camp, trigger_treatment_list,
    active_sensitivity=1.0,
    active_specificity=1.0,
    pos_event='TBTestPositive',
    treatment_fraction=1, start_day=1,
    duration=- 1,
    property_restrictions_list=[],
    nodeIDs=[], black_period=0,
    black_trigger='Blackout',
    event_name='TB Diagnosis Active Simple')
```

Create and return triggered campaign event that issues an ActiveDiagnostic intervention. See [ActiveDiagnostic](#)

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **active_sensitivity** – Sensitivity. Defaults to 1.0.
- **active_specificity** – Specificity. Defaults to 1.0.
- **pos_event** – Signal (or trigger) which is broadcast if the test is positive. Defaults to 'TBTest-Positive',
- **treatment_fraction** – Fraction of population testing positive you get the positive result effect.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.active_diagnostic.new_intervention_as_file(camp, start_day=1,
    filename=None)
```

emodpy_tbhiv.interventions.age_targeted_vaccine module

```
emodpy_tbhiv.interventions.age_targeted_vaccine.AgeTargetedVaccine(camp, trigger_treatment_list,  
                                                                    initial_efficacy=1.0,  
                                                                    vaccine_take=1,  
                                                                    vtype='AcquisitionBlocking',  
                                                                    coverage=1, age_min_yrs=0,  
                                                                    age_max_yrs=125,  
                                                                    box_duration_yrs=1,  
                                                                    immune_decay_yrs=0,  
                                                                    start_day=1, duration=- 1,  
                                                                    prop-  
                                                                    erty_restrictions_list=[],  
                                                                    nodeIDs=[],  
                                                                    black_period=0,  
                                                                    black_trigger='Blackout',  
                                                                    event_name='Vaccine')
```

Create and return triggered campaign event that issues a (generalized) Vaccine intervention. See [SimpleVaccine](#)

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **initial_efficacy** – Initial efficacy of the vaccine. Defaults to 1.0.
- **vaccine_take** – Fraction of the population receiving the vaccine for whom it is efficacious. Defaults to 1.0.
- **vtype** – ... Defaults to “AcquisitionBlocking”
- **age_min_yrs** – Lower age bound, in years. Defaults to 0.
- **age_max_yrs** – Upper age bound, in years. Defaults to 125.
- **box_duration_yrs** – Period of time over which the initial efficacy persists before decay. Defaults to 1 year.
- **immune_decay_yrs** – Period of time over which the efficacy decays to 0. Defaults to 0.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optional list of node ids to target. Defaults to all.
- **coverage** – Fraction of population to reach.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.age_targeted_vaccine.new_intervention_as_file(camp, file-  
                                                                    name='vaccine.json')
```

emodpy_tbhiv.interventions.art module

```
emodpy_tbhiv.interventions.art.ART(camp, trigger_treatment_list, start_day=1, duration=- 1,  
                                     property_restrictions_list=[], nodeIDs=[], black_period=0,  
                                     black_trigger='Blackout', event_name='ART')
```

Create and return triggered campaign event that issues an ART intervention.

Parameters

- **camp** – Centralized campaign module instance.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.art.new_intervention_as_file(camp, filename='art.json')
```

emodpy_tbhiv.interventions.bcg module

```
emodpy_tbhiv.interventions.bcg.BCG(camp, trigger_treatment_list, initial_efficacy=1.0, vaccine_take=1,  
                                     age_take_decay=1.0, box_duration_yrs=1, immune_decay_yrs=0,  
                                     start_day=1, duration=- 1, property_restrictions_list=[], nodeIDs=[],  
                                     black_period=0, black_trigger='Blackout', event_name='Vaccine  
                                     Health Seeking')
```

Create and return triggered campaign event that issues an BCG vaccine intervention.

Parameters

- **camp** – Centralized campaign module instance.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **initial_efficacy** – Initial efficacy of the vaccine. Defaults to 1.0.
- **vaccine_take** – Fraction of the population receiving the vaccine for whom it is efficacious. Defaults to 1.0.
- **age_take_decay** – ... Defaults to 1.0.
- **box_duration_yrs** – Period of time over which the initial efficacy persists before decay. Defaults to 1 year.
- **immune_decay_yrs** – Period of time over which the efficacy decays to 0. Defaults to 0.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.

- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

`emodpy_tbhiv.interventions.bcg.new_intervention_as_file(camp, filename=None)`

`emodpy_tbhiv.interventions.cd4diag` module

`emodpy_tbhiv.interventions.cd4diag.CD4Diag(camp, trigger_treatment_list, event_200='Below200', event_350='Below350', event_500='Below500', event_above_500='Above500', start_day=1, duration=- 1, property_restrictions_list=[], nodeIDs=[], black_period=0, black_trigger='Blackout', event_name='CD4 Diagnostic')`

Create and return triggered campaign event that issues an CD4Diagnostic intervention.

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **event_200** – ...
- **event_350** – ...
- **event_500** – ...
- **event_above_500** – ...
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

`emodpy_tbhiv.interventions.cd4diag.new_intervention_as_file(camp, filename='cd4.json')`

emodpy_tbhiv.interventions.diag_treat_neg module

```
emodpy_tbhiv.interventions.diag_treat_neg.DiagnosticTreatNeg(camp, trigger_treatment_list,
                                                             base_sensitivity_smearpos=1.0,
                                                             base_sensitivity_smearneg=1.0,
                                                             pos_event='TBTestPositive',
                                                             neg_event='TBTestNegative',
                                                             def_event='TBTestDefault',
                                                             treatment_fraction=1, start_day=1,
                                                             duration=- 1,
                                                             property_restrictions_list=[],
                                                             nodeIDs=[], black_period=0,
                                                             black_trigger='Blackout',
                                                             event_name='TB Diagnosis')
```

Create and return triggered campaign event that issues an DiagnosticTreatNeg intervention. See [DiagnosticTreatNeg](#)

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **base_sensitivity_smearpos** – Sensitivity. Defaults to 1.0.
- **base_sensitivity_smearneg** – Specificity. Defaults to 1.0.
- **pos_event** – Signal (or trigger) which is broadcast if the test is positive. Defaults to ‘TBTestPositive’,
- **neg_event** – Defaults to ‘TBTestNegative’.
- **def_event** – Defaults to ‘TBTestDefault’.
- **treatment_fraction** – Fraction of population testing positive you get the positive result effect.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.diag_treat_neg.new_intervention_as_file(camp, filename='dtn.json')
```

emodpy_tbhiv.interventions.drugs module

```
emodpy_tbhiv.interventions.drugs.add_tb_drug_type(config, drug_name, duration, cure_proportion,  
death_proportion, resistance_proportion,  
inactivation_proportion, relapse_proportion,  
reduced_transmit=1, reduced_acquire=1,  
cure_proportion_hiv=None,  
death_proportion_hiv=None,  
resistance_proportion_hiv=None,  
relapse_proportion_hiv=None,  
inactivation_proportion_hiv=None,  
mdr_cure_proportion=None,  
mdr_death_proportion=None,  
mdr_inactivation_proportion=None,  
mdr_relapse_proportion=None)
```

Add a drug definition to the simulation. This does not deliver the drug to anyone, and also doesn't mean we're going to use it. It's like putting it in the reference section.

emodpy_tbhiv.interventions.hiv_diag module

```
emodpy_tbhiv.interventions.hiv_diag.HIVDiagnostic(camp, trigger_treatment_list, base_sensitivity=1.0,  
base_specificity=1.0,  
pos_event='HIVTestedPositive',  
neg_event='HIVTestedNegative',  
treatment_fraction=1, start_day=1, duration=-1,  
property_restrictions_list=[], nodeIDs=[],  
black_period=0, black_trigger='Blackout',  
event_name='HIV Diagnostic')
```

Create and return triggered campaign event that issues an HIVSimpleDiagnostic intervention. See [HIVSimpleDiagnostic](#)

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **base_sensitivity** – Sensitivity. Defaults to 1.0.
- **base_specificity** – Specificity. Defaults to 1.0.
- **pos_event** – Signal (or trigger) which is broadcast if the test is positive. Defaults to 'HIVTestedPositive'.
- **neg_event** – Signal (or trigger) which is broadcast if the test is negative. Defaults to 'HIVTestedNegative'.
- **treatment_fraction** – Fraction of population testing positive you get the positive result effect.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.

- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

`emodpy_tbhiv.interventions.hiv_diag.new_intervention_as_file(camp, filename=None)`

emodpy_tbhiv.interventions.hiv_seeding module

`emodpy_tbhiv.interventions.hiv_seeding.seed(camp, disease='TB', coverage=0.01, reps=- 1, interval=1, start_day=1, nodeIDs=[], time_offset=1, event_name='HIV Incidence')`

Create a scheduled campaign event that issues an OutbreakIndividualTBorHIV intervention. Useful for seeding interventions in TBHIV_SIM.

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **disease** – “TB” or “HIV”. Default is “TB” (used to be “HIV”).
- **coverage** – Percentage of otherwise qualifying individuals who will be infected.
- **reps** – Number of repetitions (integer). Defaults to no repetition.
- **interval** – Timesteps between repetitions, if reps is set. Defaults to every day.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **time_offset** – ... Defaults to 1.
- **event_name** – Not used.

Returns New campaign event that can be added to the campaign.

`emodpy_tbhiv.interventions.hiv_seeding.new_intervention_as_file(camp, filename='hiv.json')`

emodpy_tbhiv.interventions.hsb module

`emodpy_tbhiv.interventions.hsb.HSB(camp, trigger_treatment_list, output_event, probability_per_step=1.0, start_day=1, duration=- 1, property_restrictions_list=[], nodeIDs=[], event_name='HSB', prevent_duplicates=False, fixed_initial_delay=0)`

Create and return triggered campaign event that issues an SimpleHealthSeekingBehavior intervention. See [SimpleHealthSeekingBehavior](#)

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **output_event** – Signal to broadcast when ‘health’ is ultimately sought (string).

- **probability_per_step** – Probability of seeking per timestep, default to 1 which means near instantaneous.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optional list of node ids to target. Defaults to all.
- **prevent_duplicates** – If an individual were to get one of these when they already have one, the default behaviour is to proceed additively. Use this param to cause the new one to replace the old one. Same-ness is based on same event_name.
- **fixed_initial_delay** – Optional param that lets us add a fixed delay before the HSB.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.hsb.new_intervention_as_file(camp, filename='hsb_diag.json')
```

emodpy_tbhiv.interventions.peek_camp module

```
emodpy_tbhiv.interventions.peek_camp.decorate_actual_iv_impl(iv, signal=None)
```

```
emodpy_tbhiv.interventions.peek_camp.decorate_actual_iv(iv, signal=None)
```

emodpy_tbhiv.interventions.ramp_dtn module

```
emodpy_tbhiv.interventions.ramp_dtn.RampDTN(camp, trigger_treatment_list, ramp_time=30,
base_sensitivity_smearpos=1.0,
base_sensitivity_smeareg=1.0,
base_sensitivity_smearpos2=1.0,
base_sensitivity_smeareg2=1.0, treatment_fraction=1.0,
treatment_fraction2=1.0, pos_event='TBTestPositive',
neg_event='TBTestNegative',
defaulters_event='TBTestDefault',
pos_event2='TBTestPositive',
neg_event2='TBTestNegative',
defaulters_event2='TBTestDefault', start_day=1,
duration=- 1, property_restrictions_list=[], nodeIDs=[],
black_period=0, black_trigger='Blackout',
event_name='RampDTN')
```

Create and return triggered campaign event that (TBD).

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **active_sensitivity** – Sensitivity. Defaults to 1.0.
- **active_specificity** – Specificity. Defaults to 1.0.

- **pos_event** – Signal (or trigger) which is broadcast if the test is positive. Defaults to ‘TBTest-Positive’,
- **treatment_fraction** – Fraction of population testing positive you get the positive result effect.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.ramp_dtn.new_intervention_as_file(camp, filename='ramp.json')
```

emodpy_tbhiv.interventions.resist_diag module

```
emodpy_tbhiv.interventions.resist_diag.ResistanceDiagnostic(camp, trigger_treatment_list,
                                                             sensitivity=1.0, specificity=1.0,
                                                             pos_event='TBMDRTestPositive',
                                                             neg_event='TBMDRTestNegative',
                                                             def_event='TBMDRTestDefault',
                                                             treatment_fraction=1,
                                                             treatment_fraction_negative_test=1,
                                                             start_day=1, duration=- 1,
                                                             property_restrictions_list=[],
                                                             nodeIDs=[], black_period=0,
                                                             black_trigger='Blackout',
                                                             event_name='TB Diagnosis MDR')
```

Create and return triggered campaign event that issues an ResistanceDiagnostic intervention.

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **sensitivity** – Sensitivity. Defaults to 1.0.
- **specificity** – Specificity. Defaults to 1.0.
- **pos_event** – Signal (or trigger) which is broadcast if the test is positive. Defaults to ‘TB-MDRTestPositive’.
- **neg_event** – Signal (or trigger) which is broadcast if the test is negative. Defaults to ‘TB-MDRTestNegative’.
- **def_event** – Signal (or trigger) which is broadcast if the test is default. Defaults to ‘TB-MDRTestDefault’.

- **treatment_fraction** – Fraction of population testing positive you get the positive result effect. Defaults to 1.
- **treatment_fraction_negative_test** – ... Defaults to 1.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.resist_diag.new_intervention_as_file(camp,  
                                                                filename='resist_diag.json')
```

emodpy_tbhiv.interventions.smear_diag module

```
emodpy_tbhiv.interventions.smear_diag.SmearDiagnostic(camp, trigger_treatment_list,  
                                                       base_sensitivity_smearpos=1.0,  
                                                       base_sensitivity_smearneg=1.0,  
                                                       pos_event='TestPositiveOnSmear',  
                                                       treatment_fraction=1, start_day=1,  
                                                       duration=- 1, property_restrictions_list=[],  
                                                       nodeIDs=[], black_period=0,  
                                                       black_trigger='Blackout', event_name='TB  
Diagnosis Smear Simple')
```

Create and return triggered campaign event that issues an SmearDiagnostic intervention.

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **base_sensitivity_smearpos** – Sensitivity. Defaults to 1.0.
- **base_sensitivity_smearneg** – Specificity. Defaults to 1.0.
- **pos_event** – Signal (or trigger) which is broadcast if the test is positive. Defaults to ‘TBTest-PositiveOnSmear’.
- **treatment_fraction** – Fraction of population testing positive you get the positive result effect.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.

- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.smear_diag.new_intervention_as_file(camp,
                                                             filename='smear_diag.json')
```

emodpy_tbhiv.interventions.tb_treat_basic module

```
emodpy_tbhiv.interventions.tb_treat_basic.TBDrugTreatment(camp, trigger_treatment_list,
                                                           drug_name='DOTS',
                                                           inactivation_rate=0, mortality_rate=0,
                                                           clearance_rate=0, resistance_rate=0,
                                                           relapse_rate=0, reduced_transmit=1.0,
                                                           start_day=1, treatment_duration=180,
                                                           duration=- 1,
                                                           property_restrictions_list=[],
                                                           nodeIDs=[], black_period=0,
                                                           black_trigger='Blackout',
                                                           event_name='TBDrugTreatment')
```

Create and return triggered campaign event that issues an AntiTBDrug intervention. See [AntiTBDrug](#)

Parameters

- **camp** – The [emod_api.campaign](#) module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **drug_name** – ... Defaults to 'DOTS',
- **inactivation_rate** – ... Defaults to 0,
- **mortality_rate** – ... Defaults to 0,
- **clearance_rate** – ... Defaults to 0,
- **resistance_rate** – ... Defaults to 0,
- **relapse_rate** – ... Defaults to 0,
- **reduced_transmit** – ... Defaults to 1.0,
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

`emodpy_tbhiv.interventions.tb_treat_basic.new_intervention_as_file(camp, filename=None)`

`emodpy_tbhiv.interventions.tbhiv_treat` module

`emodpy_tbhiv.interventions.tbhiv_treat.TBHIVDrugTreatment(camp, trigger_treatment_list, drug_name, latent_multiplier=1.0, active_multiplier=1.0, start_day=1, duration=-1, property_restrictions_list=[], nodeIDs=[], black_period=0, black_trigger='Blackout', event_name='TBHIVDrugTreatment')`

Create and return triggered campaign event that issues a ‘TBHIVConfigurableTBdrug’ intervention. See [TBHIVConfigurableTBdrug](#)

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **drug_name** – ...
- **latent_multiplier** – ... Defaults to 1.0.
- **active_multiplier** – ... Defaults to 1.0.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optiona list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

`emodpy_tbhiv.interventions.tbhiv_treat.new_intervention_as_file(camp, filename='tb_drug_treat.json')`

emodpy_tbhiv.interventions.triggered_pvc module

`emodpy_tbhiv.interventions.triggered_pvc.TPVC(camp, trigger_treatment_list, property_to_change, final_prop_value, revert=0, daily_prob=1, start_day=1, duration=-1, property_restrictions_list=[], nodeIDs=[], black_period=0, black_trigger='Blackout', event_name='PropertyValueChanger')`

Create and return triggered campaign event that issues an PropertyValueChanger intervention. See [PropertyValueChanger](#)

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.
- **property_to_change** – Individual Property key (string).
- **final_prop_value** – New Individual Property value (string).
- **revert** – ... Defaults to 0.
- **daily_prob** – Daily probability of changing. Defaults to 1.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optional list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

`emodpy_tbhiv.interventions.triggered_pvc.new_intervention_as_file(camp, filename='tpvc.json')`

emodpy_tbhiv.interventions.vaccine module

`emodpy_tbhiv.interventions.vaccine.Vaccine(camp, trigger_treatment_list, initial_efficacy=1.0, vaccine_take=1, vtype='AcquisitionBlocking', box_duration_yrs=1, immune_decay_yrs=10, start_day=1, duration=-1, property_restrictions_list=[], nodeIDs=[], black_period=0, black_trigger='Blackout', event_name='Vaccine')`

Create and return triggered campaign event that issues a (generalized) Vaccine intervention. See [SimpleVaccine](#)

Parameters

- **camp** – The `emod_api.campaign` module instance which serves as the campaign accumulator.
- **trigger_treatment_list** – List of 1 or more triggers (or events or signals) which are listened to and trigger the distribution of the intervention. There is no default.

- **initial_efficacy** – Initial efficacy of the vaccine. Defaults to 1.0.
- **vaccine_take** – Fraction of the population receiving the vaccine for whom it is efficacious. Defaults to 1.0.
- **vtype** – ... Defaults to “AcquisitionBlocking”
- **box_duration_yrs** – Period of time over which the initial efficacy persists before decay. Defaults to 1 year.
- **immune_decay_yrs** – Period of time over which the efficacy decays to 0. Defaults to 10 years.
- **start_day** – The timestep when this campaign event takes effect. Defaults to 1.
- **duration** – How long the campaign event remains in effect. Defaults to forever.
- **property_restrictions_list** – Optional list of Individual Properties to limit the intervention to.
- **nodeIDs** – Optional list of node ids to target. Defaults to all.
- **black_period** – Undocumented.
- **black_trigger** – Undocumented.
- **event_name** – Undocumented.

Returns New campaign event that can be added to the campaign.

```
emodpy_tbhiv.interventions.vaccine.new_intervention_as_file(camp, filename='vaccine.json')
```

emodpy_tbhiv.reporters package

Submodules

emodpy_tbhiv.reporters.plugin module

```
class emodpy_tbhiv.reporters.plugin.Report_TBHIV_ByAge(name: str = 'Report_TBHIV_ByAge',
                                                         Enabled: bool = True, Reports: list =
                                                         <factory>, dll_file: str =
                                                         'libreport_TBHIV_ByAge.dll')
```

Bases: `emodpy.reporters.base.CustomReporter`

name: `str` = 'Report_TBHIV_ByAge'

dll_file: `str` = 'libreport_TBHIV_ByAge.dll'

configure_report(*camp, max_age_yrs, min_age_yrs, start_year, stop_year, events=None*)

2.1.2 Submodules

`emodpy_tbhiv.standard_drugs` module

`emodpy_tbhiv.standard_drugs.bootstrap`(*config*)

FREQUENTLY ASKED QUESTIONS

As you get started with `emodpy-tbhiv`, you may have questions. The most common questions will be added below. For questions related to functionality in related packages, see the following documentation:

- [Frequently asked questions](#) for EMOD
- [Frequently asked questions](#) for `idmtools`
- [Frequently asked questions](#) for `emod-api`
- [Frequently asked questions](#) for `emodpy`

PYTHON MODULE INDEX

e

- `emodpy_tbhiv`, 5
- `emodpy_tbhiv.demographics`, 5
- `emodpy_tbhiv.demographics.TBHIVDemographics`, 5
- `emodpy_tbhiv.interventions`, 7
- `emodpy_tbhiv.interventions.active_diagnostic`, 7
- `emodpy_tbhiv.interventions.age_targeted_vaccine`, 8
- `emodpy_tbhiv.interventions.art`, 9
- `emodpy_tbhiv.interventions.bcg`, 9
- `emodpy_tbhiv.interventions.cd4diag`, 10
- `emodpy_tbhiv.interventions.diag_treat_neg`, 11
- `emodpy_tbhiv.interventions.drugs`, 12
- `emodpy_tbhiv.interventions.hiv_diag`, 12
- `emodpy_tbhiv.interventions.hiv_seeding`, 13
- `emodpy_tbhiv.interventions.hsb`, 13
- `emodpy_tbhiv.interventions.peek_camp`, 14
- `emodpy_tbhiv.interventions.ramp_dtn`, 14
- `emodpy_tbhiv.interventions.resist_diag`, 15
- `emodpy_tbhiv.interventions.smear_diag`, 16
- `emodpy_tbhiv.interventions.tb_treat_basic`, 17
- `emodpy_tbhiv.interventions.tbhiv_treat`, 18
- `emodpy_tbhiv.interventions.triggered_pvc`, 19
- `emodpy_tbhiv.interventions.vaccine`, 19
- `emodpy_tbhiv.reporters`, 20
- `emodpy_tbhiv.reporters.plugin`, 20
- `emodpy_tbhiv.standard_drugs`, 21

INDEX

A

ActiveDiagnostic() (in module
emodpy_tbhiv.interventions.active_diagnostic),
7
add_tb_drug_type() (in module
emodpy_tbhiv.interventions.drugs), 12
AgeTargetedVaccine() (in module
emodpy_tbhiv.interventions.age_targeted_vaccine),
8
ART() (in module emodpy_tbhiv.interventions.art), 9

B

BCG() (in module emodpy_tbhiv.interventions.bcg), 9
bootstrap() (in module
emodpy_tbhiv.standard_drugs), 21

C

CD4Diag() (in module
emodpy_tbhiv.interventions.cd4diag), 10
configure_report() (emodpy_tbhiv.reporters.plugin.Report_TBHIV_ByAge
method), 20

D

decorate_actual_iv() (in module
emodpy_tbhiv.interventions.peek_camp),
14
decorate_actual_iv_impl() (in module
emodpy_tbhiv.interventions.peek_camp),
14
DiagnosticTreatNeg() (in module
emodpy_tbhiv.interventions.diag_treat_neg),
11
dll_file(emodpy_tbhiv.reporters.plugin.Report_TBHIV_ByAge
attribute), 20

E

emodpy_tbhiv
module, 5
emodpy_tbhiv.demographics
module, 5
emodpy_tbhiv.demographics.TBHIVDemographics

module, 5
emodpy_tbhiv.interventions
module, 7
emodpy_tbhiv.interventions.active_diagnostic
module, 7
emodpy_tbhiv.interventions.age_targeted_vaccine
module, 8
emodpy_tbhiv.interventions.art
module, 9
emodpy_tbhiv.interventions.bcg
module, 9
emodpy_tbhiv.interventions.cd4diag
module, 10
emodpy_tbhiv.interventions.diag_treat_neg
module, 11
emodpy_tbhiv.interventions.drugs
module, 12
emodpy_tbhiv.interventions.hiv_diag
module, 12
emodpy_tbhiv.interventions.hiv_seeding
module, 13
emodpy_tbhiv.interventions.hsb
module, 13
emodpy_tbhiv.interventions.peek_camp
module, 14
emodpy_tbhiv.interventions.ramp_dtn
module, 14
emodpy_tbhiv.interventions.resist_diag
module, 15
emodpy_tbhiv.interventions.smear_diag
module, 16
emodpy_tbhiv.interventions.tb_treat_basic
module, 17
emodpy_tbhiv.interventions.tbhiv_treat
module, 18
emodpy_tbhiv.interventions.triggered_pvc
module, 19
emodpy_tbhiv.interventions.vaccine
module, 19
emodpy_tbhiv.reporters
module, 20
emodpy_tbhiv.reporters.plugin

```

    module, 20
emodpy_tbhiv.standard_drugs
    module, 21
F
from_csv() (in module
    emodpy_tbhiv.demographics.TBHIVDemographics),
6
from_params() (in module
    emodpy_tbhiv.demographics.TBHIVDemographics),
6
from_template_node() (in module
    emodpy_tbhiv.demographics.TBHIVDemographics),
5
fromBasicNode() (in module
    emodpy_tbhiv.demographics.TBHIVDemographics),
5
fromData() (in module
    emodpy_tbhiv.demographics.TBHIVDemographics),
6
H
HIVDiagnostic() (in module
    emodpy_tbhiv.interventions.hiv_diag), 12
HSB() (in module emodpy_tbhiv.interventions.hsb), 13
M
module
    emodpy_tbhiv, 5
    emodpy_tbhiv.demographics, 5
    emodpy_tbhiv.demographics.TBHIVDemographics,
    5
    emodpy_tbhiv.interventions, 7
    emodpy_tbhiv.interventions.active_diagnostic,
    7
    emodpy_tbhiv.interventions.age_targeted_vaccine,
    8
    emodpy_tbhiv.interventions.art, 9
    emodpy_tbhiv.interventions.bcg, 9
    emodpy_tbhiv.interventions.cd4diag, 10
    emodpy_tbhiv.interventions.diag_treat_neg,
    11
    emodpy_tbhiv.interventions.drugs, 12
    emodpy_tbhiv.interventions.hiv_diag, 12
    emodpy_tbhiv.interventions.hiv_seeding,
    13
    emodpy_tbhiv.interventions.hsb, 13
    emodpy_tbhiv.interventions.peek_camp, 14
    emodpy_tbhiv.interventions.ramp_dtn, 14
    emodpy_tbhiv.interventions.resist_diag,
    15
    emodpy_tbhiv.interventions.smear_diag, 16
    emodpy_tbhiv.interventions.tb_treat_basic,
    17
    emodpy_tbhiv.interventions.tbhiv_treat,
    18
    emodpy_tbhiv.interventions.triggered_pvc,
    19
    emodpy_tbhiv.interventions.vaccine, 19
    emodpy_tbhiv.reporters, 20
    emodpy_tbhiv.reporters.plugin, 20
    emodpy_tbhiv.standard_drugs, 21
    name (emodpy_tbhiv.reporters.plugin.Report_TBHIV_ByAge
    attribute), 20
    new_intervention_as_file() (in module
    emodpy_tbhiv.interventions.active_diagnostic),
    7
    new_intervention_as_file() (in module
    emodpy_tbhiv.interventions.age_targeted_vaccine),
    8
    new_intervention_as_file() (in module
    emodpy_tbhiv.interventions.art), 9
    new_intervention_as_file() (in module
    emodpy_tbhiv.interventions.bcg), 10
    new_intervention_as_file() (in module
    emodpy_tbhiv.interventions.cd4diag), 10
    new_intervention_as_file() (in module
    emodpy_tbhiv.interventions.diag_treat_neg),
    11
    new_intervention_as_file() (in module
    emodpy_tbhiv.interventions.hiv_diag), 13
    new_intervention_as_file() (in module
    emodpy_tbhiv.interventions.hiv_seeding),
    13
    new_intervention_as_file() (in module
    emodpy_tbhiv.interventions.hsb), 14
    new_intervention_as_file() (in module
    emodpy_tbhiv.interventions.ramp_dtn), 15
    new_intervention_as_file() (in module
    emodpy_tbhiv.interventions.resist_diag),
    16
    new_intervention_as_file() (in module
    emodpy_tbhiv.interventions.tb_treat_basic), 18
    new_intervention_as_file() (in module
    emodpy_tbhiv.interventions.tbhiv_treat),
    18
    new_intervention_as_file() (in module
    emodpy_tbhiv.interventions.triggered_pvc),
    19
    new_intervention_as_file() (in module
    emodpy_tbhiv.interventions.vaccine), 20

```


P

`purge_campaign_event()` (in module `emodpy_tbhiv.interventions`), 7

R

`RampDTN()` (in module `emodpy_tbhiv.interventions.ramp_dtn`), 14

`Report_TBHIV_ByAge` (class in `emodpy_tbhiv.reporters.plugin`), 20

`ResistanceDiagnostic()` (in module `emodpy_tbhiv.interventions.resist_diag`), 15

S

`seed()` (in module `emodpy_tbhiv.interventions.hiv_seeding`), 13

`SetHIVCoInfectionDistribution()` (`emodpy_tbhiv.demographics.TBHIVDemographics.TBHIVDemographics` method), 5

`SetHIVTBCoInfectionMortalityDistribution()` (`emodpy_tbhiv.demographics.TBHIVDemographics.TBHIVDemographics` method), 5

`SmearDiagnostic()` (in module `emodpy_tbhiv.interventions.smear_diag`), 16

T

`TBDrugTreatment()` (in module `emodpy_tbhiv.interventions.tb_treat_basic`), 17

`TBHIVDemographics` (class in `emodpy_tbhiv.demographics.TBHIVDemographics`), 5

`TBHIVDrugTreatment()` (in module `emodpy_tbhiv.interventions.tbhiv_treat`), 18

`TPVC()` (in module `emodpy_tbhiv.interventions.triggered_pvc`), 19

V

`Vaccine()` (in module `emodpy_tbhiv.interventions.vaccine`), 19