

---

**emodpy**

**Institute for Disease Modeling**

**Feb 09, 2021**



# CONTENTS

<b>1 Installation</b>	<b>3</b>
1.1 Prerequisites . . . . .	3
1.1.1 Basic installation . . . . .	3
1.1.2 Developer installation . . . . .	4
<b>2 Create simulations</b>	<b>7</b>
<b>3 Create input files</b>	<b>9</b>
<b>4 Run simulations</b>	<b>11</b>
<b>5 Calibrate simulations</b>	<b>13</b>
<b>6 Parameter sweeps and model iteration</b>	<b>15</b>
6.1 Parameter sweeps for model calibration . . . . .	15
6.2 Parameter sweeps and stochasticity . . . . .	15
6.3 How to do parameter sweeps . . . . .	15
<b>7 Introduction to analyzers</b>	<b>17</b>
<b>8 Output reports</b>	<b>19</b>
<b>9 Serialization</b>	<b>21</b>
<b>10 emodpy</b>	<b>23</b>
10.1 emodpy package . . . . .	23
10.1.1 Subpackages . . . . .	23
10.1.2 Submodules . . . . .	32
<b>11 Glossary</b>	<b>51</b>
<b>12 Changelog</b>	<b>53</b>
12.1 1.1.0 . . . . .	53
12.1.1 Additional Changes . . . . .	53
12.1.2 Bugs . . . . .	53
12.1.3 Developer/Test . . . . .	54
12.1.4 Documentation . . . . .	54
12.1.5 Feature Request . . . . .	54
12.1.6 Models . . . . .	54
12.1.7 Platforms . . . . .	54
12.1.8 User Experience . . . . .	54
12.2 1.2.0 . . . . .	55

12.2.1	Additional Changes . . . . .	55
12.2.2	Bugs . . . . .	55
12.2.3	Documentation . . . . .	55
12.2.4	Feature Request . . . . .	55
12.2.5	User Experience . . . . .	55

<b>Python Module Index</b>	<b>57</b>
----------------------------	-----------

<b>Index</b>	<b>59</b>
--------------	-----------

emodpy is a collection of Python scripts and utilities created to streamline user interactions with EMOD and idmtools.



## INSTALLATION

You can install emodpy in two different ways. If you intend to use emodpy as IDM builds it, follow the instructions in *Basic installation*. However, if you intend to modify the emodpy source code to add new functionality, follow the instructions in *Developer installation*. Whichever installation method you choose, the prerequisites are the same.

### 1.1 Prerequisites

- Windows 10 Pro or Enterprise
- Python 3.6 or 3.7 64-bit (<https://www.python.org/downloads/release>)

**Warning:** Do not install Python 3.8, which includes breaking changes.

- Python virtual environments

Python virtual environments enable you to isolate your Python environments from one another and give you the option to run multiple versions of Python on the same computer. When using a virtual environment, you can indicate the version of Python you want to use and the packages you want to install, which will remain separate from other Python environments. You may use `virtualenv`, which requires a separate installation, but `venv` is recommended and included with Python 3.3+.

#### 1.1.1 Basic installation

Follow the steps below if you will use idmtools to run and analyze simulations, but will not make source code changes.

1. Open a command prompt and create a virtual environment in any directory you choose. The command below names the environment “emodpy”, but you may use any desired name:

```
python -m venv emodpy
```

2. Activate the virtual environment:

- On Windows, enter the following:

```
emodpy\Scripts\activate
```

- On Linux, enter the following:

```
source emodpy/bin/activate
```

3. Install idmtools packages:

```
pip install emodpy --index-url=https://packages.idmod.org/api/pypi/pypi-  
→production/simple
```

If you are on Python 3.6, also run:

```
pip install dataclasses
```

4. Verify installation by pulling up idmtools help:

```
emodpy --help
```

5. When you are finished, deactivate the virtual environment by entering the following at a command prompt:

```
deactivate
```

### 1.1.2 Developer installation

Follow the steps below if you will make changes to the idmtools source code to add new functionality.

#### Install idmtools

1. Install a Git client such as Git Bash or the Git GUI.
2. Open a command prompt and clone the idmtools GitHub repository to a local directory using the following command:

```
git clone https://github.com/InstituteforDiseaseModeling/emodpy-idmtools.git
```

To work **from the** latest approved code, work **from the "master"** branch. To work **from the** latest code under active development, work **from the "dev"** branch.

3. Open a command prompt and create a virtual environment in any directory you choose. The command below names the environment “emodpy”, but you may use any desired name:

```
python -m venv emodpy
```

4. Activate the virtual environment:

- On Windows, enter the following:

```
emodpy\Scripts\activate
```

- On Linux, enter the following:

```
source emodpy/bin/activate
```

5. In the base directory of the cloned GitHub repository, run the setup script.

- On Windows, enter the following:

```
pip install py-make  
pymake setup-dev
```

- On Linux, enter the following:

```
make setup-dev
```

6. To verify that idmtools is installed, enter the following command:

```
emodpy --help
```

You should see a list of available cookie cutter projects and command-line options.

## Run tests

If you want to run tests on the code, do the following. You can add new tests to the GitHub repository and they will be run using the same commands. Note that COMPS access is generally restricted to IDM employees.

1. Login to COMPS by navigating to the idmtools root directory and entering the following at a command prompt:

```
python dev_scripts\create_auth_token_args.py --comps_url https://comps2.idmod.org  
--username yourcomps_user --password yourcomps_password
```

2. If you are running the local platform with the nightly idmtools build, enter the following to log in to Docker:

```
docker login idm-docker-staging.packages.idmod.org
```

3. Navigate to the directory containing the code you want to test, such as the root directory or a subdirectory like emodpy\_platform\_comps, enter the following command:

```
pymake test-all
```



---

**CHAPTER  
TWO**

---

**CREATE SIMULATIONS**



---

CHAPTER  
**THREE**

---

## **CREATE INPUT FILES**



---

**CHAPTER  
FOUR**

---

**RUN SIMULATIONS**



---

**CHAPTER  
FIVE**

---

**CALIBRATE SIMULATIONS**



## PARAMETER SWEEPS AND MODEL ITERATION

### Contents

- *Parameter sweeps for model calibration*
- *Parameter sweeps and stochasticity*
- *How to do parameter sweeps*

### 6.1 Parameter sweeps for model calibration

(more info) For more information on model calibration, see [Calibrate simulations](#).

### 6.2 Parameter sweeps and stochasticity

With a stochastic model (such as EMOD), it is especially important to utilize parameter sweeps, not only for calibration to data or parameter selection, but to fully explore the stochasticity in output. Single model runs may appear to provide good fits to data, but variation will arise and multiple runs are necessary to determine the appropriate range of parameter values necessary to achieve desired outcomes. Multiple iterations of a single set of parameter values should be run to determine trends in simulation output: a single simulation output could provide results that are due to random chance.

### 6.3 How to do parameter sweeps



---

CHAPTER  
**SEVEN**

---

## **INTRODUCTION TO ANALYZERS**



---

**CHAPTER  
EIGHT**

---

**OUTPUT REPORTS**



---

**CHAPTER  
NINE**

---

**SERIALIZATION**



# EMODPY

## 10.1 emodpy package

### 10.1.1 Subpackages

#### emodpy.analyzers package

##### Submodules

#### emodpy.analyzers.adult\_vectors\_analyzer module

**class** emodpy.analyzers.adult\_vectors\_analyzer.**AdultVectorsAnalyzer** (*name='hi'*)

Bases: idmtools.entities.i analyzer.IAnalyzer

**initialize()**

Call once after the analyzer has been added to the AnalyzeManager.

Add everything depending on the working directory or unique ID here instead of in `__init__`.

**map** (*data: Any, item: idmtools.core.interfaces.IItem*) → *Any*

In parallel for each simulation, consume raw data from filenames and emit selected data.

##### Parameters

- **data** – A dictionary associating filename with content for simulation data.
- **item** – IItem object that the passed data is associated with.

**Returns** Selected data for the given item.

**reduce** (*all\_data: dict*) → *Any*

Combine the `map()` data for a set of items into an aggregate result.

**Parameters** **all\_data** – A dictionary with entries for the item ID and selected data.

**emodpy.analyzers.population\_analyzer module**

```
class emodpy.analyzers.population_analyzer.PopulationAnalyzer(name='idm')
    Bases: idmtools.entities.ianalyzer.IAnalyzer
```

**initialize()**

Call once after the analyzer has been added to the AnalyzeManager.

Add everything depending on the working directory or unique ID here instead of in `__init__`.

**map (data: Any, item: idmtools.core.interfaces.IItem) → Any**

In parallel for each simulation, consume raw data from filenames and emit selected data.

**Parameters**

- **data** – A dictionary associating filename with content for simulation data.
- **item** – IItem object that the passed data is associated with.

**Returns** Selected data for the given item.

**reduce (all\_data: dict) → Any**

Combine the `map ()` data for a set of items into an aggregate result.

**Parameters** **all\_data** – A dictionary with entries for the item ID and selected data.

**emodpy.analyzers.timeseries\_analyzer module**

```
class emodpy.analyzers.timeseries_analyzer.TimeseriesAnalyzer(filenames=['output/InsetChart.json'],
                                                               chan-
                                                               nels=('Statistical
                                                               Population',
                                                               'Infectious
                                                               Population',
                                                               'Infected', 'Wan-
                                                               ing Population'),
                                                               save_output=True)
```

Bases: idmtools.entities.ianalyzer.IAnalyzer

```
data_group_names = ['group', 'sim_id', 'channel']
```

```
ordered_levels = ['channel', 'group', 'sim_id']
```

```
output_file = 'timeseries.csv'
```

**initialize()**

Call once after the analyzer has been added to the AnalyzeManager.

Add everything depending on the working directory or unique ID here instead of in `__init__`.

```
default_select_fn(ts)
```

```
default_group_fn(k, v)
```

```
default_plot_fn(df, ax)
```

```
default_filter_fn(md)
```

**filter (simulation)**

Decide whether the analyzer should process a simulation.

**Parameters** **item** – An IItem to be considered for processing with this analyzer.

**Returns** A Boolean indicating whether simulation should be analyzed by this analyzer.

**get\_channel\_data** (*data\_by\_channel*, *selected\_channels*)

**map** (*data*, *simulation*)

In parallel for each simulation, consume raw data from filenames and emit selected data.

#### Parameters

- **data** – A dictionary associating filename with content for simulation data.
- **item** – Item object that the passed data is associated with.

**Returns** Selected data for the given item.

**plot\_by\_channel** (*channels*, *plot\_fn*)

**reduce** (*all\_data*)

Combine the [map \(\)](#) data for a set of items into an aggregate result.

**Parameters** **all\_data** – A dictionary with entries for the item ID and selected data.

## emodpy.defaults package

### Subpackages

#### emodpy.defaults.ep4 package

##### Submodules

###### emodpy.defaults.ep4.dtk\_in\_process module

`emodpy.defaults.ep4.dtk_in_process.application(timestep)`

###### emodpy.defaults.ep4.dtk\_post\_process module

`emodpy.defaults.ep4.dtk_post_process.application(output_path)`

###### emodpy.defaults.ep4.dtk\_pre\_process module

`emodpy.defaults.ep4.dtk_pre_process.convert_plugin_reports(config_json)`

`emodpy.defaults.ep4.dtk_pre_process.application(json_config_path)`

##### Submodules

###### emodpy.defaults.emod\_sir module

**class** `emodpy.defaults.emod_sir.EMODSir`

Bases: `emodpy.defaults.iemod_default.IEMODDefault`

**static config** (*erad\_path*) → Dict

**static campaign** () → `emodpy.emod_campaign.EMODCampaign`

```
static demographics() → Dict
```

## emodpy.defaults.iemod\_default module

```
class emodpy.defaults.iemod_default.IEMODDefault
    Bases: object

    config(erad_path) → Dict
    campaign() → Dict
    demographics() → Dict
    process_simulation(simulation)
```

## emodpy.generic package

### Submodules

#### emodpy.generic.serialization module

```
emodpy.generic.serialization.enable_serialization(task:
                                                    emodpy.emod_task.EMODTask,
                                                    use_absolute_times: bool = False)
Enable serialization either by TIME or Timestep based on use_absolute_times :param task: Task to enable
:param use_absolute_times: When true, Serialization_Type will be set to TIME, otherwise it will be set to :param
*Timestep*:
```

Returns:

```
emodpy.generic.serialization.add_serialization_timesteps(task:
                                                       emodpy.emod_task.EMODTask,
                                                       timesteps:      List[int],
                                                       end_at_final:
                                                       bool           =      False,
                                                       use_absolute_times:
                                                       bool = False)
```

Serialize the population of this simulation at specified time steps.

If the simulation is run on multiple cores, multiple files will be created.

#### Parameters

- **task** (`EMODTask`) – An EMODSimulation
- **timesteps** (`List[int]`) – Array of integers representing the time steps to use
- **end\_at\_final** (`bool`) – False means set the simulation duration such that the last serialized\_population file ends the simulation. NOTE- may not work if time step size is not 1
- **use\_absolute\_times** (`bool`) – False means the method will define simulation times instead of time steps see documentation on *Serialization\_Type* for details

**Returns** None

---

```
emodpy.generic.serialization.load_serialized_population(task:
                                                       emodpy.emod_task.EMODTask,
                                                       population_path: str,
                                                       population_filenames:
                                                       List[str])
```

Sets simulation to load a serialized population from the filesystem

#### Parameters

- **task** ([EMODTask](#)) – An EMODSimulation
- **population\_path** (*str*) – relative path from the working directory to the location of the serialized population files.
- **population\_filenames** (*List[str]*) – names of files in question

#### Returns

**None**

## emodpy.interventions package

### Submodules

#### emodpy.interventions.emod\_empty\_campaign module

```
class emodpy.interventions.emod_empty_campaign.EMODEEmptyCampaign
Bases: emodpy.defaults.iemod_default.IEMODDefault

static campaign() → emodpy.emod_campaign.EMODCampaign
```

## emodpy.reporters package

### Submodules

#### emodpy.reporters.base module

```
class emodpy.reporters.base.BaseReporter
Bases: object

abstract to_dict()

from_dict(data)
Function allowing to initialize a Reporter instance with data. This function is called when reading a custom_reports.json file.

class emodpy.reporters.base.CustomReporter(name: str = None, Enabled: bool = True, Reports: list = <factory>, dll_file: str = None)
Bases: emodpy.reporters.base.BaseReporter
```

This class represents a custom reporter. - name: Name that will be added to the custom\_reports.json file and should match the DLL's class name - Enabled: True/False to enable/disable the reporter - Reports: Default section present in the custom\_reports.json file allowing to configure the reporter - dll\_file: Filename of the dll containing the reporter. This file will be searched in the dll folder specified by the user on the *EMODTask.reporters*.

```
name: str = None
Enabled: bool = True
```

```
Reports: list
dll_file: str = None
to_dict() → Dict
    Export the reporter to a dictionary. This function is called when serializing the reporter before writing the custom_reports.json file.

enable()
disable()

class emodpy.reporters.base.BuiltInReporter(class_name: str = None, parameters: dict
                                              = <factory>, Enabled: bool = True,
                                              Pretty_Format: bool = True)
Bases: emodpy.reporters.base.BaseReporter

class_name: str = None
parameters: dict
Enabled: bool = True
Pretty_Format: bool = True
to_dict()

from_dict(data)
    Function allowing to initialize a Reporter instance with data. This function is called when reading a custom_reports.json file.

class emodpy.reporters.base.Reporters(relative_path='reporter_plugins')
Bases: emodpy.emod_file.InputFilesList

add_reporter(reporter)
property json
property empty
add_dll(dll_path: str)
    Add a dll file from a path
        Parameters dll_path – Path to file
    Returns:
add_dll_folder(dll_folder: str)
    Add all the dll files from a folder
        Parameters dll_folder – Folder to add the dll file from
    Returns:
read_custom_reports_file(custom_reports_path, extra_classes=[]) → NoReturn
    Read from a custom reporter file
        Parameters custom_reports_path – The custom reports file to add(single file).
set_task_config(task: EMODTask) → NoReturn
    Set task config
        Parameters task – Task to configure
    Returns:
```

---

**gather\_assets** (\*\*kwargs) → List[idmtools.assets.asset.Asset]  
Gather input files for Input File List

Returns:

### emodpy.reporters.builtin module

```
class emodpy.reporters.builtin.ReportNodeDemographics(class_name: str = 'ReportNodeDemographics',
                                                       parameters: dict = <factory>, Enabled: bool = True,
                                                       Pretty_Format: bool = True, Stratify_By_Gender: bool = False, Age_Bins: list = <factory>)
```

Bases: *emodpy.reporters.base.BuiltInReporter*

**Stratify\_By\_Gender**: bool = False

**Age\_Bins**: list

**class\_name**: str = 'ReportNodeDemographics'

```
class emodpy.reporters.builtin.ReportHumanMigrationTracking(class_name: str = None, parameters: dict = <factory>, Enabled: bool = True, Pretty_Format: bool = True)
```

Bases: *emodpy.reporters.base.BuiltInReporter*

**config**(config\_builder, manifest)

**parameters**: dict

### emodpy.reporters.custom module

```
class emodpy.reporters.custom.Report_TBHIV_ByAge(name: str = 'Report_TBHIV_ByAge', Enabled: bool = True, Reports: list = <factory>, dll_file: str = 'lib_customreport_TBHIV_ReportByAge.dll')
```

Bases: *emodpy.reporters.base.CustomReporter*

**name**: str = 'Report\_TBHIV\_ByAge'

**dll\_file**: str = 'lib\_customreport\_TBHIV\_ReportByAge.dll'

**add\_report**(max\_age\_yrs, min\_age\_yrs, start\_year, stop\_year, events=[])

```
class emodpy.reporters.custom.ReportPluginAgeAtInfectionHistogram(name: str
= 'ReportPluginAgeAtInfectionHistogram',
Enabled: bool = True,
Reports: list = <factory>,
dll_file: str = 'libReportAgeAtInfectionHistogram_plugin.dll',
age_bins: list = <factory>,
interval_years: int = <factory>)

Bases: emodpy.reporters.base.CustomReporter
name: str = 'ReportPluginAgeAtInfectionHistogram'
dll_file: str = 'libReportAgeAtInfectionHistogram_plugin.dll'
Reports: list
age_bins: list
interval_years: int

class emodpy.reporters.custom.ReportHumanMigrationTracking(name: str = 'ReportHumanMigrationTracking',
Enabled: bool = True,
Reports: list = <factory>, dll_file: str = 'libhumanmigrationtracking.dll')

Bases: emodpy.reporters.base.CustomReporter
name: str = 'ReportHumanMigrationTracking'
dll_file: str = 'libhumanmigrationtracking.dll'
Reports: list

class emodpy.reporters.custom.ReportNodeDemographics(name: str = 'ReportNodeDemographics',
Enabled: bool = True,
Reports: list = <factory>, dll_file: str = 'libReportNodeDemographics.dll',
age_bins: list = <factory>)
```

```

Bases: emodpy.reporters.base.CustomReporter
name: str = 'ReportNodeDemographics'
age_bins: list
dll_file: str = 'libReportNodeDemographics.dll'
from_dict(data)
    Function allowing to initialize a Reporter instance with data. This function is called when reading a custom_reports.json file.

add_report(age_bins)
to_dict()
    Export the reporter to a dictionary. This function is called when serializing the reporter before writing the custom_reports.json file.

class emodpy.reporters.custom.MalariaSummaryReport(name: str = 'MalariaSummaryReport', Enabled: bool = True, Reports: list = <factory>, dll_file: str = 'libmalariasummary_report_plugin.dll')
Bases: emodpy.reporters.base.CustomReporter
name: str = 'MalariaSummaryReport'
dll_file: str = 'libmalariasummary_report_plugin.dll'
add_report(age_bins=None, duration_days=365, event_trigger_list=None, individual_property_filter='', infectiousness_bins=None, max_number_reports=10000, parasitemia_bins=None, report_description='', reporting_interval=30, start_day=0)

class emodpy.reporters.custom.ReportEventCounter(name: str = 'ReportEventCounter', Enabled: bool = True, Reports: list = <factory>, dll_file: str = 'libreporteventcounter.dll')
Bases: emodpy.reporters.base.CustomReporter
name: str = 'ReportEventCounter'
dll_file: str = 'libreporteventcounter.dll'
add_report(duration_days=10000, event_trigger_list=None, nodeset_config=None, report_description='', start_day=0)

class emodpy.reporters.custom.ReportMalariaFiltered(name: str = 'ReportMalariaFiltered', Enabled: bool = True, Reports: list = <factory>, dll_file: str = 'libReportMalariaFiltered.dll')
Bases: emodpy.reporters.base.CustomReporter
name: str = 'ReportMalariaFiltered'
dll_file: str = 'libReportMalariaFiltered.dll'
add_report(end_day=0, node_ids_of_interest=None, report_file_name='ReportMalariaFiltered.json', start_day=0)

class emodpy.reporters.custom.MalariaImmunityReport(name: str = 'MalariaImmunityReport', Enabled: bool = True, Reports: list = <factory>, dll_file: str = 'libmalariaimmunity_report_plugin.dll')

```

```
Bases: emodpy.reporters.base.CustomReporter
name: str = 'MalariaImmunityReport'
dll_file: str = 'libmalariaimmunity_report_plugin.dll'
add_report(pretty_format=1, age_bins=[], start_day=0, duration_days=10000, nodeset_config={'class': 'NodeSetAll'}, event_trigger_list=['EveryUpdate'], max_number_reports=15, report_description='', reporting_interval=15)

class emodpy.reporters.custom.MalariaSurveyJSONAnalyzer(name: str = 'MalariaSurveyJSONAnalyzer',
                                                       Enabled: bool = True,
                                                       Reports: list = <factory>, dll_file: str = 'libmalariasurveyJSON_analyzer_plugin.dll')

Bases: emodpy.reporters.base.CustomReporter
name: str = 'MalariaSurveyJSONAnalyzer'
dll_file: str = 'libmalariasurveyJSON_analyzer_plugin.dll'
add_report(pretty_format=1, start_day=0, duration_days=10000, nodeset_config={'class': 'NodeSetAll'}, event_trigger_list=['NewClinicalCase'], max_number_reports=15, report_description='Day0', reporting_interval=73)

class emodpy.reporters.custom.MalariaTransmissionReport(name: str = 'MalariaTransmissionReport',
                                                       Enabled: bool = True,
                                                       Reports: list = <factory>, dll_file: str = 'libReportMalariaTransmissions.dll')

Bases: emodpy.reporters.base.CustomReporter
name: str = 'MalariaTransmissionReport'
dll_file: str = 'libReportMalariaTransmissions.dll'
add_report(pretty_format=1, start_day=0, duration_days=365, nodeset_config={'class': 'NodeSetAll'}, event_trigger_list=['NewInfection'], report_description='')
```

## 10.1.2 Submodules

### emodpy.bamboo module

```
emodpy.bamboo.get_model_files(plan, manifest)
```

## emodpy.bamboo\_api\_utils module

`emodpy.bamboo_api_utils.bamboo_connection()`

**class** `emodpy.bamboo_api_utils.BambooConnection`

Bases: `object`

Bamboo API config and basic functionality/connectivity wrapper.

Automatically probes the most likely endpoint locations (with and without https, with and without port numbers).

Important functions:

- `login`: logs into the bamboo api, caches the login token so you don't have to pass creds for every req. in a session
- `get_bamboo_api_url`: translate a relative API URL into a fully qualified URL
- `normalize_url`: detect whether a URL is relative or not, translate relative URLs to fully qualified ones
- `make_get_request`: makes a request to the specified API url, adds some convenient error and login handling
- `download_file`: downloads a file from the specified artifacts url to a location on disk

**property server**

`str`: Keeps track of a single instance of the server base url. (e.g. `http://idm-bamboo:8085`)

**property session\_cookie**

`str`: Automatically load and instance the login session cookie jar.

**get\_server\_url** (`ssl: bool = False, useport: bool = False`) → `str`

Get a particular variant of the server url w/ or w/o ssl and port (e.g. `False/False -> http://idm-bamboo`)

**Parameters**

- `ssl (bool)` – whether to use ssl
- `useport (bool)` – whether to use the port

**Returns** endpoint url

**Return type** `str`

**find\_server** () → `str`

Explore all possible server urls, return the first one found to exist.

**Returns** server url

**Return type** `str`

**url\_exists** (`url: str`) → `bool`

Try a simple get request given an endpoint url, return whether it was successful (code 200).

**Parameters** `url (str)` – url to issue a test request to

**Returns** whether or not a request to the url succeeds (w/ status 200)

**Return type** `bool`

**property session\_cookie\_filename**

File where bamboo session cookie is stored.

**Returns** fully qualified file path of session cookie file

**Return type** `str`

```
load_session_cookie()      →      <module      'requests.cookies'      from
                                  '/home/docs/checkouts/readthedocs.org/user_builds/institute-
                                  for-disease-modeling-emodpy/envs/v1.9.1/lib/python3.7/site-
                                  packages/requests/cookies.py'>
```

Load api login session cookies from disk.

**Returns** session cookie jar

**Return type** requests.cookies

```
write_session_cookie(cookies:           <module      'requests.cookies'      from
                                  '/home/docs/checkouts/readthedocs.org/user_builds/institute-
                                  for-disease-modeling-emodpy/envs/v1.9.1/lib/python3.7/site-
                                  packages/requests/cookies.py'>)
```

Write post-login cookies for session to disk.

```
get_bamboo_url(relative_url: str) → str
```

Add bamboo server, port, and protocol to bamboo url.

**Parameters** **relative\_url** (str) – relative url (artifact link or api url)

**Returns** fully qualified url

**Return type** str

```
get_bamboo_api_url(relative_url: str, json: bool = False, params: dict = {}) → str
```

Get fully qualified bamboo api url from a relative url w/ given json mode and appending all parameters.

**Parameters**

- **relative\_url** (str) – api url (e.g. project/<project-key>)
- **json** (bool) – whether to get results in json format (otherwise, default is xml)
- **params** (dict) – name/value dictionary of query parameters

**Returns** fully qualified url that a request can be issued against

**Return type** str

```
save_credentials(username: str, password: str)
```

Save bamboo api login credentials using keyring.

**Parameters**

- **username** (str) – bamboo api login username (e.g. somebody@idmod.org)
- **password** (str) – bamboo api login password

```
ensure_logged_in()
```

Check if a login session exists using saved cookies, if not login using keyring stored creds.

```
login_session_exists() → bool
```

Test whether an existing session cookie exists and an active login session exists.

**Returns** whether an active login session exists

**Return type** bool

```
login(username: str = None, password=None) → bool
```

Login to the bamboo api. If username or password are not provided, use stored credentials from keyring.

**Parameters**

- **username** (str) – bamboo api login username (e.g. somebody@idmod.org)
- **password** (str) – bamboo api login password

**Returns** success/failure

**Return type** bool

**normalize\_url** (*url*: str) → str

Determine whether a url is relative or fully qualified, translate relative urls to fully qualified versions.

**Parameters** **url** (str) – relative or fully qualified url

**Returns** fully qualified url

**Return type** str

**make\_get\_request** (*url*: str, *retries*: int = 3) → requests.models.Response

Make a get request against the bamboo server.

**Parameters** **url** (str) – relative or fully qualified url

**Returns** request object returned from requests.get()

**Return type** requests.Response

**make\_api\_get\_request** (*relative\_url*: str, *json*: bool = False, *params*: dict = {}) → requests.models.Response

Translate relative api url to the fully qualified bamboo api url, make a get request against it.

**Parameters**

- **relative\_url** (str) – url relative to the bamboo api endpoint (e.g. ‘result/MYPROJ-MYPLAN/123’) to make the request against
- **json** (bool) – whether to return results in json
- **params** (dict) – name/value dictionary of additional parameters to pass

**Returns** request object returned from requests.get()

**Return type** requests.Response

**download\_file** (*url*: str, *destination*: str) → list

Download a specific artifact file (from the full artifact url provided) to disk.

Streams the download to avoid common ‘gotchas’ with downloading via http.

**Parameters**

- **url** (str) – url to download
- **destination** (str) – destination path or filename where the artifact is to be downloaded to

**Returns** local filename of file that has been downloaded

**Return type** (str)

**class** emodpy.bamboo\_api\_utils.**BuildInfo**

Bases: object

A collection of methods for getting data on build results.

**classmethod** **build\_passed** (*plan\_key*: str, *build\_num*: int) → bool

Determine whether a given build succeeded or not.

**Parameters**

- **plan\_key** (str) – bamboo plan key (including project key)
- **build\_num** (int) – build number to retrieve results for

**Returns** whether the build succeeded

**Return type** bool

**static successful\_build\_result(result) → bool**

Analyze a build result json object and determine if it corresponds to a successful build

**Parameters** **result** – json build result

**Returns** whether the build was successful

**Return type** bool

**static get\_build\_info(plan\_key: str, index: int)**

Retrieve the build info in json format for a given build plan with a relative index (0=latest)

**Parameters**

- **plan\_key** (str) – bamboo plan key (including project key)
- **index** (int) – index of build to retrieve info for (0=latest, 1=2nd most recent, etc.)

**Returns** build info results json

**classmethod get\_latest\_successful\_build(plan\_key: str, scheduled\_only: bool = True, max\_iterations: int = 100)**

Find the latest successful build within the last max\_iterations builds for a given plan.

**Parameters**

- **plan\_key** (str) – bamboo plan key (including project key)
- **scheduled\_only** (bool) – only count automatically run scheduled or triggered builds as successful
- **max\_iterations** (int) – maximum number of older builds to look through

**Returns**

**tuple containing:** build\_num (str): build number of last successful build build\_info: json data structure of build info for that build

**Return type** (tuple)

**classmethod get\_latest\_build(plan\_key: str)**

Get the build info for the most recently run build for a given plan.

**Parameters** **plan\_key** (str) – bamboo plan key (including project key)

**Returns**

**tuple containing:** build\_num (str): build number of last successful build build\_info: json data structure of build info for that build

**Return type** (tuple)

**class** emodpy.bamboo\_api\_utils.**BuildArtifacts**

Bases: object

A collection of methods for finding and interacting with build artifacts.

**ERADICATION\_EXE** = 'Eradication.exe'

**SCHEMA\_JSON** = 'schema.json'

**REPORTER\_PLUGINS** = 'Reporter-Plugins'

**classmethod find\_artifacts\_by\_name(plan\_key: str, build\_num: int, artifact: str) → list**

Find all urls for files of an artifact of a given name for a specific build.

**Parameters**

- **plan\_key** (*str*) – bamboo plan key (including project key)
- **build\_num** (*int*) – build number to retrieve artifact urls for
- **artifact** (*str*) – artifact name/id

**Returns** list of artifact urls that can be downloaded**Return type** (list of str)**classmethod** **find\_artifacts** (*plan\_key: str, build\_num: int, artifact\_list: list*) → list

Find all urls for files of a list of artifacts for a specific build.

**Parameters**

- **plan\_key** (*str*) – bamboo plan key (including project key)
- **build\_num** (*int*) – build number to retrieve artifact urls for
- **artifact\_list** (*list*) – list of artifact names/ids

**Returns** list of artifact urls that can be downloaded**Return type** (list of str)**classmethod** **find\_build\_essential\_artifacts** (*plan\_key: str, build\_num: int*) → list

Find all ‘build essential’ artifact urls (Eradication, schema, reporters) for a specific build

**Parameters**

- **plan\_key** (*str*) – bamboo plan key (including project key)
- **build\_num** (*int*) – build number to retrieve artifact urls for

**Returns** list of artifact urls that can be downloaded**Return type** (list of str)**classmethod** **find\_all\_artifacts** (*plan\_key: str, build\_num: int*) → list

Find all artifact urls (Eradication, schema, reporters) for a specific build

**Parameters**

- **plan\_key** (*str*) – bamboo plan key (including project key)
- **build\_num** (*int*) – build number to retrieve artifact urls for

**Returns** list of artifact urls that can be downloaded**Return type** (list of str)**classmethod** **find\_all\_artifact\_names** (*plan\_key: str, build\_num: int*) → list

Find all artifact names (e.g. ‘Eradication.exe’) for a specific build (can be plugged into find\_artifacts() to get actual urls that can be downloaded)

**Parameters**

- **plan\_key** (*str*) – bamboo plan key (including project key)
- **build\_num** (*int*) – build number to retrieve artifact urls for

**Returns** list of artifact names that can be downloaded**Return type** (list of str)

```
classmethod download_artifact_to_file(plan_key: str, build_num: int, artifact, destination: str) → list
```

Download files found for a named artifact to the filepath provided.

Additional files found will be downloaded as \_2, \_3, \_4, etc. For example, if there are 3 files for ‘Eradication.exe’ the first will be Eradication.exe, the second will be Eradication\_2.exe, the third Eradication\_3.exe.

#### Parameters

- **plan\_key** (*str*) – bamboo plan key (including project key)
- **build\_num** (*int*) – build number to retrieve artifact urls for
- **artifact** (*list or str*) – list (or string) of artifact names
- **destination** (*str*) – destination path or filename where the artifact is to be downloaded to

**Returns** list of local filenames of files that have been downloaded

**Return type** (list of str)

```
classmethod download_artifacts_to_path(plan_key: str, build_num: int, artifact, destination_path: str) → list
```

Download all the files for a given artifact and build to a specific folder, using their original filenames.

#### Parameters

- **plan\_key** (*str*) – bamboo plan key (including project key)
- **build\_num** (*int*) – build number to retrieve artifact urls for
- **artifact** (*list or str*) – list (or string) of artifact names
- **destination\_path** (*str*) – path to destination folder where files are to be downloaded

**Returns** list of local filenames of files that have been downloaded

**Return type** (list of str)

```
classmethod download_latest_good_Eradication_exe(plan_key: str, destination: str) → str
```

Find the latest successful build for a specified plan, download the Eradication.exe artifact to a specified path.

#### Parameters

- **plan\_key** (*str*) – bamboo plan key (including project key)
- **destination** (*str*) – destination path or filename where the artifact is to be downloaded to

**Returns** build number of build that was found and had its artifact downloaded

**Return type** str

```
classmethod download_latest_good_schema_json(plan_key: str, destination: str) → str
```

Find the latest successful build for a specified plan, download the schema.json artifact to a specified path.

#### Parameters

- **plan\_key** (*str*) – bamboo plan key (including project key)
- **destination** (*str*) – destination path or filename where the artifact is to be downloaded to

**Returns** build number of build that was found and had its artifact downloaded

**Return type** str

```
classmethod download_ereadication_exe(plan_key: str, build_num: str, destination: str) → str
```

Download Eradication.exe artifact from a specific build.

**Parameters**

- **plan\_key** (str) – bamboo plan key (including project key)
- **build\_num** (str) – build number to download from
- **destination** (str) – destination path or filename where the artifact is to be downloaded to

```
classmethod make_exe_executable(file_path: str)
```

On linux change the file permissions on a binary to make it executable

**Parameters** file\_path (str) – binary file to mark as executable

```
classmethod download_schema_json(plan_key: str, build_num: str, destination: str) → str
```

Download schema.json artifact from a specific build.

**Parameters**

- **plan\_key** (str) – bamboo plan key (including project key)
- **build\_num** (str) – build number to download from
- **destination** (str) – destination path or filename where the artifact is to be downloaded to

```
classmethod download_from_bamboo_url(url: str, destination: str)
```

Download Eradication.exe/Eradication directly from bamboo url Assume you already done login

**Parameters**

- **url** –
- **destination** (str) – destination path or filename where the artifact is to be downloaded to

**Returns** local file path that have been downloaded

**Return type** str

```
class emodpy.bamboo_api_utils.BuildPlans
```

Bases: object

Collection of methods for getting information on build plans.

```
static export_spec(plan_key: str) → str
```

Export a specific build plan to java specs.

**Parameters** plan\_key (str) – bamboo plan key (including project key)

**Returns** full text of the .java file for the plan spec, if the plan was found (empty string if not)

**Return type** str

```
static get_plans_for_project(project_key: str) → list
```

Return a list of all the build plans for every plan in the project.

**Parameters** project\_key (str) – bamboo project key

**Returns** list of plan keys for each plan that was found in the project

**Return type** (list of str)

`emodpy.bamboo_api_utils.login(username=None, password=None)`  
Pass through to BambooConnection.login()

`emodpy.bamboo_api_utils.save_credentials(username, password)`  
Pass through to BambooConnection.save\_credentials()

## emodpy.collections\_utils module

`emodpy.collections_utils.cut_iterable_to(obj: Iterable, to: int) → Tuple[Union[List, Mapping], int]`

Cut an iterable to a certain length.

### Parameters

- `obj` – The iterable to cut.
- `to` – The number of elements to return.

**Returns** A list or dictionary (depending on the type of object) of elements and the remaining elements in the original list or dictionary.

`emodpy.collections_utils.deep_get(d, key, default: callable = None, getter: callable = None, sep: str = '.')`

`emodpy.collections_utils.deep_set(d, key, value, default: callable = None, getter: callable = None, setter: callable = None, sep: str = '.')`

`emodpy.collections_utils.deep_del(d: dict, key, getter: callable = None, deleter: callable = None, sep: str = '.')`

## emodpy.emod\_campaign module

`class emodpy.emod_campaign.EMODCampaign(name='Campaign', events=None, use_defaults=True, **kwargs)`

Bases: object

Class representing an EMOD Campaign. It contains:  
- events: a list of events for the given campaign  
- name: campaign name  
- use\_defaults: EMOD flag to use defaults for unspecified parameters  
- extra\_parameters: parameters set by the user that will be added to the campaign JSON

### property json

Property to transform the object in JSON

`static load_from_file(filename: str) → object`  
Load a campaign from a JSON file.

**Parameters** `filename` – Path to the campaign file

Returns: an initialized `EMODCampaign` instance

`static load_from_dict(data: Dict) → object`  
Create a campaign object from a dict. :param data: The dictionary containing the data

Returns: an initialized `EMODCampaign` instance

`clear() → NoReturn`  
Clear all campaign events

---

**get\_events\_at** (*timestep*: int) → List[Dict]  
Get a list of events happening at the specified timestep. Does not take into account recurrence and only consider start timestep. :param timestep: selected timestep

Returns: list of events

**get\_events\_with\_name** (*name*: str) → List[Dict]  
Get a list of events with the given name. This search is based on the *Event\_Name* key of events. :param name: Name of the events

Returns: list of events

**add\_event** (*event*: Dict) → NoReturn  
Add the given event to the campaign event. :param event: The event to add

**add\_events** (*events*: List[Dict]) → NoReturn  
Add a list of events to the campaign events. :param events: List of events to add

## emodpy.emod\_file module

```
class emodpy.emod_file.InputFilesList (relative_path=None)
Bases: idmtools.assets.asset_collection.AssetCollection

abstract set_task_config (simulation)
gather_assets () → List[idmtools.assets.asset.Asset]
Gather input files for Input File List

Returns:

class emodpy.emod_file.MigrationTypes (value)
Bases: enum.Enum

An enumeration.

LOCAL = 'Local'
AIR = 'Air'
FAMILY = 'Family'
REGIONAL = 'Regional'
SEA = 'Sea'

class emodpy.emod_file.MigrationModel (value)
Bases: enum.Enum

An enumeration.

NO_MIGRATION = 'NO_MIGRATION'
FIXED_RATE_MIGRATION = 'FIXED_RATE_MIGRATION'

class emodpy.emod_file.MigrationPattern (value)
Bases: enum.Enum

An enumeration.

RANDOM_WALK_DIFFUSION = 'RANDOM_WALK_DIFFUSION'
SINGLE_ROUND_TRIPS = 'SINGLE_ROUND_TRIPS'
WAYPOINTS_HOME = 'WAYPOINTS_HOME'
```

```
class emodpy.emod_file.MigrationFiles(relative_path=None)
Bases: emodpy.emod_file.InputFilesList

enable_migration()
    Enables migration and sets the pattern if defined. If there are not other other parameters, it also set Enable_Migration_Heterogeneity to 0

update_migration_pattern(migration_pattern: emodpy.emod_file.MigrationPattern,
                         **kwargs) → NoReturn
    Update migration pattern

    Parameters
        • migration_pattern – Migration Pattern to use
        • **kwargs –

    Returns NoReturn

add_migration_from_file(migration_type: emodpy.emod_file.MigrationTypes, file_path: str,
                        multiplier: float = 1)
    Add migration info from a file

    Parameters
        • migration_type – Type of migration
        • file_path – Path to file
        • multiplier – Multiplier

    Returns:

set_task_config(task: EMODTask)
    Update the task with the migration configuration

    Parameters task – Task to update

    Returns:

gather_assets()
    Gather assets for Migration files. Called by EMODTask Returns:

set_all_persisted()
    Set all migration assets as persisted

    Returns:

merge_with(mf: emodpy.emod_file.MigrationFiles, left_precedence: bool = True) → NoReturn
    Merge migration file with other Migration file

    Parameters
        • mf – Other migration file to merge with
        • left_precedence – Does the current object have precedence or the other object?

    Returns:

read_config_file(config_path, asset_path)
    Try to recreate the migration based on a given config file and an asset path :param config_path: path to the config :param asset_path: path containing the assets

class emodpy.emod_file.DemographicsFiles(relative_path=None)
Bases: emodpy.emod_file.InputFilesList
```

---

**set\_task\_config** (*task: EMODTask, extend: bool = False*)  
Set the simulation level config. If extend is true, the demographics files are appended to the list :param task: :param extend:

Returns:

**add\_demographics\_from\_file** (*absolute\_path: str, filename: Optional[str] = None*)  
Add demographics from a file

**Parameters**

- **absolute\_path** – Path to file
- **filename** – Optional filename. If not provided, the file name of source file will be used

Returns:

**add\_demographics\_from\_dict** (*content: Dict, filename: str*)  
Add demographics from a dictionary object

**Parameters**

- **content** – Dictionary Content
- **filename** – Filename to call demographics file

Returns:

```
class emodpy.emod_file.ClimateFileType (value)
Bases: enum.Enum

An enumeration.

AIR_TEMPERATURE = 'Air_Temperature'
LAND_TEMPERATURE = 'Land_Temperature'
RELATIVE_HUMIDITY = 'Relative_Humidity'
RAINFALL = 'Rainfall'
```

```
class emodpy.emod_file.ClimateModel (value)
Bases: enum.Enum

An enumeration.

CLIMATE_OFF = 'CLIMATE_OFF'
CLIMATE_CONSTANT = 'CLIMATE_CONSTANT'
CLIMATE_KOPPEN = 'CLIMATE_KOPPEN'
CLIMATE_BY_DATA = 'CLIMATE_BY_DATA'
```

```
class emodpy.emod_file.ClimateFiles
Bases: emodpy.emod_file.InputFilesList

set_task_config (task: EMODTask)
Set the task Config. Set all the correct files for the climate.
```

**Parameters** **task** – Task to config

**add\_climate\_files** (*file\_type, file\_path*)

**gather\_assets** ()  
Gather assets for Climate files. Called by EMODTask

**set\_climate\_constant** (*Base\_Air\_Temperature, Base\_Rainfall, Base\_Land\_Temperature=None, Base\_Relative\_Humidity=None*)

**read\_config\_file**(config\_path, asset\_path)

Try to recreate the climate based on a given config file and an asset path :param config\_path: path to the config :param asset\_path: path containing the assets

**emodpy.emod\_task module**

```
emodpy.emod_task.logger = <Logger emodpy.emod_task (DEBUG)>
```

Note that these 3 functions could be member functions of EMODTask but Python modules are already pretty good at being ‘static classes’.

```
emodpy.emod_task.add_ep4_from_path(task, ep4_path)
```

```
emodpy.emod_task.default_ep4_fn(task)
```

```
class emodpy.emod_task.EMODTask(command: Union[str, tools.entities.command_line.CommandLine] = <property object>, platform_requirements: Set[idmtools.entities.platform_requirements.PlatformRequirements] = <factory>, _ITask__pre_creation_hooks: List[Callable[[Union[Simulation, IWorkflowItem], IPlatform], NoReturn]] = <factory>, _ITask__post_creation_hooks: List[Callable[[Union[Simulation, IWorkflowItem], IPlatform], NoReturn]] = <factory>, common_assets: idmtools.assets.asset_collection.AssetCollection = <factory>, transient_assets: idmtools.assets.asset_collection.AssetCollection = <factory>, eradication_path: str = None, demographics: emodpy.emod_file.DemographicsFiles = <factory>, migrations: emodpy.emod_file.MigrationFiles = <factory>, reporters: emodpy.reporters.base.Reporters = <factory>, climate: emodpy.emod_file.ClimateFiles = <factory>, config: dict = <factory>, config_file_name: str = 'config.json', campaign: emodpy.emod_campaign.EMODCampaign = <factory>, simulation_demographics: emodpy.emod_file.DemographicsFiles = <factory>, simulation_migrations: emodpy.emod_file.MigrationFiles = <factory>, use_embedded_python: bool = True, is_linux: bool = False, implicit_configs: list = <factory>)
```

Bases: idmtools.entities.itask.ITask

EMODTask allows easy running and configuration of EMOD Experiments and Simulations

**eradication\_path: str = None**

Eradication path. Can also be set through config file

**demographics: emodpy.emod\_file.DemographicsFiles**

Common Demographics

**migrations: emodpy.emod\_file.MigrationFiles**

Common Migrations

**reporters: emodpy.reporters.base.Reporters**

Common Reports

**climate: emodpy.emod\_file.ClimateFiles**

Common Climate

---

```

config: dict
    Represents config.json

config_file_name: str = 'config.json'

campaign: emodpy.emod_campaign.EMODCampaign
    Campaign configuration

simulation_demographics: emodpy.emod_file.DemographicsFiles
    Simulation level demographics such as overlays

simulation_migrations: emodpy.emod_file.MigrationFiles
    Simulation level migrations

use_embedded_python: bool = True
    Add --python-script-path to command line

is_linux: bool = False

implicit_configs: list

create_campaign_from_callback(builder)

classmethod from_default2(eradication_path, schema_path, param_custom_cb, config_path='new_config.json', campaign_builder=None, ep4_custom_cb=<function default_ep4_fn>, demog_builder=None, plugin_report=None, serial_pop_files=None, **kwargs) → emodpy.emod_task.EMODTask
Create a task from emod-api Defaults

```

#### Parameters

- **config\_path** – /path/to/new\_config.json
- **eradication\_path** – Path to Eradication binary
- **param\_custom\_cb** – Function that sets parameters for config
- **ep4\_custom\_cb** – Function that sets EP4 assets
- **plugin\_report** – Custom reports file

#### Returns EMODTask

```

classmethod from_files(eradication_path=None, config_path=None, campaign_path=None, demographics_paths=None, ep4_path=None, custom_reports_path=None, asset_path=None, **kwargs)

```

Load custom EMOD files when creating [EMODTask](#).

#### Parameters

- **asset\_path** – If an asset path is passed, the climate, dlls, and migrations will be searched there
- **eradication\_path** – The eradication.exe path.
- **config\_path** – The custom configuration file.
- **campaign\_path** – The custom campaign file.
- **demographics\_paths** – The custom demographics files (single file or a list).
- **custom\_reports\_path** – Custom reports file

Returns: An initialized experiment

**load\_files** (*config\_path=None*, *campaign\_path=None*, *custom\_reports\_path=None*, *demographics\_paths=None*, *asset\_path=None*) → NoReturn  
Load files in the experiment/base\_simulation.

#### Parameters

- **asset\_path** – Path to find assets
- **config\_path** – Configuration file path
- **campaign\_path** – Campaign file path
- **demographics\_paths** – Demographics file path
- **custom\_reports\_path** – Path for the custom reports file

**pre\_creation** (*parent*: Union[idmtools.entities.simulation.Simulation, tools.entities.iworkflow\_item.IWorkflowItem], *platform*: tools.entities.iplatform.IPlatform) → idm-

Call before a task is executed. This ensures our configuration is properly done

**set\_command\_line** () → NoReturn

Builds and sets the command line object

Returns:

**gather\_common\_assets** () → idmtools.assets.asset\_collection.AssetCollection

Gather Experiment Level Assets Returns:

**gather\_transient\_assets** () → idmtools.assets.asset\_collection.AssetCollection

Gather assets that are per simulation Returns:

**copy\_simulation** (*base\_simulation*: idmtools.entities.simulation.Simulation) → idm-  
tools.entities.simulation.Simulation

Called when making copies of a simulation.

Here we deep copy parts of the simulation to ensure we don't accidentally update objects :param  
*base\_simulation*: Base Simulation

Returns:

**set\_parameter** (*name*: str, *value*: any) → dict

Set a value in the EMOD config.json file. This will be deprecated in the future in favour of  
emod\_api.config.

#### Parameters

- **name** – Name of parameter to set
- **value** – Value to set

Returns Tags to set

**static set\_parameter\_sweep\_callback** (*simulation*: tools.entities.simulation.Simulation, *param*: str, *value*: Any) → Dict[str, Any] → idm-

Convenience callback for sweeps

#### Parameters

- **simulation** – Simulation we are updating
- **param** – Parameter
- **value** – Value

Returns Tags to set on simulation

---

```
classmethod set_parameter_partial(parameter: str)
    Convenience callback for sweeps

        Parameters parameter – Parameter to set

        Returns:

get_parameter(name: str, default: Optional[Any] = None)
    Get a parameter in the simulation.

        Parameters

            • name – The name of the parameter.

            • default – Optional, the default value.

        Returns The value of the parameter.

update_parameters(params)
    Bulk update the configuration parameter values. This will be deprecated in the future in favour of emod_api.config.

        Parameters params – A dictionary with new values.

        Returns None

reload_from_simulation(simulation: idmtools.entities.simulation.Simulation)
    Optional hook that is called when loading simulations from a platform

class emodpy.emod_task.EMODTaskSpecification
    Bases: idmtools.registry.task_specification.TaskSpecification

get(configuration: dict) → emodpy.emod_task.EMODTask
    Return an EMODTask object using provided configuration :param configuration: Configuration for Task

        Returns EMODTask for configuration

get_description() → str
    Defines a description of the plugin

        Returns Plugin description

get_example_urls() → List[str]
    Return a list of examples. This is used by the examples cli command to allow users to quickly load examples locally

        Returns List of urls to examples

get_type() → Type[emodpy.emod_task.EMODTask]
    Returns the Task type defined by specification

        Returns:

get_version() → str
    Return the version string for EMODTask. This should be the module version so return that

        Returns Version
```

## **emodpy.utils module**

```
class emodpy.utils.EradicationPlatformExtension(value)
    Bases: enum.Enum

    An enumeration.

    LINUX = ''
    Windows = '.exe'

class emodpy.utils.EradicationBambooBuilds(value)
    Bases: enum.Enum

    An enumeration.

    GENERIC_LINUX = 'DTKGENCI-SCONSLNXGEN'
    GENERIC_WIN = 'DTKGENCI-SCONSWINGEN'
    GENERIC = 'DTKGENCI-SCONSLNXGEN'
    TBHIV_LINUX = 'DTKTBHIVCI-SCONSRELLNXTBHIV'
    TBHIV_WIN = 'DTKTBHIVCI-SCONSWINTBHIV'
    TBHIV = 'DTKTBHIVCI-SCONSRELLNXTBHIV'
    MALARIA_LINUX = 'DTKMALCI-SCONSLNXMAL'
    MALARIA_WIN = 'DTKMALCI-SCONSWINMAL'
    MALARIA = 'DTKMALCI-SCONSLNXMAL'
    HIV_LINUX = 'DTKHIVCI-SCONSRELLNXHIV'
    HIV_WIN = 'DTKHIVCI-RELWINHIV'
    HIV = 'DTKHIVCI-SCONSRELLNXHIV'
    DENGUE_LINUX = 'DTKDENGCI-SCONSRELLNX'
    DENGUE_WIN = 'DTKDENGCI-VSRELWINALL'
    DENGUE = 'DTKDENGCI-SCONSRELLNX'
    FP_LINUX = 'DTKFPCI-SCONSRELLNX'
    FP_WIN = 'DTKFPCI-SCONSWINFP'
    FP = 'DTKFPCI-SCONSRELLNX'
    TYPHOID_LINUX = 'DTKTYPHCI-SCONSRELLNX'
    TYPHOID_WIN = 'DTKTYPHCI-SCONSWINENV'
    TYPHOID = 'DTKTYPHCI-SCONSRELLNX'
    EMOD_RELEASE = 'EMODREL-SCONSRELLNX'
    RELEASE = 'DTKREL-SCONSRELLNX'

class emodpy.utils.BambooArtifact(value)
    Bases: enum.Flag

    An enumeration.

    ERADICATION = 1
    SCHEMA = 2
```

---

```
PLUGINS = 4
```

```
ALL = 7
```

```
emodpy.utils.get_github_ereadication_url(version: str, extension: emodpy.utils.EradicationPlatformExtension = <EradicationPlatformExtension.LINUX: ">) → str
```

Get the github eradication url for specified release

#### Parameters

- **version** – Release to fetch
- **extension** – Optional extensions. Defaults to Linux(None)

#### Returns

Url of eradication release

```
emodpy.utils.save_bamboo_credentials(username, password)
```

Save bamboo api login credentials using keyring.

#### Parameters

- **username** (*str*) – bamboo api login username (e.g. somebody@idmod.org)
- **password** (*str*) – bamboo api login password

```
emodpy.utils.bamboo_api_login()
```

Automatically login to bamboo, prompt for credentials if none are cached or there's no login session.

```
emodpy.utils.download_bamboo_artifacts(plan_key: str, build_num: str = None, scheduled_builds_only: bool = True, artifact: emodpy.utils.BambooArtifact = <BambooArtifact.ERADICATION: 1>, out_path: str = None) → list
```

Downloads artifact(s) for a DTK Bamboo build plan to the specified path

#### Parameters

- **plan\_key** (*str*) –
- **build\_num** (*str*) –
- **scheduled\_builds\_only** (*bool*) –
- **artifact** (*BambooArtifact*) –
- **out\_path** (*str*) – Output path to save file (default to current directory)

#### Returns

Returns list of downloaded files on filesystem

```
emodpy.utils.download_latest_bamboo(plan: emodpy.utils.EradicationBambooBuilds, scheduled_builds_only: bool = True, out_path: str = None) → str
```

Downloads the Eradication binary for the latest successful build for a Bamboo Plan to specified path. Exists for backward compatibility, just a pass-thru to download\_latest\_ereadication().

#### Parameters

- **plan** – Bamboo Plan key. for supported build
- **out\_path** – Output path to save file (default to current directory)

#### Returns

Returns local filename of downloaded file

```
emodpy.utils.download_latest_ eradication(plan: emodpy.utils.EradicationBambooBuilds,  
                                         scheduled_builds_only: bool = True, out_path:  
                                         str = None) → str
```

Downloads the Eradication binary for the latest successful build for a Bamboo Plan to specified path.

**Parameters**

- **plan** – Bamboo Plan key. for supported build
- **out\_path** – Output path to save file (default to current directory)

**Returns** Returns local filename of downloaded file

```
emodpy.utils.download_latest_reporters(plan: emodpy.utils.EradicationBambooBuilds,  
                                         scheduled_builds_only: bool = True, out_path: str  
                                         = None) → list
```

Downloads the reporter plugins for the latest successful build for a Bamboo Plan to specified path.

**Parameters**

- **plan** – Bamboo Plan key. for supported build
- **out\_path** – Output path to save file (default to current directory)

**Returns** Returns list of local filenames of downloaded files

```
emodpy.utils.download_latest_schema(plan: emodpy.utils.EradicationBambooBuilds, sched-  
                                         uled_builds_only: bool = True, out_path: str = None)
```

Downloads the schema.json for the latest successful build for a Bamboo Plan to specified path.

**Parameters**

- **plan** – Bamboo Plan key. for supported build
- **out\_path** – Output path to save file (default to current directory)

**Returns** Returns local filename of downloaded file

```
emodpy.utils.download_from_url(url, out_path: str = None) → str
```

```
emodpy.utils.download_ eradication(url: str, cache_path: str = None, spinner=None)
```

Downloads Eradication binary

Useful for downloading binaries from Bamboo or Github

**Parameters**

- **url** – Url to binary
- **cache\_path** – Optional output directory
- **spinner** – Spinner object

**Returns** Full path to output file

---

CHAPTER  
**ELEVEN**

---

## GLOSSARY

The following terms describe both the features and functionality of the emodpy software, as well as information relevant to using emodpy.

**asset collection** The set of specific input files (such as input parameters, weather or migration data, or other configuration settings) required for running a simulation.

**assets** See asset collection.

**builder** TBD

**experiment** A collection of multiple simulations, typically sent to an HPC.

**high-performance computing (HPC)** The use of parallel processing for running advanced applications efficiently, reliably, and quickly.

**task** TBD

**template** TBD



---

CHAPTER  
TWELVE

---

CHANGELOG

## 12.1 1.1.0

### 12.1.1 Additional Changes

- #0001 - Fix emod tests
- #0024 - Support of Kurt's workflows in idmtools
- #0070 - Custom\_reporters.json does not get automatically added?

### 12.1.2 Bugs

- #0011 - task with simulation level demographics not work
- #0012 - How to add custom simulation tags from task?
- #0040 - examples- emod\_model- serialization- 03\_parameter\_reload getting wrong campaign
- #0042 - We should make EMODSir default work with eradication
- #0043 - Wired campaign format error
- #0044 - Examples- create\_sims\_pre\_and\_post\_process.py should import config\_update\_parameters correctly
- #0055 - Creation of campaign.json will fail in AC in COMPS - cannot overwrite AC files
- #0059 - EmodTask.pre\_post\_process should be renamed
- #0069 - Fix create\_serialized\_sims\_reload and create\_sims\_from\_default\_run\_analyzer examples
- #0072 - custom\_reports.json - not all of them have “enabled”, but code assumes they do
- #0073 - Climate\_Model should be set to whatever it is set in config.json when from\_files is used.
- #0075 - custom\_reports: when reading my ReportNodeDemographics report, one of the parameters is not read in

### **12.1.3 Developer/Test**

- #0015 - Add changelog script
- #0039 - Rename repo to emodpy

### **12.1.4 Documentation**

- #0007 - Automate docs
- #0008 - Document a simple example of running DTK in idmtools
- #0045 - examples- emod\_model- post\_process\_command\_task- needs some mortality
- #0061 - make docs failed

### **12.1.5 Feature Request**

- #0028 - We should implement reload\_from\_simulation() for EMODTask
- #0030 - Support of a list of campaign events
- #0032 - Utility function to create a campaign event
- #0033 - Support of reporters for EMOD
- #0034 - Support of schema defaults
- #0063 - Support of climate files

### **12.1.6 Models**

- #0014 - Need to add –python-script-path option to EMODTask arguments
- #0029 - Modifications of base config parameters

### **12.1.7 Platforms**

- #0021 - SSMT Build as part of GithubActions

### **12.1.8 User Experience**

- #0037 - Add examples url to plugins specifications and then each plugin if they have examples
- #0049 - Add system tags for EMODTask

## 12.2 1.2.0

### 12.2.1 Additional Changes

- #0091 - Eradication.exe can't consume emodpy\_covid installed in a virtual environment (Windows)

### 12.2.2 Bugs

- #0054 - examplescreate\_sims\_ereadication\_from\_github\_url.py failed
- #0098 - Few migration bugs

### 12.2.3 Documentation

- #0060 - Help with repro: dtk\_pre\_process executed twice before simulation attempted

### 12.2.4 Feature Request

- #0036 - Creation of migration file from code
- #0090 - We should have utils to download Eradication by giving url

### 12.2.5 User Experience

- #0047 - Directly use Eradication.exe from bamboo url seems not working
- #0068 - emodpyutils.py needs more robust solution for getting Eradication.exe paths



## PYTHON MODULE INDEX

### e

emodpy, 23  
emodpy.analyzers, 23  
emodpy.analyzers.adult\_vectors\_analyzer,  
    23  
emodpy.analyzers.population\_analyzer,  
    24  
emodpy.analyzers.timeseries\_analyzer,  
    24  
emodpy.bamboo, 32  
emodpy.bamboo\_api\_utils, 33  
emodpy.collections\_utils, 40  
emodpy.defaults, 25  
emodpy.defaults.emod\_sir, 25  
emodpy.defaults.ep4, 25  
emodpy.defaults.ep4.dtk\_in\_process, 25  
emodpy.defaults.ep4.dtk\_post\_process,  
    25  
emodpy.defaults.ep4.dtk\_pre\_process, 25  
emodpy.defaults.iemod\_default, 26  
emodpy.emod\_campaign, 40  
emodpy.emod\_file, 41  
emodpy.emod\_task, 44  
emodpy.generic, 26  
emodpy.generic.serialization, 26  
emodpy.interventions, 27  
emodpy.interventions.emod\_empty\_campaign,  
    27  
emodpy.reporters, 27  
emodpy.reporters.base, 27  
emodpy.reporters.builtin, 29  
emodpy.reporters.custom, 29  
emodpy.utils, 48



# INDEX

## A

add\_climate\_files()  
    (emodpy.emod\_file.ClimateFiles method), 43  
add\_demographics\_from\_dict()  
    (emodpy.emod\_file.DemographicsFiles method), 43  
add\_demographics\_from\_file()  
    (emodpy.emod\_file.DemographicsFiles method), 43  
add\_dll() (emodpy.reporters.base.Reporters method), 28  
add\_dll\_folder() (emodpy.reporters.base.Reporters method), 28  
add\_ep4\_from\_path() (in module emodpy.emod\_task), 44  
add\_event() (emodpy.emod\_campaign.EMODCampaign method), 41  
add\_events() (emodpy.emod\_campaign.EMODCampaign method), 41  
add\_migration\_from\_file()  
    (emodpy.emod\_file.MigrationFiles method), 42  
add\_report() (emodpy.reporters.custom.MalariaImmunologyReport method), 32  
add\_report() (emodpy.reporters.custom.MalariaSummaryReport method), 31  
add\_report() (emodpy.reporters.custom.MalariaSurveyJSONAnalyzer method), 32  
add\_report() (emodpy.reporters.custom.MalariaTransmissionReport method), 32  
add\_report() (emodpy.reporters.custom.Report\_TBHIV\_ByAge method), 29  
add\_report() (emodpy.reporters.custom.ReportEventCounter method), 31  
add\_report() (emodpy.reporters.custom.ReportMalariaFiltered method), 31  
add\_report() (emodpy.reporters.custom.ReportNodeDemographics method), 31  
add\_reporter() (emodpy.reporters.base.Reporters method), 28  
add\_serialization\_timesteps() (in module emodpy.generic.serialization), 26

AdultVectorsAnalyzer (class in emodpy.analyzers.adult\_vectors\_analyzer), 23  
Age\_Bins (emodpy.reporters.builtin.ReportNodeDemographics attribute), 29  
age\_bins (emodpy.reporters.custom.ReportNodeDemographics attribute), 31  
age\_bins (emodpy.reporters.custom.ReportPluginAgeAtInfectionHistogram attribute), 30  
AIR (emodpy.emod\_file.MigrationTypes attribute), 41  
AIR\_TEMPERATURE (emodpy.emod\_file.ClimateFileType attribute), 43  
ALL (emodpy.utils.BambooArtifact attribute), 49  
application() (in module emodpy.defaults.ep4.dtk\_in\_process), 25  
application() (in module emodpy.defaults.ep4.dtk\_post\_process), 25  
application() (in module emodpy.defaults.ep4.dtk\_pre\_process), 25  
asset collection, 51  
assets, 51

## B

bamboo\_api\_login() (in module emodpy.utils), 49  
bamboo\_connection() (in module emodpy.bamboo\_api\_utils), 33  
BambooArtifact (class in emodpy.utils), 48  
BambooConnection (class in emodpy.bamboo\_api\_utils), 33  
BaseReporter (class in emodpy.reporters.base), 27  
build\_passed() (emodpy.bamboo\_api\_utils.BuildInfo class method), 35  
BuildArtifacts (class in emodpy.bamboo\_api\_utils), 36  
builder, 51  
BuildInfo (class in emodpy.bamboo\_api\_utils), 35  
BuildPlans (class in emodpy.bamboo\_api\_utils), 39  
BuiltInReporter (class in emodpy.reporters.base), 28

## C

campaign (emodpy.emod\_task.EMODTask attribute), 45

```
campaign() (emodpy.defaults.emod_sir.EMODSir default_filter_fn()
    static method), 25 (emodpy.analyzers.timeseries_analyzer.TimeseriesAnalyzer
campaign() (emodpy.defaults.iemod_default.IEMODDefault method), 24
    method), 26 default_group_fn()
campaign() (emodpy.interventions.emod_empty_campaign.EMODEmptyCampaign default_plot_fn()
    static method), 27 (emodpy.analyzers.timeseries_analyzer.TimeseriesAnalyzer
class_name (emodpy.reporters.base.BuiltInReporter default_select_fn())
    attribute), 28 (emodpy.analyzers.timeseries_analyzer.TimeseriesAnalyzer
class_name (emodpy.reporters.builtin.ReportNodeDemographics method), 24
    attribute), 29 default_select_fn()
clear() (emodpy.emod_campaign.EMODCampaign (emodpy.analyzers.timeseries_analyzer.TimeseriesAnalyzer
    method), 40 method), 24
climate (emodpy.emod_task.EMODTask attribute), 44 demographics (emodpy.emod_task.EMODTask
CLIMATE_BY_DATA (emodpy.emod_file.ClimateModel attribute), 44
    attribute), 43 demographics()
CLIMATE_CONSTANT (emodpy.emod_file.ClimateModel (emodpy.defaults.emod_sir.EMODSir
    attribute), 43 static method), 25
CLIMATE_KOPPEN (emodpy.emod_file.ClimateModel
    attribute), 43 demographics()
CLIMATE_OFF (emodpy.emod_file.ClimateModel attribute), 43
    attribute), 43 DemographicsFiles (class in emodpy.emod_file), 42
ClimateFiles (class in emodpy.emod_file), 43 DENGUE (emodpy.utils.EradicationBambooBuilds
ClimateFileType (class in emodpy.emod_file), 43 attribute), 48
ClimateModel (class in emodpy.emod_file), 43 DENGUE_LINUX (emodpy.utils.EradicationBambooBuilds
config (emodpy.emod_task.EMODTask attribute), 44 attribute), 48
config() (emodpy.defaults.emod_sir.EMODSir config() (emodpy.defaults.iemod_default.IEMODDefault
    static method), 25 dll_file (emodpy.reporters.base.CustomReporter
method), 26 attribute), 28
config() (emodpy.defaults.iemod_default.IEMODDefault config() (emodpy.reporters.builtin.ReportHumanMigrationTracking
    static method), 26 attribute), 32
config() (emodpy.reporters.builtin.ReportHumanMigrationTracking config_file_name (emodpy.emod_task.EMODTask
    attribute), 29 dll_file (emodpy.reporters.custom.MalariaSummaryReport
attribute), 31
    attribute), 45 convert_plugin_reports() (in module dll_file (emodpy.reporters.custom.MalariaSurveyJSONAnalyzer
    emodpy.defaults.ep4.dtk_pre_process), 25 attribute), 32
copy_simulation() (emodpy.emod_task.EMODTask copy_simulation() (emodpy.emod_task.EMODTask
    method), 46 method), 46 dll_file (emodpy.reporters.custom.MalariaTransmissionReport
create_campaign_from_callback() (emodpy.emod_task.EMODTask method), 45 attribute), 32
    attribute), 45 dll_file (emodpy.reporters.custom.Report_TBHIV_ByAge
CustomReporter (class in emodpy.reporters.base), 27 create_campaign_from_callback() (emodpy.emod_task.EMODTask
cut_iterable_to() (in module dll_file (emodpy.reporters.custom.ReportEventCounter
    emodpy.collections_utils), 40 attribute), 31
    attribute), 30
    attribute), 31
deep_del() (in module dll_file (emodpy.reporters.custom.ReportHumanMigrationTracking
    emodpy.collections_utils), 40 attribute), 30
deep_get() (in module dll_file (emodpy.reporters.custom.ReportMalariaFiltered
    emodpy.collections_utils), 40 attribute), 31
deep_set() (in module dll_file (emodpy.reporters.custom.ReportPluginAgeAtInfectionHistogram
    emodpy.collections_utils), 40 attribute), 30
default_ep4_fn() (in module download_artifact_to_file()
    emodpy.emod_task), 44 (emodpy.bamboo_api_utils.BuildArtifacts
    attribute), 37
download_artifacts_to_path() (emodpy.bamboo_api_utils.BuildArtifacts
```

## D

```
data_group_names (emodpy.analyzers.timeseries_analyzer.TimeseriesAnalyzer
    attribute), 24 attribute), 31
deep_del() (in module download_artifact_to_file()
    emodpy.collections_utils), 40 (emodpy.bamboo_api_utils.BuildArtifacts
deep_get() (in module download_artifacts_to_path()
    emodpy.collections_utils), 40 (emodpy.bamboo_api_utils.BuildArtifacts
deep_set() (in module download_artifacts_to_path()
    emodpy.collections_utils), 40 class method), 37
default_ep4_fn() (in module download_artifacts_to_path()
    emodpy.emod_task), 44 (emodpy.bamboo_api_utils.BuildArtifacts
```

```

    class method), 38
download_bamboo_artifacts() (in module emodpy.utils), 49
download_ eradication() (in module emodpy.utils), 50
download_ eradication_exe() (emodpy.bamboo_api_utils.BuildArtifacts class method), 39
download_file() (emodpy.bamboo_api_utils.BambooConnection method), 35
download_from_bamboo_url() (emodpy.bamboo_api_utils.BuildArtifacts class method), 39
download_from_url() (in module emodpy.utils), 50
download_latest_bamboo() (in module emodpy.utils), 49
download_latest_ eradication() (in module emodpy.utils), 49
download_latest_good_Eradication_exe() (emodpy.bamboo_api_utils.BuildArtifacts class method), 38
download_latest_good_schema_json() (emodpy.bamboo_api_utils.BuildArtifacts class method), 38
download_latest_reporters() (in module emodpy.utils), 50
download_latest_schema() (in module emodpy.utils), 50
download_schema_json() (emodpy.bamboo_api_utils.BuildArtifacts class method), 39

```

**E**

```

EMOD_RELEASE (emodpy.utils.EradicationBambooBuilds attribute), 48
EMODCampaign (class in emodpy.emod_campaign), 40
EMODEEmptyCampaign (class in emodpy.interventions.emod_empty_campaign), 27
emodpy module, 23
emodpy.analyzers module, 23
emodpy.analyzers.adult_vectors_analyzer module, 23
emodpy.analyzers.population_analyzer module, 24
emodpy.analyzers.timeseries_analyzer module, 24
emodpy.bamboo module, 32
emodpy.bamboo_api_utils module, 33
emodpy.collections_utils

```

```

    module, 40
emodpy.defaults module, 25
emodpy.defaults.emod_sir module, 25
emodpy.defaults.ep4 module, 25
emodpy.defaults.ep4.dtk_in_process
emodpy.defaults.ep4.dtk_post_process module, 25
emodpy.defaults.ep4.dtk_pre_process module, 25
emodpy.defaults.iemod_default module, 26
emodpy.emod_campaign module, 40
emodpy.emod_file module, 41
emodpy.emod_task module, 44
emodpy.generic module, 26
emodpy.generic.serialization module, 26
emodpy.interventions module, 27
emodpy.interventions.emod_empty_campaign module, 27
emodpy.reporters module, 27
emodpy.reporters.base module, 27
emodpy.reporters.builtin module, 29
emodpy.reporters.custom module, 29
emodpy.utils module, 48
EMODSir (class in emodpy.defaults.emod_sir), 25
EMODTask (class in emodpy.emod_task), 44
EMODTaskSpecification (class in emodpy.emod_task), 47
empty() (emodpy.reporters.base.Reporters property), 28
enable() (emodpy.reporters.base.CustomReporter method), 28
enable_migration() (emodpy.emod_file.MigrationFiles method), 42
enable_serialization() (in module emodpy.generic.serialization), 26
Enabled (emodpy.reporters.base.BuiltInReporter attribute), 28

```

```

Enabled (emodpy.reporters.base.CustomReporter attribute), 27
ensure_logged_in() (emodpy.bamboo_api_utils.BambooConnection method), 34
ERADICATION (emodpy.utils.BambooArtifact attribute), 48
ERADICATION_EXE (emodpy.bamboo_api_utils.BuildArtifacts attribute), 36
eradication_path (emodpy.emod_task.EMODTask attribute), 44
EradicationBambooBuilds (class in emodpy.utils), 48
EradicationPlatformExtension (class in emodpy.utils), 48
experiment, 51
export_spec() (emodpy.bamboo_api_utils.BuildPlans static method), 39

F
FAMILY (emodpy.emod_file.MigrationTypes attribute), 41
filter() (emodpy.analyzers.timeseries_analyzer.TimeseriesAnalyzer method), 24
find_all_artifact_names() (emodpy.bamboo_api_utils.BuildArtifacts class method), 37
find_all_artifacts() (emodpy.bamboo_api_utils.BuildArtifacts class method), 37
find_artifacts() (emodpy.bamboo_api_utils.BuildArtifacts class method), 37
find_artifacts_by_name() (emodpy.bamboo_api_utils.BuildArtifacts class method), 36
find_build_essential_artifacts() (emodpy.bamboo_api_utils.BuildArtifacts class method), 37
find_server() (emodpy.bamboo_api_utils.BambooConnection method), 33
FIXED_RATE_MIGRATION (emodpy.emod_file.MigrationModel attribute), 41
FP (emodpy.utils.EradicationBambooBuilds attribute), 48
FP_LINUX (emodpy.utils.EradicationBambooBuilds attribute), 48
FP_WIN (emodpy.utils.EradicationBambooBuilds attribute), 48
from_default2() (emodpy.emod_task.EMODTask class method), 45
from_dict() (emodpy.reporters.base.BaseReporter method), 27
from_dict() (emodpy.reporters.base.BuiltInReporter method), 28
from_dict() (emodpy.reporters.custom.ReportNodeDemographics method), 31
from_files() (emodpy.emod_task.EMODTask class method), 45

G
gather_assets() (emodpy.emod_file.ClimateFiles method), 43
gather_assets() (emodpy.emod_file.InputFilesList method), 41
gather_assets() (emodpy.emod_file.MigrationFiles method), 42
gather_assets() (emodpy.reporters.base.Reporters method), 28
gather_common_assets() (emodpy.emod_task.EMODTask method), 46
gather_transient_assets() (emodpy.emod_task.EMODTask method), 46

T
TimeseriesAnalyzer (emodpy.utils.EradicationBambooBuilds attribute), 48
GENERIC_LINUX (emodpy.utils.EradicationBambooBuilds attribute), 48
GENERIC_WIN (emodpy.utils.EradicationBambooBuilds attribute), 48
get() (emodpy.emod_task.EMODTaskSpecification method), 47
bamboo_api_url() (emodpy.bamboo_api_utils.BambooConnection method), 34
get_bamboo_url() (emodpy.bamboo_api_utils.BambooConnection method), 34
get_build_info() (emodpy.bamboo_api_utils.BuildInfo static method), 36
get_channel_data()
get_description() (emodpy.emod_task.EMODTaskSpecification method), 47
get_events_at() (emodpy.emod_campaign.EMODCampaign method), 40
get_events_with_name() (emodpy.emod_campaign.EMODCampaign method), 41
get_example_urls() (emodpy.emod_task.EMODTaskSpecification method), 47
get_github_eradication_url() (in module emodpy.utils), 49
get_latest_build()

```

(*emodpy.bamboo\_api\_utils.BuildInfo method*), 36  
**get\_latest\_successful\_build()** (*emodpy.bamboo\_api\_utils.BuildInfo method*), 36  
**get\_model\_files()** (*in module emodpy.bamboo*), 32  
**get\_parameter()** (*emodpy.emod\_task.EMODTask method*), 47  
**get\_plans\_for\_project()** (*emodpy.bamboo\_api\_utils.BuildPlans static method*), 39  
**get\_server\_url()** (*emodpy.bamboo\_api\_utils.BambooConnection method*), 33  
**get\_type()** (*emodpy.emod\_task.EMODTaskSpecification method*), 47  
**get\_version()** (*emodpy.emod\_task.EMODTaskSpecification method*), 47

**H**  
high-performance computing (*HPC*), 51  
HIV (*emodpy.utils.EradicationBambooBuilds attribute*), 48  
HIV\_LINUX (*emodpy.utils.EradicationBambooBuilds attribute*), 48  
HIV\_WIN (*emodpy.utils.EradicationBambooBuilds attribute*), 48

**I**  
IEMODDefault (*class in emodpy.defaults.iemod\_default*), 26  
implicit\_configs (*emodpy.emod\_task.EMODTask attribute*), 45  
initialize () (*emodpy.analyzers.adult\_vectors\_analyzer.AdultVectorsAnalyzer method*), 23  
initialize () (*emodpy.analyzers.population\_analyzer.PopulationAnalyzer attribute*), 24  
initialize () (*emodpy.analyzers.timeseries\_analyzer.TimeseriesAnalyzer attribute*), 24  
InputFilesList (*class in emodpy.emod\_file*), 41  
interval\_years (*emodpy.reporters.custom.ReportPlugin attribute*), 30  
is\_linux (*emodpy.emod\_task.EMODTask attribute*), 45

**J**  
json () (*emodpy.emod\_campaign.EMODCampaign property*), 40  
json () (*emodpy.reporters.base.Reporters property*), 28

**L**  
LAND\_TEMPERATURE (*emodpy.emod\_file.ClimateFileType attribute*), 43

class LINUX (*emodpy.utils.EradicationPlatformExtension attribute*), 48  
load\_files () (*emodpy.emod\_task.EMODTask method*), 45  
load\_from\_dict () (*emodpy.emod\_campaign.EMODCampaign static method*), 40  
load\_from\_file () (*emodpy.emod\_campaign.EMODCampaign static method*), 40  
load\_serialized\_population () (*in module emodpy.generic.serialization*), 26  
load\_session\_cookie () (*emodpy.bamboo\_api\_utils.BambooConnection LOCAL (emodpy.emod\_file.MigrationTypes attribute)*), 41  
logger (*in module emodpy.emod\_task*), 44  
login () (*emodpy.bamboo\_api\_utils.BambooConnection method*), 34  
login () (*in module emodpy.bamboo\_api\_utils*), 40  
login\_session\_exists () (*emodpy.bamboo\_api\_utils.BambooConnection method*), 34

**M**  
make\_api\_get\_request () (*emodpy.bamboo\_api\_utils.BambooConnection method*), 35  
make\_exe\_executable () (*emodpy.bamboo\_api\_utils.BuildArtifacts class method*), 39  
make\_get\_request () (*emodpy.bamboo\_api\_utils.BambooConnection method*), 35  
MALARIA (*emodpy.utils.EradicationBambooBuilds attribute*), 48  
MALARIA\_LINUX (*emodpy.utils.EradicationBambooBuilds attribute*), 48  
MALARIA\_WIN (*emodpy.utils.EradicationBambooBuilds attribute*), 48  
MalariaImmunityReport (*class in emodpy.reporters.custom*), 31  
MalariaSummaryReport (*class in emodpy.reporters.custom*), 31  
MalariaSurveyJSONAnalyzer (*class in emodpy.reporters.custom*), 32  
MalariaTransmissionReport (*class in emodpy.reporters.custom*), 32  
map () (*emodpy.analyzers.adult\_vectors\_analyzer.AdultVectorsAnalyzer method*), 23  
map () (*emodpy.analyzers.population\_analyzer.PopulationAnalyzer method*), 24  
map () (*emodpy.analyzers.timeseries\_analyzer.TimeseriesAnalyzer method*), 25  
merge\_with () (*emodpy.emod\_file.MigrationFiles method*), 42

MigrationFiles (*class in emodpy.emod\_file*), 41  
MigrationModel (*class in emodpy.emod\_file*), 41  
MigrationPattern (*class in emodpy.emod\_file*), 41  
migrations (*emodpy.emod\_task.EMODTask attribute*), 44  
MigrationTypes (*class in emodpy.emod\_file*), 41  
module  
    emodpy, 23  
    emodpy.analyzers, 23  
    emodpy.analyzers.adult\_vectors\_analyzer, 23  
    emodpy.analyzers.population\_analyzer, 24  
    emodpy.analyzers.timeseries\_analyzer, 24  
    emodpy.bamboo, 32  
    emodpy.bamboo\_api\_utils, 33  
    emodpy.collections\_utils, 40  
    emodpy.defaults, 25  
    emodpy.defaults.emod\_sir, 25  
    emodpy.defaults.ep4, 25  
    emodpy.defaults.ep4.dtk\_in\_process, 25  
    emodpy.defaults.ep4.dtk\_post\_process, 25  
    emodpy.defaults.ep4.dtk\_pre\_process, 25  
    emodpy.defaults.iemod\_default, 26  
    emodpy.emod\_campaign, 40  
    emodpy.emod\_file, 41  
    emodpy.emod\_task, 44  
    emodpy.generic, 26  
    emodpy.generic.serialization, 26  
    emodpy.interventions, 27  
    emodpy.interventions.emod\_empty\_campaign, 27  
    emodpy.reporters, 27  
    emodpy.reporters.base, 27  
    emodpy.reporters.builtin, 29  
    emodpy.reporters.custom, 29  
    emodpy.utils, 48

## N

name (*emodpy.reporters.base.CustomReporter attribute*), 27  
name (*emodpy.reporters.custom.MalariaImmunityReport attribute*), 32  
name (*emodpy.reporters.custom.MalariaSummaryReport attribute*), 31  
name (*emodpy.reporters.custom.MalariaSurveyJSONAnalyzer attribute*), 32  
name (*emodpy.reporters.custom.MalariaTransmissionReport attribute*), 32

name (*emodpy.reporters.custom.Report\_TBHIV\_ByAge attribute*), 29  
name (*emodpy.reporters.custom.ReportEventCounter attribute*), 31  
name (*emodpy.reporters.custom.ReportHumanMigrationTracking attribute*), 30  
name (*emodpy.reporters.custom.ReportMalariaFiltered attribute*), 31  
name (*emodpy.reporters.custom.ReportNodeDemographics attribute*), 31  
name (*emodpy.reporters.custom.ReportPluginAgeAtInfectionHistogram attribute*), 30  
NO\_MIGRATION (*emodpy.emod\_file.MigrationModel attribute*), 41  
normalize\_url () (*emodpy.bamboo\_api\_utils.BambooConnection method*), 35

## O

ordered\_levels (*emodpy.analyzers.timeseries\_analyzer.TimeseriesAnalyzer attribute*), 24  
output\_file (*emodpy.analyzers.timeseries\_analyzer.TimeseriesAnalyzer attribute*), 24

## P

parameters (*emodpy.reporters.base.BuiltInReporter attribute*), 28  
parameters (*emodpy.reporters.builtin.ReportHumanMigrationTracking attribute*), 29  
plot\_by\_channel ()  
    (*emodpy.analyzers.timeseries\_analyzer.TimeseriesAnalyzer method*), 25  
PLUGINS (*emodpy.utils.BambooArtifact attribute*), 48  
PopulationAnalyzer (*class in emodpy.analyzers.population\_analyzer*), 24  
pre\_creation ()  
    (*emodpy.emod\_task.EMODTask method*), 46  
Pretty\_Format (*emodpy.reporters.base.BuiltInReporter attribute*), 28  
process\_simulation ()  
    (*emodpy.defaults.iemod\_default.IEMODDefault method*), 26

## R

RAINFALL (*emodpy.emod\_file.ClimateFileType attribute*), 43  
RANDOM\_WALK\_DIFFUSION  
    (*emodpy.emod\_file.MigrationPattern attribute*), 41  
read\_config\_file ()  
    (*emodpy.emod\_file.ClimateFiles method*), 44  
read\_config\_file ()  
    (*emodpy.emod\_file.MigrationFiles method*), 42

```

read_custom_reports_file()           save_credentials()      (in      module
    (emodpy.reporters.base.Reporters     method),      emodpy.bamboo_api_utils), 40
    28
reduce() (emodpy.analyzers.adult_vectors_analyzer.AdultVectorsAnalyzer     SCHEMA (emodpy.utils.BambooArtifact attribute), 48
    method), 23
reduce() (emodpy.analyzers.population_analyzer.PopulationAnalyzer     SERVER_AND_QUEUE (emodpy.bamboo_api_utils.BuildArtifacts
    method), 24
reduce() (emodpy.analyzers.timeseries_analyzer.TimeseriesAnalyzer     attribute), 36
    method), 25
REGIONAL (emodpy.emod_file.MigrationTypes     SESSION (emodpy.emod_file.MigrationTypes attribute), 41
    attribute), 41
RELATIVE_HUMIDITY
    (emodpy.emod_file.ClimateFileType attribute), 43
RELEASE (emodpy.utils.EradicationBambooBuilds     server () (emodpy.bamboo_api_utils.BambooConnection
    attribute), 48
reload_from_simulation()           SESSIONPROPERTY (emodpy.bamboo_api_utils.BambooConnection
    (emodpy.emod_task.EMODTask     attribute), 33
    method), 47
Report_TBHIV_ByAge (class     session_cookie() (emodpy.bamboo_api_utils.BambooConnection
    emodpy.reporters.custom), 29
REPORTER_PLUGINS (emodpy.bamboo_api_utils.BuildArtifacts     property), 33
    attribute), 36
Reporters (class in emodpy.reporters.base), 28
reporters (emodpy.emod_task.EMODTask attribute),
    44
ReportEventCounter (class     in     session_cookie_filename() (emodpy.bamboo_api_utils.BambooConnection
    emodpy.reporters.custom), 31
ReportHumanMigrationTracking (class in     property), 33
    emodpy.reporters.builtin), 29
ReportHumanMigrationTracking (class in     set_all_persisted()
    emodpy.reporters.custom), 30
ReportMalariaFiltered (class     in     (emodpy.emod_file.MigrationFiles method), 42
    emodpy.reporters.custom), 31
ReportNodeDemographics (class     in     set_climate_constant()
    emodpy.reporters.builtin), 29
ReportNodeDemographics (class     in     (emodpy.emod_file.ClimateFiles method), 43
    emodpy.reporters.custom), 30
ReportPluginAgeAtInfectionHistogram (class in     set_command_line()
    in     (emodpy.emod_task.EMODTask static method), 46
    emodpy.reporters.custom), 29
Reports (emodpy.reporters.base.CustomReporter     set_parameter()
    attribute), 27
Reports (emodpy.reporters.custom.ReportHumanMigrationTracking     parameter () (emodpy.emod_task.EMODTask
    attribute), 30
Reports (emodpy.reporters.custom.ReportPluginAgeAtInfectionHistogram     method), 46
    attribute), 30
S
save_bamboo_credentials() (in      module
    emodpy.utils), 49
save_credentials()     simulation_demographics
    (emodpy.bamboo_api_utils.BambooConnection     attribute), 45
    method), 34
simulation_migrations
    (emodpy.emod_task.EMODTask     attribute), 45
SIMPLE_ROUND_TRIPS
    (emodpy.emod_file.MigrationPattern attribute), 41
Stratify_By_Gender
    (emodpy.reporters.builtin.ReportNodeDemographics
```

attribute), 29  
successful\_build\_result()  
(*emodpy.bamboo\_api\_utils.BuildInfo* static  
method), 36

**T**

task, 51  
TBHIV (*emodpy.utils.EradicationBambooBuilds* attribute), 48  
TBHIV\_LINUX (*emodpy.utils.EradicationBambooBuilds* attribute), 48  
TBHIV\_WIN (*emodpy.utils.EradicationBambooBuilds* attribute), 48  
template, 51  
TimeseriesAnalyzer (class in  
*emodpy.analyzers.timeseries\_analyzer*), 24  
to\_dict() (*emodpy.reporters.base.BaseReporter* method), 27  
to\_dict() (*emodpy.reporters.base.BuiltInReporter* method), 28  
to\_dict() (*emodpy.reporters.base.CustomReporter* method), 28  
to\_dict() (*emodpy.reporters.custom.ReportNodeDemographics* method), 31  
TYPHOID (*emodpy.utils.EradicationBambooBuilds* attribute), 48  
TYPHOID\_LINUX (*emodpy.utils.EradicationBambooBuilds* attribute), 48  
TYPHOID\_WIN (*emodpy.utils.EradicationBambooBuilds* attribute), 48

**U**

update\_migration\_pattern()  
(*emodpy.emod\_file.MigrationFiles* method), 42  
update\_parameters()  
(*emodpy.emod\_task.EMODTask* method), 47  
url\_exists() (*emodpy.bamboo\_api\_utils.BambooConnection* method), 33  
use\_embedded\_python  
(*emodpy.emod\_task.EMODTask* attribute), 45

**W**

WAYPOINTS\_HOME (*emodpy.emod\_file.MigrationPattern* attribute), 41  
Windows (*emodpy.utils.EradicationPlatformExtension* attribute), 48  
write\_session\_cookie()  
(*emodpy.bamboo\_api\_utils.BambooConnection* method), 34